

## Clydesdale Cut 18 Specifications and Warranties

$\overline{}$					
(-	Δ	n	Δ	ra	١.
u	•		_	ıu	и.

Description: Cut pile broadloom
Dye Method: Injection dyed
Dye Resolution: 256 dpi

Fiber: Premium Continuous Filament Nylon

Tufted Face Weight: 18 oz. / sq.yd.

Tuft Bind: Exceeds industry standards

Gauge: 1/10<sup>th</sup>
Pile Height: .186 in.

Primary Backing: Woven polypropylene

Secondary Backing: ActionBac

Secondary Backing (optional): KangaTRAC polyurethane cushion Delamination: Exceeds industry standards

Anti-Soil and Stain Protection: Impervion® soil and stain treatment

Antimicrobial Protection: Impervion® mold, mildew, and odor treatment

Broadloom Width: 12'
Origin: U.S.A.

Performance:

Static Electricity: less than 3.5kv (permanent anti-static fiber)

Traffic: Commercial

Indoor Air Quality: Green Label Plus Certified

Flammability:

Radiant Panel: Class I

NBS Smoke Chamber: less than 450

Maintenance:

Spot Cleaning: Spot clean with approved carpet cleaner. Follow

manufacturer recommendations. Vacuum regularly.

Professional Cleaning: Hot water extraction.

Warranties:

20 Year Texture Retention Limited Warranty
20 Year Abrasive Wear Limited Warranty
10 Year Soil and Stain Protection Limited Warranty
Static Protection

Fade Resistance (for indoor use only)
Limited Manufacturer Defects Warranty