

PRODUCT SPECIFICATIONS

- OVERALL ASSEMBLED DIMENSIONS
 HEIGHT: 37.8 CM (14-7/8"). WIDTH: 35.6 CM (14").
- 133 LIGHTS: WARM WHITE, 12 WATT LED RING. WHITE ON/OFF LINE SWITCH LOCATED AS SHOWN. LIFE OF THE LED: 30000 HOURS.
- TRANSFORMER: CUL LISTED, INPUT: 110V. OUTPUT: 24V. 1A.
- METAL RING: ALUMINUM, 1 CM (3/8") X 1.3 CM (1/2") TUBING. 35.6 CM (14") DIA. SHAPED AS SHOWN.
- BASE: PAINTED STEEL, 15.2 CM (6") DIA. x 5 MM (1/4") THICKNESS. FELT PAD INSTALLED ON BOTTOM OF BASE.
- CORD: UL LISTED, MIN 183 CM (6 FT.) LENGTH, 2 CONDUCTORS, WHITE COLOR, COPPER MATERIAL, WIRES MUST BE LEAD FREE.
- LABELS: MANUFACTURING DATE, MODEL # AND COUNTRY OF ORIGIN LABEL ARE PROVIDED.

PACKAGING AND SHIPPING DETAILS

- THE LAMP IS ASSEMBLED FOR SHIPPING. THE WHOLE LAMP IS CAREFULLY WRAPPED IN A PLASTIC BAG AND PLACED SECURELY IN THE INNER PACKING SO IT CAN NOT MOVE AROUND DURING SHIPPING. A SMALL BAG OF SILICA IS INCLUDED IN THE PACKAGE.
- THE CARTON IS MADE OF DOUBLE WALL, CORRUGATED CARDBOARD "A MA A". BROWN IN COLOR. THE INNER PACKING IS DIE—CUT CARDBOARD OR STYROFOAM TO PROTECT AND SECURE THE LAMP AND MUST PASS THE FEDEX AND ISTA—3A DROP TEST REQUIREMENTS.

Light Output (Lumens): 200 LM.

Lumens per Watt (Efficacy): 75 LM/W.

Watts (Measured Power): 2.3 W.

Color Rendering Index (CRI): 70 ~ 80.

Correlated Color Temperature (CCT): 2850~3000K.

Warranty: 30000H.

		_	_	-			 _
7.3	ш	_ 1		1 1		. V I	 v.
	_	_	•		- 1	A	 _

- MODEL LW1010 INSTRUCTIONS ARE TO BE PACKED WITH EACH LAMP. INSTRUCTIONS MUST BE PRINTED CLEARLY ON QUALITY PAPER.
- ALL VISIBLE PARTS MUST MATCH LAMP FINISH UNLESS OTHERWISE SPECIFIED.
- ALL BAGS MUST BE LABELED WITH OFFICIAL "THIS BAG IS NOT A TOY" STATEMENT.
- LAMP MUST REST FLAT ON SURFACE AND NOT ROCK. LAMP MUST PASS AN 8° TILT TEST.
- DIMS OF UNIT BOX: $36.5 \text{ CM} (14-3/8") \text{ LENGTH } \times 18.5 \text{ CM} (7-1/4") \text{ WIDTH } \times 42 \text{ CM} (16-1/2") \text{ HEIGHT. (CUFT.: 1')}$
- DIMS OF MASTER BOX: 75 CM (29-1/2") LENGTH x 58.5 CM (23") WIDTH x 44 CM (17-3/8") HEIGHT. (CUFT.: 6.81') (6 PCS/CTN)
- ☐ NW (UNIT): 2 LBS. GW (UNIT): 4 LBS.
- NW (MASTER): 12 LBS. GW (MASTER): 30 LBS. (6 PCS/CTN)