



US Patent #11,628,698
and 11,660,916

Onemount™ #10001 Instruction Sheet

Disclaimer: The ratings of the Onemount™ System are intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The Onemount™ System consists of two separate parts referred to as the Platform and the Dual Ball. The Platform included with this kit is rated weight carrying up to 14,000 lbs. GVWR (gross vehicle weight rating) and up to 1,400 lbs. tongue weight.

The Dual Ball is rated up to 10,000 lbs. GVWR/1000 lbs. tongue weight when using the 2" ball and 14,000 lbs. GVWR/1,400 lbs. tongue weight when using the 2-5/16" ball.



WARNING: Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

1. Install the Platform mount into the 2" receiver hitch of your vehicle and secure it with the included bent hitch pin and clip. Always secure the hitch pin with a clip unless a locking device is being used.
2. Determine which hitch ball size to be used is 2" or 2-5/16". Once the approximate height for the ball installation has been determined, mate the dual ball to the platform by inserting the supplied clevis pins through the holes that line up with the holes in the platform. Secure the pins with the included cotter pins. *A patented pre-installed rubber bumper is installed in the dual ball to help prevent excessive rattles. During installation, some force may be required to push the dual ball in to position to allow the clevis pins to mate correctly.*

Note: The supplied pins are specifically engineered for the Onemount™ System. If replacement pins are needed, they must be replaced with original factory Onemount™ pins. **WARNING: Use of any pin other than of Onemount™ manufacture could be a serious safety hazard and will void the warranty.**

Notes:

- Prior to towing, check to make sure that the pins are secured into place with cotter pins.
- Never hook up trailer safety chains to the Onemount™ System.
- The function of the pre-installed rubber bumper is to reduce rattles only.

Warning: Please ensure that the safety chains operate freely around the Onemount™ System and don't become entangled in the Platform or Dual Ball.