

Model 65 UL Listed Wire Combinations Strip Wires 1/2 in.
UL File Number E5238

Copper to Aluminum wire (do not use on Aluminum to Aluminum)

600 Volt Maximum. For use with solid or stranded combinations



1 #10 AL w/1 or 2 #12 CU			
1 #10 AL w/1 or 2 #14 CU			
1 #10 AL w/1 or 2 #16 CU			
1 #10 AL w/1 or 2 #18 CU			
2 #10 AL sol. w/1 #12 CU			
2 #10 AL sol. w/1 #14 CU			
2 #10 AL sol. w/1 #16 CU			
2 #10 AL sol. w/1 #18 CU			
1 #12 AL sol. w/1 or 2 #10 CU			
1 #12 AL str. w/1 or 2 #10 CU sol.			
1 #12 AL w/1 or 2 #12 CU			
1 #12 AL w/1 or 2 #14 CU			
1 #12 AL w/1 or 2 #16 CU			
1 #12 AL w/1 or 2 #18 CU			
2 #12 AL sol. w/1 #10 CU			
2 #12 AL sol. w/1 #12 CU			
2 #12 AL sol. w/1 #14 CU			
2 #12 AL sol. w/1 #16 CU			
2 #12 AL sol. w/1 #18 CU			