SAFETY DATA SHEET



1. Identification

Product identifier KILZ Porch & Patio Low-Lustre Enamel Floor Paint - Slate Gray

Other means of identification

Product number L5737

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Masterchem Industries LLC

3135 Old Highway M Imperial, MO 63052-2834

 Telephone
 636-942-2510

 Emergency telephone
 +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Category 2

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	3 - 7
Carbon black	1333-86-4	0.1 - 1
Diuron	330-54-1	0.1 - 1

Composition commentsAll concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard

KILZ Porch & Patio Low-Lustre Enamel Floor Paint - Slate Gray
952305 Version #: 02 Revision date: 16-June-2020 Issue date: 13-March-2020

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse mouth. Get medical attention if symptoms occur.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Most important

General information

symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware

of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Do not use water jet as an extinguisher, as this will spread the fire.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table 7-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	

KILZ Porch & Patio Low-Lustre Enamel Floor Paint - Slate Gray

Components	s for Air Contaminants (29 CFR 1910 Type	Value	Form	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 C Components	FR 1910.1000) Type	Value	Form	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.	
•		15 mg/m3	Total dust.	
		50 mppcf	Total dust.	
		15 mppcf	Respirable fraction.	
US. ACGIH Threshold Lim	nit Values			
Components	Туре	Value	Form	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.	
Diuron (CAS 330-54-1)	TWA	10 mg/m3		
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3		
US. NIOSH: Pocket Guide		Value		
Components	Type			
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3		
Diuron (CAS 330-54-1)	TWA	10 mg/m3		
ogical limit values	No biological exposure limits noted for the ingredient(s).			
ropriate engineering trols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.			
-	s, such as personal protective equip			
Eye/face protection	Wear safety glasses with side shiel	ds (or goggles).		
Skin protection Hand protection	Wear appropriate chemical resistar	nt gloves.		
Skin protection Other	Wear appropriate chemical resistar	nt clothina.		
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
eral hygiene siderations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

9. Physical and chemical properties

Appearance

Physical state
Form
Color
Gray.

Odor
Slight.
Odor threshold
DH
7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point Not applicable
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.

Relative density 1.18

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 50 - 140 KU (25 °C)

Other information

Density9.85 lbs/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

VOC 17 g/l (including water) (Material) 49 g/l (excluding water) (Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

KILZ Porch & Patio Low-Lustre Enamel Floor Paint - Slate Gray

952305 Version #: 02 Revision date: 16-June-2020 Issue date: 13-March-2020

Components Species Test Results

Carbon black (CAS 1333-86-4)

Acute Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 8000 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)

ZB Possibly carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7)

ZB Possibly carcinogenic to humans.

NTP Report on Carcinogens

Carbon black (CAS 1333-86-4) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium hydroxide (CAS 1336-21-6) Listed.
Diuron (CAS 330-54-1) Listed.
Zinc oxide (CAS 1314-13-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard Carcinogenicity

categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)

Carbon black (CAS 1333-86-4)

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Ammonium hydroxide (CAS 1336-21-6)

Carbon black (CAS 1333-86-4)

Diuron (CAS 330-54-1)

Mildewcide (CAS 55406-53-6)

952305 Version #: 02 Revision date: 16-June-2020 Issue date: 13-March-2020 6 / 7

Titanium dioxide (CAS 13463-67-7) Zinc oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium hydroxide (CAS 1336-21-6)

Carbon black (CAS 1333-86-4)

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Carbon black (CAS 1333-86-4)

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

Zinc oxide (CAS 1314-13-2)

16. Other information, including date of preparation or last revision

Issue date13-March-2020Revision date16-June-2020

Version # 02

Further information HMIS® is a registered trade and service mark of the ACA.

G - Safety Glasses, Gloves, Vapor Respirator

HMIS® ratings Health: 0*

Flammability: 0 Physical hazard: 0 Personal protection: G

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Masterchem Industries LLC cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

KILZ Porch & Patio Low-Lustre Enamel Floor Paint - Slate Gray

SDS US