

Safety Data Sheet

(GF.006.01)

No: R1.02.359.00 [ENG]

Date of Issued : Dec 06th 2024

Copy No:



SANLEX WOOD COATING

Category : NC Sanding Sealer

Color : Solid Color

1. Identification of substance/mixture

Product Name : SANLEX WOOD COATING NC SANDING SEALER
WHITE 1131, BLUE VINTAGE INDIGO 2276, NAVY
BLUE 2277, DUSTY GREEN 4126, GREY WASH 4512,
GREY SHW 4513, BLACK 5021, NCSWC 7118
BLEACH YELLOW

Recommended use : Paint for Industrial and/or professional use only

Manufacturer or supplier's details : PT. RAJAWALI HIYOTO
Jl. Industri II / 8, Lewigajah-Cimahi
Bandung, Indonesia
Tel:62-22-6032344-6032348
Fax : 62-22-6012878

Emergency telephone number : 62-22-6032344-6032348

2. Hazards Identification

Classification of the substance or mixture	Flammable liquids	Category 2
	Specific target organ toxicity (repeated exposure)	Category 2
	Specific target organ toxicity (single exposure)	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Aspiration Hazard	Category 1
	Chronic aquatic toxicity	Category 2

GHS Label element
Hazard statement : Flammable liquid and vapor
Causes skin and eye irritation
May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Toxic to aquatic life with long lasting effect

Dilarang menggandakan dokumen ini tanpa seijin pihak yang berwenang Informasi diatas diberikan atas pengetahuan terbaik kami berdasarkan test laboratorium. Apabila terjadi penyimpangan di lapangan, maka kami tidak dapat memberi jaminan karena biasanya pemakaian cat diluar kontrol kami. Informasi diatas dapat ubah sewaktu - waktu tanpa pemberitahuan terlebih dahulu.

Do not copy this document without permission from Document Controller. This information is presented with best our knowledge and under laboratory test. This information can be changed without prior notice.

PT. RAJAWALI HIYOTO

Jl. Industri II No. 8 Lewigajah
Cimahi - Bandung 40533, Indonesia
Phone. +62 22 603 2348, +62 22 603 2344,
Fax +62 22 603 8381



www.hiyoto.com

Safety Data Sheet

(GF.006.01)

No: R1.02.359.00 [ENG]

Date of Issued : Dec 06th 2024

Copy No:



Precautionary Statements : Wash face, hands and any exposed skin thoroughly after handling
Use only in well-ventilated area

Pictogram : 

Other hazards : None known

3. Composition/information on ingredients

Alkyd resin, Nitrocelulose, Solvent mix: Aromatic Hydrocarbon, Ester, glycol ether. Anorganic Pigment, Organic Pigment

4. First Aid Measures

Description of first aid measures

Inhalation : Remove to fresh air
Skin contact : Wash off with soap and plenty of water
Eye contact : Immediately flush with plenty of water. If symptoms persist, seek medical advice.
Ingestion : Rinse mouth with water. Do not induce vomiting. Get medical aid

5. Fire-fighting Measures

Flammable properties : Flammable, may be ignited by heat, sparks or flames.
Suitable extinguishing media : Foam, Dry chemical, or Carbon dioxide (CO₂)
Specific hazards arising from the substance : None known
Special protective equipment and fire precautions for fire-fighter : Wear self-contained breathing apparatus and protective suit.

Dilarang menggandakan dokumen ini tanpa seijin pihak yang berwenang Informasi diatas diberikan atas pengetahuan terbaik kami berdasarkan test laboratorium. Apabila terjadi penyimpangan di lapangan, maka kami tidak dapat memberi jaminan karena biasanya pemakaian cat diluar kontrol kami. Informasi diatas dapat ubah sewaktu - waktu tanpa pemberitahuan terlebih dahulu.

Do not copy this document without permission from Document Controller. This information is presented with best our knowledge and under laboratory test. This information can be changed without prior notice.

PT. RAJAWALI HIYOTO

Jl. Industri II No. 8 Leuwigajah
Cimahi - Bandung 40533, Indonesia
Phone. +62 22 603 2348, +62 22 603 2344,
Fax +62 22 603 8381



www.hiyoto.com

Safety Data Sheet

(GF.006.01)

No: R1.02.359.00 [ENG]

Date of Issued : Dec 06th 2024

Copy No:



6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	: Do not walk through spilled material. Wear personal protection equipment.
Environmental precautions	: Prevent spilled material from entering soil, surface water, drains or sewers.
Methods and material for containment and cleaning up	: Take up mechanically and dispose of according to local.state/federal regulations. For small amounts: absorb with absorbent material (e.d earth, sand). For larger amounts pump into suitable containers.

7. Handling and Storage

General information	: Mix homogen before use
Precautions for safe handling	: Use personal protection equipment. Avoid contact with eyes and skin. Avoid breathing vapors or mists.
Conditions for safe storage	: Keep container tightly closed. Store in dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.

8. Exposure control/Personal protection

Engineering Controls	: Ensure adequate ventilation, especially in confined areas
Personal protective equipment	
Respiratory protection	: Use appropriate respiratory protection equipment
Hand protection	: Protective gloves made of butyl or nitrile rubber
Eyes protection	: Safety glasses
Skin and body protection	: Antistatic footwear, Wear fire resistant or flame retardant clothing
Hygiene measures	: When using do not eat, drink or smoke. when handling. Wash hands before breaks and at the end of workday.

9. Physical and chemical properties

Physical state/form	: Viscous liquid
Colour	: 7 Solid Color
Odour	: Characteristic

Dilarang menggandakan dokumen ini tanpa seijin pihak yang berwenang Informasi diatas diberikan atas pengetahuan terbaik kami berdasarkan test laboratorium. Apabila terjadi penyimpangan di lapangan, maka kami tidak dapat memberi jaminan karena biasanya pemakaian cat diluar kontrol kami. Informasi diatas dapat ubah sewaktu - waktu tanpa pemberitahuan terlebih dahulu.

Do not copy this document without permission from Document Controller. This information is presented with best our knowledge and under laboratory test. This information can be changed without prior notice.

PT. RAJAWALI HIYOTO

Jl. Industri II No. 8 Leuwigajah

Cimahi - Bandung 40533, Indonesia

Phone. +62 22 603 2348, +62 22 603 2344,

Fax +62 22 603 8381



www.hiyoto.com

Safety Data Sheet

(GF.006.01)

No: R1.02.359.00 [ENG]

Date of Issued : Dec 06th 2024



Copy No:

Odour Threshold	: No data available
pH	: Not applicable
Melting point	: No data available
Boiling point	: No data available
Flammability	: No data available
Flash point	: No data available
Evaporation rate	: No data available
Vapor pressure	: No data available
Density	: 0.91 – 1.13 g/cm ³
Water solubility	: Insoluble
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	: 50 – 90 KU

10. Stability and Reactivity

Chemical stability	: Stable under normal conditions
Possibility of hazardous reactions	: No data available
Condition to avoid	: Heat, flames and sparks
Incompatible materials	: Strong oxidizing agent
Hazardous decomposition products	: None expected

11. Toxicological Information

Toxicological information on product : No data available

12. Ecological Information

Ecotoxicity	: No data available
Persistency and degradability	: No data available
Bioaccumulative potential	: No data available
Mobility in soil	: No data available
Other adverse effects	: No data available

13. Disposal consideration

Dilarang menggandakan dokumen ini tanpa seijin pihak yang berwenang Informasi diatas diberikan atas pengetahuan terbaik kami berdasarkan test laboratorium. Apabila terjadi penyimpangan di lapangan, maka kami tidak dapat memberi jaminan karena biasanya pemakaian cat diluar kontrol kami. Informasi diatas dapat ubah sewaktu - waktu tanpa pemberitahuan terlebih dahulu.

Do not copy this document without permission from Document Controller. This information is presented with best our knowledge and under laboratory test. This information can be changed without prior notice.

PT. RAJAWALI HIYOTO

Jl. Industri II No. 8 Leuwigajah

Cimahi - Bandung 40533, Indonesia

Phone. +62 22 603 2348, +62 22 603 2344,

Fax +62 22 603 8381



www.hiyoto.com

Safety Data Sheet

(GF.006.01)

No: R1.02.359.00 [ENG]

Date of Issued : Dec 06th 2024

Copy No:



The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Empty containers should be recycled or disposed through an approved waste management facility

14. Transport Information

UN number	:	UN1263
UN proper shipping name	:	Paint
Transport hazard class	:	3
Packing group	:	III

15. Regulatory information

Safety, health, and environmental regulation for the substance:

National and local regulation must be observed

For information on labelling please refer to section 2 of this document

16. Other information

Date of issued : 06-12-2024

The information contained herein is based on the present state of our knowledge and does not therefore guarantee certain properties. Recipients of product must take responsibility for observing existing laws. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data is current prior to using the product.

Dilarang menggandakan dokumen ini tanpa seijin pihak yang berwenang Informasi diatas diberikan atas pengetahuan terbaik kami berdasarkan test laboratorium. Apabila terjadi penyimpangan di lapangan, maka kami tidak dapat memberi jaminan karena biasanya pemakaian cat diluar kontrol kami. Informasi diatas dapat ubah sewaktu - waktu tanpa pemberitahuan terlebih dahulu.

Do not copy this document without permission from Document Controller. This information is presented with best our knowledge and under laboratory test. This information can be changed without prior notice.

PT. RAJAWALI HIYOTO

Jl. Industri II No. 8 Leuwigajah

Cimahi - Bandung 40533, Indonesia

Phone. +62 22 603 2348, +62 22 603 2344,

Fax +62 22 603 8381



www.hiyoto.com