Product Features:

Extra thick LED light Touch switch with memory Touch switch dim function Anti-fog pad

LED Mirror



Series : REJSBM2432VCSKXXX

Size: W:24"*H:32"* D:1.3" SKU: DTG-3224M3ZK1

PAGE 1/7



For easy and safe installation, please refer to the following:

Read all instructions thoroughly before installing the enclosed product. Read and take note of all safety, care and maintenance information.

PLEASE KEEP THIS INSTRUCTION MANUAL FOR FUTURE REFERENCE DURING PRODUCT OPERATION AND MAINTENANCE.





WARNING AND SAFETY INSTRUCTIONS

Before assembling your LED Lighted Mirror fixture, please make sure that you carefully read through this instruction sheet, refer back to them during installation to ensure your product is fitted safely and correctly. Keep these instructions for future use.

WARNING Risk of Fire and Electric Shock

•All fittings must be installed in accordance with current IEE wiring regulations. If in doubt, consult a qualified electrician.

•Switch off the electrical supply at the main circuit board BEFORE installation and maintenance.

•Suitable for indoor use only. This product should be positioned well away from curtains and fabrics. Never cover the mirror.

•Regularly check the cord, the transformer and all other parts for damage, if any part is damaged the product should not be used.

INSTALLATION SAFETY

•Inspect the product immediately upon receipt for the transit damage or missing parts. Handle the product with care and protect against knocks to all sides and edges of the glass.

•Ensure there are no hidden pipes or cables in the wall before drilling.

•Wear suitable eye protection when drilling. Take care if drilling on tiled surfaces in case the drill slips.

CAUTION

The light source of this product is non-changeable light diodes (LED). Do not disassemble the product, as the light diodes can cause damage to the eyes.

NOTE: The important safeguards and instructions that appear in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors that can't be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture. Do not install this fixture in hazardous locations.



PAGE 3/7

CHECK PRODUCT LIST AFTER

OPENING THE PACKAGE

- •LED Lighted Mirror
- Installation Manual
- •Z-bar
- •REJSBM2432VCSKXXX-Wall Mounting Screws
- •REJSBM2432VCSKXXX-Drywall Anchor
- -4pcs (One as a spare part)

- -1pcs

- -1pcs

- -1pcs

- -4pcs (One as a spare part)
- -5pcs (One as a spare part)



(TOOLS YOU MAY NEED)

Series:

REJSBM2432VCSKXXX

Size: W610XH812MM



* All diagrams are for reference only. All model dimensions and proportions position will vary.

PRODUCT DESCRIPTION & INFORMATION

Model: REJSBM2432VCSKXXX DTG-3224M3ZK1



PAGE 4/7

WELLFOR

INSTALLATION PROCESS

WELLFOR





According to actual needs) (According to actual needs)

Hardwire Supported(UL Listed)



Step 1:

Use an I-Beam level to mount the included mounting bracket with 3 screws (Use anchor when it's installed on drywall, concrete or tile surface). **Step 2:**

Step 2:

Make sure the circuit breaker for the power source of the mirror is off. Then connect the neutral (White), hot (black) and ground (copper wire or Green) wire between the mirror and the junction box.

Step 3:

Hang the mirror with desired placement by mirror Z-bar on to the mounting bracket.

PAGE 5/7

Warning: Always switch off the electrical supply at the mains during installation and maintenance.

Do not switch on the electrical supply at the mains until the end of the installation.

For customer support please call 626.708.1381 weekdays 9:00 to 6:00 PST, or by email: service@wellfor.com. For more information: www.wellfor.com



PAGE 6/7



Button 1:

First short press , anti-fog function works . Second short press , anti-fog function stops . The two operations loop in turn .

Button 2:

Short press (< 1 second) the LED light switch button to turn on / off the LED lamp. Long press (> 1 second) the button to adjust the brightness. When the LED is on, long press the button to activate dimming. The LED brightness changes in loop from 100% to 5%, or from 5% to 100% on second press.

Scenario 1 🕑 (Wall Switch)

By doing so, the mirror is now bridged to the wall switch. In order to turn on the mirror, the wall switch needs to be on. The touch switch can be used to turn on the LED mirror and anti-fog pad. The mirror shuts down once the wall switch is flipped to OFF.



Do not try this way as it will damage the LED driver.



WELLFOR



THANK YOU FOR CHOOSING US.

PAGE 7/7