

JOB NAME:

CONTRACTOR:

DATE:

## WIRE COIL COLLATION FOR FRAMING NAILS

### TYPES

Smooth




Ring



Spiral



**PROFIT**



### FUNCTION

For general construction, framing, sub-flooring, roof sheathing, decks, fences, pallets, boxes, and crates  
Fits most 15° wire coil framing nailers

### FEATURES

Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)  
Smooth Shanks provide lower withdrawal strength when compared to ring shanks and spiral shanks  
Ring Shanks are deformed to have repeated ridges to increase withdrawal strength  
Spiral Shanks are designed to ease installation into hardwoods and still provide improved withdrawal strength

### CORROSION

Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards  
Brite finishes offer little to no corrosion protection

### CAUTION



Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener  
All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer

| TECHNICAL | Length x Dia | Penny Length | Gauge (W&M) | Head Diameter | Deformation Length, MIN | Nails per Coil | ASTM F1667 Bend Yield* |
|-----------|--------------|--------------|-------------|---------------|-------------------------|----------------|------------------------|
|           | 1-3/4 x .099 | -            | 12.5        | Ø 0.250 in    | 1.00 in                 | 250            | 100,000 psi            |
|           | 2 x .099     | 6d           | 12.5        | Ø 0.250 in    | 1.13 in                 | 250            | 100,000 psi            |
|           | 2 x .113     | 6d           | 11.5        | Ø 0.266 in    | 1.13 in                 | 250            | 100,000 psi            |
|           | 2-1/4 x .099 | 7d           | 12.5        | Ø 0.250 in    | 1.13 in                 | 250            | 100,000 psi            |
|           | 2-3/8 x .113 | -            | 11.5        | Ø 0.266 in    | 1.25 in                 | 250            | 100,000 psi            |
|           | 2-1/2 x .113 | 8d           | 11.5        | Ø 0.266 in    | 1.25 in                 | 250            | 100,000 psi            |
|           | 2-1/2 x .131 | 8d           | 10.25       | Ø 0.281 in    | 1.25 in                 | 250            | 100,000 psi            |
|           | 3 x .120     | 10d          | 11          | Ø 0.281 in    | 1.50 in                 | 250            | 100,000 psi            |
|           | 3 x .131     | 10d          | 10.25       | Ø 0.281 in    | 1.50 in                 | 250            | 100,000 psi            |
|           | 3-1/4 x .120 | 12d          | 11          | Ø 0.281 in    | 1.50 in                 | 250            | 100,000 psi            |
|           | 3-1/4 x .131 | 12d          | 10.25       | Ø 0.281 in    | 1.50 in                 | 250            | 100,000 psi            |
|           | 3-1/2 x .131 | 16d          | 10.25       | Ø 0.281 in    | 1.50 in                 | 250            | 100,000 psi            |

\* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

# WIRE COIL COLLATION FOR FRAMING NAILS

## TYPES

Smooth



Ring



Spiral



**PROFIT**



| PRODUCT | Size         | Box Count<br>QTY | Brite<br>sku | EG<br>sku | HDG<br>sku | 305 SS<br>sku | 316 SS<br>sku |
|---------|--------------|------------------|--------------|-----------|------------|---------------|---------------|
| Smooth  | 2 x .113     | 3000             | 616633       | -         | -          | -             | -             |
| Smooth  | 2-3/8 x .113 | 3000             | 616653       | -         | 616852     | -             | -             |
| Smooth  | 2-1/2 x .113 | 3000             | -            | -         | 616850     | -             | -             |
| Smooth  | 2-1/2 x .131 | 2500             | 616655       | -         | -          | -             | -             |
| Smooth  | 3 x .120     | 2500             | 616673       | -         | 616870     | -             | -             |
| Smooth  | 3 x .120     | 4000             | 616674       | -         | -          | -             | -             |
| Smooth  | 3 x .120     | 4500             | 616675       | -         | -          | -             | -             |
| Smooth  | 3 x .131     | 2500             | 616670       | -         | -          | -             | -             |
| Smooth  | 3-1/4 x .120 | 2500             | 616690       | -         | 616890     | -             | -             |
| Smooth  | 3-1/4 x .131 | 2500             | 616693       | -         | -          | -             | -             |
| Ring    | 2 x .113     | 3000             | 616433       | -         | -          | -             | -             |
| Ring    | 2-3/8 x .113 | 3000             | 616453       | -         | 634151     | -             | -             |
| Ring    |              | 4500             | 616455       | -         | -          | -             | -             |
| Ring    | 2-1/2 x .131 | 2500             | 616463       | -         | -          | -             | -             |
| Ring    | 3 x .120     | 2500             | 616473       | -         | 634171     | -             | -             |
| Ring    | 3 x .131     | 2500             | 616479       | -         | -          | -             | -             |
| Ring    | 3-1/4 x .120 | 2500             | -            | -         | 634181     | -             | -             |
| Ring    | 3-1/2 x .131 | 2500             | -            | -         | 634191     | -             | -             |
| Spiral  | 1-3/4 x .099 | 9000             | 614110       | -         | -          | -             | -             |
| Spiral  | 2 x .099     | 9000             | 614130       | -         | -          | -             | -             |
| Spiral  | 2-1/4 x .099 | 4500             | 614151       | -         | -          | -             | -             |
| Spiral  |              | 9000             | 614140       | -         | -          | -             | -             |