



# GR2540 Single Tank Compressor With Wheels

Featuring a 2.5 HP motor, an oil splash pump, roll cage design, and 10 inch (25.4 cm) pneumatic tires, the Grip-Rite GR2540 is the perfect combination of toughness and portability. Combine that with the air capacity to keep the fastest contractor going all day, the GR2540 is the last compressor you will ever need.

### Features include:

- ☑ Locking pull-out handle provides leverage for maximum mobility
- ☑ 10 inch (25.4 cm) pneumatic tires for tough terrain
- ☑ Recessed gauges, roll cage design
- ☑ Electric, direct drive, oil splash pump
- ☑ 3450 RPM motor
- ☑ Heavy duty pump features a cast iron cylinder
- ☑ Overload protection with manual reset
- ☑ Initial oil fill included
- ☑ 12-month warranty



### Specifications:

HP (peak)	Tank Capacity (gallons)	Lubrication	Draw (amps)	On/Off PSI	CFM @90 PSI	Max PSI	Pump Up (seconds)	Recovery (seconds)	Height (inches)	X Length (inches)	X Width (inches)	Weight (pounds)
2.5	4.0	Oil	14	110/150	4.5	150	77	19	20	x 23.6	x 22	88



Distributed by/Distribuido por/Imported by/Importé par:

**PRIME SOURCE**<sup>®</sup>  
BUILDING PRODUCTS, INC.  
and  
BUILDING PRODUCTS CANADA CORPORATION  
*are Tochu Companies*

Carrollton, Texas 75006 USA  
www.primesourcebp.com

800-676-7777 - USA  
866-512-1418 - Canada  
www.grip-rite.com

© 2007, PrimeSource Building Products, Inc.

06/2007  
GRCSS2540



# GR2540

## Compresor de depósito individual con ruedas

El GR2540 de Grip-Rite con motor de 2.5 HP, bomba de salpicaduras de aceite, diseño de jaula de vuelco y neumáticos de 10 pulgadas (25.4 cm), es la combinación perfecta de resistencia y portabilidad. Combine eso con la capacidad de aire para mantener ocupado todo el día al contratista más rápido. El GR2540 es el último compresor que va a necesitar.

### Incluye las siguientes características:

- ☑ Asa de tracción de traba que permite una movilidad máxima
- ☑ Ruedas y neumáticos de 10 pulgadas (25.4 cm) para terreno irregular
- ☑ Medidores empotrados, diseño de caja de vuelco
- ☑ Bomba eléctrica de mando directo lubricada por salpicadura de aceite
- ☑ Motor de 3450 rpm
- ☑ Bomba de servicio pesado con cilindro de fundición de hierro
- ☑ Protección contra sobrecarga con reajuste manual
- ☑ Llenado de aceite inicial incluido
- ☑ Garantía limitada de 12 meses



### Especificaciones:

HP (máx.)	Capacidad del depósito (galones)	Lubricación	Toma (amp)	PSI On/Off	CFM @90 PSI	PSI máx.	Bombeo (segundos)	Recuperación (segundos)	Altura (pulgadas)	X Longitud (pulgadas)	X Ancho (pulgadas)	Peso (libras)
2.5	4.0	Aceite	14	110/150	4.5	150	77	19	20	x 23.6	x 22	88



Distributed by/Distribuido por/Imported by/Importé par:

**PRIME SOURCE**<sup>®</sup>  
 BUILDING PRODUCTS, INC.  
 and  
 BUILDING PRODUCTS CANADA CORPORATION  
 are Itochu Companies

Carrollton, Texas 75006 USA  
[www.primesourcebp.com](http://www.primesourcebp.com)

800-676-7777 - USA  
 866-512-1418 - Canada  
[www.grip-rite.com](http://www.grip-rite.com)

© 2007, PrimeSource Building Products, Inc.

06/2007  
 GRCSS2540