

**#1** *BRANDED*  
ENGINE  
PROTECTION\*

# Prestone®

trusted quality since 1927

## **50/50 PREDILUTED ANTIFREEZE/COOLANT**

- ✓ **COR-GUARD™** STOPS THE SPREAD OF CORROSION
- ✓ DELIVERS LONGER ENGINE LIFE
- ✓ GUARANTEED FOR ALL VEHICLES  
(AMERICAN/ASIAN/EUROPEAN)

**DO NOT ADD WATER**



P-5872



**5X More Effective**  
AT PROTECTING AGAINST CORROSION†

**WARNING:** HARMFUL OR FATAL IF SWALLOWED.  
Read carefully other cautions on back panel.

**1 GAL (3.78 L)**



Visit our site or call for specific  
guarantee requirements and limitations.  
[www.prestone.com/lifetimeguarantee](http://www.prestone.com/lifetimeguarantee)  
1-888-269-0750

Prestone® 50/50 Prediluted Antifreeze/Coolant is the convenient way to top off your car's cooling system with the superior protection of Prestone antifreeze. Prestone's patented COR-GUARD™ corrosion inhibitors, protect against corrosion and helps rejuvenate your car or light duty truck's tired existing antifreeze. This ready-to-use solution provides your car with the enhanced COR-GUARD™ inhibitor package and patented Prestone formulation that prevents corrosion and helps your engine run longer. Use Prestone to keep today's sophisticated cooling system running efficiently.

- All makes, all models of ANY car or light duty truck
- Works with ANY color antifreeze
- Will NOT void vehicle manufacturer's warranty
- Up to 5 years or 150,000 miles of protection\*\*

\*Prestone is the number one selling Antifreeze/Coolant brand in North America.  
\*\*With a complete flush and fill per manufacturers' recommendations.

PROTECTION	FREEZE-UP Protection	BOIL-OVER Protection†	CORROSION Protection
50/50 PREDILUTED Antifreeze/Coolant	-34° F	+265° F	Meets ASTM D3306 and ASTM D4985

† Using a 15 lb. pressure cap in good condition

**! WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**WARNING:** Contains ethylene glycol (107-21-1), diethylene glycol (111-46-6), water (7732-18-5), and proprietary inhibitors.

**DO NOT** drink antifreeze or solution. Do not store in open or unlabeled containers. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists. Solution is poisonous to animals.

**IF SWALLOWED, CALL A POISON CENTER OR GO TO A HOSPITAL EMERGENCY ROOM IMMEDIATELY.** If inhaled, move to fresh air. Seek medical attention if symptoms persist. In case of contact, wash with water.

**KEEP OUT OF REACH OF CHILDREN AND PETS**

# Prestone®

trusted quality since 1927

## 50/50 PREDILUTED ANTIFREEZE/COOLANT

**CAUTION: DO NOT OPEN THE COOLING SYSTEM WHEN THE ENGINE IS HOT.** Refer to service manual for any special cooling system service instructions. After use, please tighten child-resistant cap and wash hands.

†Based on testing vs. the leading branded competitor.

### Top Off:

- ✓ Requires 1 gallon of Prestone 50/50
- ✓ Fill overflow tank to max level to rejuvenate your existing antifreeze and protect against corrosion.



### Drain and Fill:

- ✓ Requires 2 gallons of Prestone 50/50
- ✓ Refresh system to help stop the spread of corrosion and protect against freeze-up and boil-over
- ✓ With cool engine, open drain valve to empty and refill to indicated level



For more information on how to flush and fill your system, scan this code or visit our website  
[www.prestone.com](http://www.prestone.com)

**DISPOSING OF USED ANTIFREEZE/COOLANT:** Dispose of contents and containers in accordance with local and national regulations.

## Prestone®

PRODUCTS CORPORATION

69 Eagle Road, Danbury, CT 06810  
AF2100 SDS 508 P-5872  
Visit [WWW.PRESTONE.COM](http://WWW.PRESTONE.COM)

Questions? Call 1-888-269-0750

©2018 Prestone Products Corporation

Made in the U.S.A. from foreign and domestic material  
Patents: [Prestone.com/patents](http://Prestone.com/patents)



Prop65 Warning:  
[www.gov](http://www.gov)  
Warning in box:

13pt  
8pt  
11pt