



## MAGNOLIA HOME BY JOANNA GAINES® CHALK SPRAY PAINT



### PRODUCT INFORMATION

Magnolia Home By Joanna Gaines® Chalk Spray Paint features an enhanced formulation that combines paint and primer in a single can, delivering a premium, durable ultra matte finish. Designed for both indoor and outdoor use, this product can be used on wood, metal, plastic, cast stone and wicker. The matte finish could be distressed and further enhanced with Magnolia Home by Joanna Gaines Clear or Dark Sealing wax. The comfort tip delivers a superior spray experience that fights finger fatigue so you can create a smooth finish every time.

### WHERE TO USE

Use on properly prepared surfaces such as:

- Wood
- Metal
- Plastic<sup>1</sup>
- Cast Stone
- Wicker

**COLOR AND SHEEN ON THE CAP IS REPRESENTATIVE OF THE PRODUCT.** Not for touch-up on surfaces previously painted with MAGNOLIA CHALK STYLE PAINT.

### PRODUCT SPECIFICATIONS

**M106247 MAGNOLIA HOME BY JOANNA GAINES®**

Chalk Spray Paint Shiplap

**M106647 MAGNOLIA HOME BY JOANNA GAINES**

Chalk Spray Paint Blackboard

**M107347 MAGNOLIA HOME BY JOANNA GAINES**

Chalk Spray Paint Ella Rose

**M108647 MAGNOLIA HOME BY JOANNA GAINES**

Chalk Spray Paint Yarn

**M107747 MAGNOLIA HOME BY JOANNA GAINES**

Chalk Spray Paint Rainy Days

**M107847 MAGNOLIA HOME BY JOANNA GAINES**

Chalk Spray Paint Vine Ripened Tomato

**\*M106347 MAGNOLIA HOME BY JOANNA GAINES**

Chalk Spray Paint Clear

**FILL LEVEL**

12 oz./340g

**FINISH**

Sheen @ 85° < 5

*Sheen level depends on porosity of surface and various surface irregularities.*

**COMPOSITION**

**Vehicle:** Modified Alkyd

**% Solids by Weight:** 21

**% Solids by Volume:** 16.4

**Max VOC (by weight):** 60%

**Max Product Weighted MIR:** 0.80

**COVERAGE RATE**

12 sq. ft. per can, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

### SURFACE PREPARATION

- The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

- Peeling or checked Paint: scrape off loose paint and sand to a smooth surface.

**Difficult Surfaces:**

- \*For optimal adhesion to difficult surfaces use a coat of primer such as KILZ Original Oil-Based Primer/Sealer/Stainblocker or KILZ Premium Water-Based Primer/Sealer/Stainblocker.

### APPLICATION

- Eye protection is recommended.
- Apply if surface, air and product temperatures are between 50°-90°F.
- Ensure adequate ventilation when spraying indoors.
- Mask and cover the surrounding area to protect from overspray.
- Sand glossy or hard to adhere surfaces to improve adhesion.
- Avoid painting in direct sunlight, hot and humid weather. These conditions affect dry time and film integrity.
- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use.
- Test your spray application technique on a scrap surface or inconspicuous area before starting the project.
- Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted. Always begin and finish spraying off the object. Each spray pass should overlap the other pass by half.
- **Apply multiple thin coats to prevent dripping and sagging.**

\*NOTE: Use MAGNOLIA HOME BY JOANNA GAINES Clear Chalk Spray Paint over glossy surfaces to create a matte finish. For high use surfaces like coffee tables, dining tables or vanities, spray over surfaces previously painted with MAGNOLIA HOME BY JOANNA GAINES Chalk Style Paint for a permanent seal.

**DRY TIME at 77°F (25° C), 50% RH:**

Allow to dry between each coat.

- Dries to touch in 15 minutes
- Re-coat after 45 minutes.

### CLEAN UP & DISPOSAL

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean with mineral spirits.
- Do not stick pins or wire into can opening.
- Clean fresh overspray with mineral spirits or paint thinner. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.

**WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING** Cancer and Reproductive Harm  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**VENTILATION REQUIRED:** To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. **CONTAINS ACETONE, N-BUTYL ACETATE, PROPANE, ISOBUTANE, METHYL ETHYL KETONE AND PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe the vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. **KEEP OUT OF REACH OF CHILDREN**

<sup>1</sup>Numbers given here are from MAGNOLIA HOME BY JOANNA GAINES® SPRAY CHALK PAINT Shiplap color.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • [www.kilz.com](http://www.kilz.com)

MAGNOLIA HOME BY JOANNA GAINES is a registered trademark of Magnolia IP Holdings, LLC, and is used under license.