

Assembly Instructions



CAUTION

- Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.
- Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape



Phillips screwdriver



Flat blade screwdriver




Pliers



Wire strippers

HARDWARE INCLUDED



Fixture



Decorative Nut



Cover




Wire Nuts

***PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**

INSTALLATION

STEP 1

Unscrew the **mounting screws** from the **fixture**.



STEP 2



Make the electrical connection from the junction box to the **fixture**. Connect the ground wire to the **mounting unit** using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied **wire nuts**. Secure with electrical tape.

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor




Assembly Instructions

INSTALLATION


STEP 3

Attach the **fixture** to the post through **screw holes** as shown, and secure it with **screw**.



STEP 4

Install bulbs (not included).



STEP 5

1. Unscrew the **washer and hex nut** from the **decorative nut** . Use the **washer and hex nut** to attach the **decorative nut** to the **cover**.
2. Unscrew the **ball nuts and rubber ring** from the **cover** . Use the **ball nuts and rubber ring** to attach the **cover** to the **fixture**.

