

KOHLER®

Roughing-In

K-922, K-923, K-924 LAMINAR FLOW BATH SPOUT

Product Information

Applicable product:	
*Bath spout (.8" (2 cm) D. orifice)	K-922
*Bath spout (.95" (2.4 cm) D. orifice)	K-923
Drip tray for use with wall-mount installations	K-924
* Valve and handles must be ordered to complete faucet.	

Applicable product:			
Spout	Orifice	Flow Range	Minimum Recommended Kohler supply valve
K-922	.8" (2 cm) D.	5-10 gpm (19-38 lpm)	K-302-K OR K-306-KS OR K-679-KS OR K-680-KS
K-923	.95" (2.4 cm) D.	7-15 gpm (26-57 lpm)	K-300-K OR K-301-K OR K-438-K OR K-669-KS OR K-670-KS OR K-682-K
K-924	Drip Tray		Optional

Installation Notes

Install this product according to the installation guide.

For ceiling-mount installation, product must be mounted a maximum of 9 ft (2.74 m) above the bath/whirlpool floor.

3-3/8" (8.6 cm) cutout hole required for bath filler.

Two 1/2" (1.3 cm) cutout holes required for drip tray support rods.

Six #10 x 1" wood or drywall screws required for drip tray.

