

Twister[®] ProFLEX™ MAX Wire Connector

FEATURES/BENEFITS:

- Swept wing design provides extra leverage for maximum torque
- Wide range, expanding spring handles small combinations and expands to accommodate large combinations when you need it
- Copolymer shell expands for smooth, progressive tightening ensuring dependable connections
- Flexible skirt increases protection without requiring added space in tight boxes

ELECTRICAL:

Voltage Rating: 1000V maximum in building wire; 1000V maximum in fixtures and signs.

PHYSICAL:			STANDARDS & SPECIFICATIONS:		
Housing: Thermoplastic polypropylene with thermoplastic elastomer Insert: Steel Plating: Zinc Temperature: 105°C (221°F)			UL 486C UL 94V-2 Flame retardant shell cUL Listed to CSA C22.2 No. 188-8 RoHS Compliant		
WIRE RANGE:	 Solid and/orstranded wire combinations unless stated otherwise Consult websitefor other combinations not listed 				
		Strip Length: 7/8" (22r	nm)		
1 or 2 #6 2 or 3 #8 2 to 5 #10 3 to 6 #12 5 or 6 #14 1 #8 w/1 to 5 #14 or #12 1 #8 w/1 to 4 #10 1 #10 w/3 to 5 #14 1 #12 w/4 or 5 #14 2 #12 w/2 to 4 #14 3 #12 w/1 to 3 #14 4 #12 w/1 to 4 #14 1 #6 w/1 to 5 #12	2 #6 w/1 #14 or #12 1 #6 w/1 #12 w/1 to 4 #14 1 #6 w/2 #12 w/1 to 3 #14 1 #6 w/3 #12 w/1 or 2 #14 1 #6 w/4 #12 w/1 #14 1 #6 w/1 #10 w/1 to 4 #14 1 #6 w/1 #10 w/1 to 3 #12 1 #6 w/2 #10 w/1 or 2 #14 1 #6 w/2 #10 w/1 #12 1 #6 w/1 #8 w/1 to 3 #14 1 #6 w/1 #8 w/1 or 2 #12 1 #6 w/1 #8 w/1 or 2 #12 1 #6 w/1 #8 w/1 to 3 #14 2 #8 w/1 to 4 #14 2 #8 w/1 to 3 #12	1 #8 w/1 #12 w/1 to 4 #14 1 #8 w/2 #12 w/1 to 3 #14 1 #8 w/3 #12 w/1 or 2 #14 1 #8 w/4 #12 w/1 #14 1 #8 w/1 #10 w/1 to 4 #14 1 #8 w/1 #10 w/1 to 4 #12 1 #8 w/2 #10 w/1 to 3 #14 1 #8 w/2 #10 w/1 to 3 #12 1 #8 w/3 #10 w/1 or 2 #14 1 #8 w/3 #10 w/1 ir 3 #14 2 #8 w/2 #12 w/1 or 2 #14 2 #8 w/2 #12 w/1 or 2 #14 2 #8 w/3 #12 w/1 #14 2 #8 w/3 #10 w/1 to 3 #14	2 #8 w/2 #10 w/1 #14 sol 1 #10 w/1 #12 w/1 to 4 #14 1 #10 w/2 #12 w/1 to 3 #14 1 #10 w/3 #12 w/1 or 2 #14 1 #10 w/4 #12 w/1 #14 1 #10 w/2 to 4 #12 2 #10 w/1 #12 w/1 to 3 #14 2 #10 w/2 #12 w/1 or 2 #14 2 #10 w/3 #12 w/1 #14 2 #10 w/1 to 4 #14 or #12 3 #10 w/1 to 4 #14 or #12 3 #10 w/1 to 3 #14 3 #10 w/1 to 3 #14		

DIMENSIONS:	ORDERING INFORMATION:		
Ø.85 in 1.81 in [46.0mm]	Quantity	Part No.	Weight (Ibs.)
1.20 in.	Box of 25	30-348	0.5751
	Jar of 150	30-1348J	3.5034
FACTORY CONTACT:			
IDEAL INDUSTRIES, INC.			
1375 Park Avenue; Sycamore, IL 60178			
Ph: (800) 435-0705			
Fax: (888) 222-6140			
E: contactus@idealindustries.com		-	
W: www.idealind.com		Re	vised: 9/2024