



Aquifer® | K-77688

Two-pack replacement filter cartridges

Features

- Reduces Chlorine Taste & Odor, Chloramine, Particulate Class I, Lead, Asbestos, Cyst, Mercury, Turbidity, and select Pharmaceuticals. See Performance Data Sheet for individual contaminants and reduction performance
- Filter head automatically turns off water supply when cartridge is removed
- 1.7 gpm (gallons per minute) maximum flow rate at 60 psi
- Eco-friendly coconut shell-based carbon filter



Available Colors/Finishes

Color tiles intended for reference only.

- | | |
|----|----------------|
| 0 | White |
| NA | Not Applicable |



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
3-27-2026 18:32 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

CSA B483.1
 NSF/ANSI 42
 NSF Protocol P473
 NSF/ANSI 401
 NSF/ANSI 53
 NSF/ANSI 42|NSF/ANSI 53|NSF/ANSI 401|NSF Protocol P473

Technical Information

All product dimensions are nominal.

Flow Rate

Faucet Flow Rate: 1.7 gpm (6.4 l/min)

Material

- High-impact plastic construction

Recommended Products/Accessories


K-560 Pull-down kitchen sink faucet with three-function sprayhead
 K-596 Pull-down kitchen sink faucet with three-function sprayhead
 K-597 Compact pull-down kitchen sink faucet with three-function sprayhead
 K-647 Pull-down kitchen sink faucet with three-function sprayhead
 K-649 Pull-down bar sink faucet with three-function sprayhead
 K-7505 Pull-out kitchen sink faucet with three-function sprayhead
 K-7506 Pull-out kitchen sink faucet with three-function sprayhead
 K-7508 Single-handle kitchen sink faucet with side sprayer
 K-7509 Single-handle bar sink faucet
 K-22033 Semi-professional kitchen sink faucet with three-function sprayhead
 K-22034 Single-handle bar sink faucet
 K-99259 Pull-down kitchen sink faucet with three-function sprayhead
 K-99264 Single-handle kitchen sink faucet
 K-99265 Single-handle kitchen sink faucet with side sprayer
 K-99266 Single-handle kitchen sink faucet
 K-99267 Single-handle bar sink faucet
 K-99268 Single-handle bar sink faucet
 K-7547-4 Two-hole bridge kitchen sink faucet
 K-7548-4 Two-hole bridge kitchen sink faucet with side sprayer
 K-76520-4 Three-hole bridge bar sink faucet with side sprayer

Warranty

See website for detailed warranty information.

KOHLER® One-Year Limited Warranty





Installation

- Quarter-turn twist cartridge for easy installation and replacement

Installation Notes

Install this product according to the installation instructions.

To prevent the risk of property damage, protect from freezing.

For cold water use only.

To ensure the filter continues to reduce contaminants effectively, it is recommended that the filter gets replaced every 6 months.

Application guideline/water supply parameters: Water Pressure: 40-

120 psi (276-827 kPa) Water Temperature: 33-100°F (0.5-37.8°C)

Capacity: 778 gal (2,945 L)



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

3-27-2026 18:32 - US-CA