

STAINLESS STEEL

STAINLESS STEEL

STAINLESS STEEL



¡PRECAUCIÓN! CONTIENE: Etiltriace-
toxisilano y metiltriace-
toxisilano. Se
genera ácido acético durante el período
de curado. Evite el contacto con los
ojos, la piel y la ropa. Evite inhalar los
vapores. Utilice solamente con
ventilación adecuada. Cerciórese de
que exista entrada de aire fresco
durante la aplicación y el secado. Use
guantes y gafas de seguridad. Retire los
lentes de contacto antes de utilizar el
producto. Lávese cuidadosamente
después de manipular el producto.
PRIMEROS AUXILIOS: PIEL: Lávese
meticulosamente con agua y jabón. No
utilice solventes ni limpiadores
abrasivos para retirar el producto de la
piel. OJOS: Enjuague inmediatamente
con abundante cantidad de agua.
INHALACIÓN: Trasládese al aire fresco.
INGESTIÓN: NO INDUZCA EL VÓMITO.
Obtenga atención médica si surgen
complicaciones debido a la exposición.
En caso de emergencia, llame al
centro de control de envenenamiento
al 800-222-1222. Consulte la Hoja de
datos de seguridad (SDS, por sus siglas
en inglés) para más información.
Para obtener una SDS, comuníquese
con su proveedor o visite dap.com.
**MANTENGA FUERA DEL ALCANCE
DE LOS NIÑOS.**

Commercial Kitchen 100% Silicone

FOOD-GRADE

- 100% Waterproof
- -75°F – 350°F
(up to 400°F for intermittent use)
- FDA Reg 21, CFR 177.2600
- Certified by NSF to NSF/
ANSI Standard #51



WARNING!

CONTACT WITH UNCURED PRODUCT MAY CAUSE
EYE, SKIN & RESPIRATORY TRACT IRRITATION.
Read back panel for cautions!

¡PRECAUCIÓN!

EL CONTACTO CON PRODUCTOS NO CURADOS
PUEDE CAUSAR IRRITACIÓN EN LOS OJOS,
LA PIEL Y LAS VIAS RESPIRATORIAS.
¡Lea las precauciones en el panel posterior!

9.8 FL OZ (290 mL)

When tested in accordance with ASTM C719,
meets C920 specification for Class 25, Uses
G & A.

FOR BEST RESULTS: Apply when surface
temperatures are -35°F to 140°F. Not
recommended for continuous underwater use,
filling butt joints, surface defects, tuck-pointing,
chimneys, stovepipes or fireplace applications.
Corrodes some metals. Not for oily woods or
cementitious surfaces. Joint width should not
exceed 1/2". If joint depth exceeds 1/2", use
backer rod material. Not paintable. Store below
90°F in a dry place.

INSTRUCTIONS: 1. Surface must be clean, dry
& free of old caulk and all foreign materials.
2. Cut nozzle at 45° angle to desired bead size.
3. Puncture inner foil seal. 4. Load cartridge into
caulking gun. 5. Fill gap with sealant, pushing
sealant ahead of nozzle. 6. Smooth bead.
7. Allow at least 12 hours before exposing
sealant to water. Do not touch or clean sealant
for 24 hours. 8. Clean up excess uncured sealant
with mineral spirits. Do not use mineral spirits to
clean skin. Excess cured sealant must be cut or
scraped away. Wash hands with soap & water.

CAUTION! CONTAINS: Ethyltriace-
toxisilane and methyltriace-
toxisilane. Acetic acid is evolved during cure.
Avoid contact with eyes, skin &
clothing. Avoid breathing vapors. Use
only with adequate ventilation. Ensure
fresh air entry during application and
drying. Wear gloves & safety glasses.
Remove contact lenses before using
product. Wash thoroughly after
handling. **FIRST AID:** SKIN: Wash
thoroughly with soap and water. Do
not use solvents or abrasive cleansers
to remove product from skin. EYE:
Immediately flood with large quantities
of water. INHALATION: Remove to fresh
air. INGESTION: DO NOT INDUCE
VOMITING. Get medical attention if
complications arise from any exposure.
For emergencies, call your poison
control center at 800-222-1222. See
Safety Data Sheet (SDS) for additional
information. For an SDS, contact your
supplier or visit dap.com. **KEEP OUT
OF REACH OF CHILDREN.**

CCCS Calif. ARB VOC <3.0 wt/wt% (31 g/L)

GUARANTEE: If product fails to perform when
used as directed, within one year of date
of purchase, call **888-DAP-TIPS**, with your
sales receipt and product container available,
for replacement product or sales price refund.
DAP Global Inc. will not be responsible for
incidental or consequential damages.

QUESTIONS? ¿PREGUNTAS? Call/Llame
al **888-DAP-TIPS** or visit/o
visite dap.com
& click on/y pulse
en "Ask the Expert."

Para obtener las
instrucciones y garantía
en español, llame al
888-327-8477 o visite
dap.com.

DAP Global Inc.,
Baltimore, MD 21224
Made in the USA with
U.S. and globally
sourced materials.
dap.com