N-2697

2% 25% 50% 75% 98% 100%

## **SONOCO KASE LAYOUT DATE REVISED BY DIXIE: 06-12-08 HANOVER**

CENTER LINE

DDEGRAPHICS

**PART NO: 89-3** 

1117

DATE: 11-07-08

COPY

**CLOSED** 

**END** 

1/2"

6-3/16" MAX. WRAP AROUND/BLEED 4400 CARTRIDGES

5-3/4" MAX. TEXT AND ART

e know what you're thinking. "Concrete repair products dry out and crack - again. Why bother?" You're right, they're not what they're cracked up to be. You need an elastic repair that moves when the crack moves; you need it to stick; you need it textured like concrete; and you need easy water clean-up. You need Slab®.

Paintable

2

AROUND

CARTRI

| ON |

ONLY

AROUND (

- Textured to blend-in with concrete
- · Spans gaps up to 3" wide
- Use Slab to Repair & Seal:
- Driveways & Sidewalks
- Patios & Garages
- Expansion Joints
- Stone, Brick, Stucco, Mortar

## INSTRUCTIONS

## Before You Start:

- · Apply to clean surfaces
- Use on horizontal concrete surfaces that have cured at least 4 weeks
- Application range: surface temperature of 40°F to 120°F
- Skins over in 30 min.\* Tack free in 2-4 hours.\* Cure time 1-2 weeks.\* May attract dirt and debris until skin forms. \* Sealant skin and cure times are dependent on temperature, humidity,
- and bead size.
- Keep foot and vehicle traffic off of the sealant for a minimum of 24 hours after application to give Slab sufficient time to build strength.

  Note: in areas of 50% humidity or higher it is best to wait 48 hours.
- Protect from water for 24-48 hours after application
- For best results recess Slab below the surface of the crack

Step 1. Remove any previously applied caulk or foams, as well as oils. dirt and other contaminants. Thoroughly clean the crack with either a stiff bristled brush or a drill-mounted brush. Sweep or blow out any debris.

Step 2. For joints deeper than 1/2", install Sashco Filler Rope™ (see diagram).

Step 3. Cut nozzle to the desired bead size.

Step 4. Gun Slab into the crack.

Step 5. Press Slab into the sides of the crack for best adhesion. Smooth out using water and a foam brush or finger, etc. For best results, recess Slab below the surface of the crack.



## **CLEAN UP & STORAGE**

Clean up any fresh product on surfaces and skin with soap and water. Tightly reseal cartridges with plastic wrap and a rubber band. Store between 40°F and 90°F.

CAUTION: Avoid contact with eyes and skin. Do not swallow. In case of eye or skin contact, flush thoroughly with water. If swallowed, do not induce vomiting. Call physician immediately. KEEP OUT OF REACH OF CHILDREN.

MARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

VOC: 58 g/L, <1.5% by weight.

LIMITED LIFETIME WARRANTY: For a detailed description of the warranty and exclusions, please visit our website at www.sashco.com.  $\sim$ 



©2018 Sashco, Inc. 10300 E. 107th Place Brighton, CO 80601 800-767-5656 www.sashco.com Made in the USA



CENTER LINE

**COLORS: BLACK** 

10.5 FL. OZ. (310 mL)

UPC: 0 31525 16210 2

Prints 3 color: PMS 2627, PMS 375 & Black

REORDER NO: SN-2697 PART NO: 89-3 DATE: 11-07-08

525NC0 4400 CARTRIDGE WRAP **AROUND** ONLY - NO **TEXT OR** CARTRIDGE WRAP AROUND Serious F for Concrete Gracks Sticks · Stretches · Stays

HEIGHT 7-1/2" TUBE LENGTH 8-1/2"

PRINT

**COLORS: BLACK** 

**OPEN END** 

1/2"



DX#043