

MATERIAL SAFETY DATA SHEET



GLB Super Charge

1. Product And Company Identification

| | |
|---|---|
| Supplier GLB 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770)521-5999 FAX Number: (770)521-5959 Web Site: www.poolspacare.com | Manufacturer Advantis Technologies, Inc. 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 United States Telephone Number: (770) 521-5999 FAX Number: (770) 521-5959 Web Site: www.poolspacare.com |
| Supplier Emergency Contacts & Phone Number CHEMTRIC - DAY OR NIGHT: (800) 424-9300 | Manufacturer Emergency Contacts & Phone Number CHEMTRIC - DAY OR NIGHT: (800) 424-9300 |

Issue Date: 02/16/2006

Product Name: GLB Super Charge
 Chemical Name: Calcium Hypochlorite
 CAS Number: Not Established
 Chemical Family: Oxidizer
 Chemical Formula: Proprietary
 MSDS Number: 99

2. Composition/Information On Ingredients

| Ingredient Name | CAS Number | Percent Of Total Weight |
|---------------------|-----------------|-------------------------|
| CALCIUM CARBONATE | 471-34-1 | |
| CALCIUM CHLORATE | 10137-74-3 | |
| CALCIUM CHLORIDE | Not Established | |
| CALCIUM CHLORIDE | 10043-52-4 | |
| CALCIUM HYDROXIDE | 1305-62-0 | |
| CALCIUMHYPOCHLORITE | 7778-54-3 | |
| SODIUMCHLORIDE | 7647-14-5 | |

Ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. Materials determined to be health hazards are listed if they comprise 1% or more of the composition. Materials identified as carcinogens are listed if they comprise 0.1% or more of the composition. Information on proprietary materials is available in 29CFR 1910.1200(i)(1).

Hazards Identification (Pictograms)



3. Hazards Identification

Primary Routes(s) Of Entry

Skin Contact, Eye Contact, Ingestion

Eye Hazards

Causes severe eye burns.

MATERIAL SAFETY DATA SHEET

GLB Super Charge

3. Hazards Identification - Continued

Skin Hazards

Causes skin irritation.

Ingestion Hazards

If ingested, get immediate medical attention.

Inhalation Hazards

Causes respiratory tract irritation. May cause severe allergic respiratory reaction.

Chronic/Carcinogenicity Effects

Chronic exposure may cause

 impairment of lung function or lung damage
 secondary tissue destruction

Signs And Symptoms

Inhalation of dust or vapor from this product can be irritating to the nose, mouth, throat and lungs. In confined areas, mechanical agitation can result in high levels of dust, and reaction with incompatible materials can result in high concentrations of chlorine vapor either of which may result in burns, wheezing, choking, chest pains, impairment of lung function and possible lung damage.

Severe eye irritation and/or burns can occur following eye exposure. Contact may cause impairment of vision and corneal damage.

Dermal exposure can cause severe irritation and/or burns characterized by redness, swelling and scab formation. Prolonged exposure may cause permanent damage.

Conditions Aggravated By Exposure

Asthma, respiratory, and cardiovascular disease

May be fatal if swallowed. Avoid breathing dust or fumes. Harmful if product is inhaled in high concentrations. Causes skin, eye, digestive tract and respiratory burns.

First Aid (Pictograms)



4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Call a physician or a poison control center immediately.

Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Call a physician or poison control center immediately. Remove contaminated clothing and shoes. Thoroughly clean shoes before reuse. Wash clothing before reuse.

Ingestion

DO NOT INDUCE VOMITING. If victim is fully conscious, drink large amounts of water. Call a physician or a poison control center immediately.

Inhalation

If inhaled, remove to fresh air. Call a physician or a poison control center immediately.

MATERIAL SAFETY DATA SHEET

GLB Super Charge

Fire Fighting (Pictograms)



5. Fire Fighting Measures

Flash Point: N/A °F

Fire And Explosion Hazards

This product is chemically reactive with many substances. Any contamination of this product with other substances by spill or otherwise may result in a chemical reaction and fire. This product is a strong oxidizer which is capable of intensifying a fire once started.

Extinguishing Media

WATER ONLY. In case of fire, soak (flood) with water.

DO NOT USE Dry Chemical OR OTHER EXTINGUISHERS CONTAINING AMMONIUM COMPOUNDS

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

GRINDING OR INTENSIVE MIXING MAY GENERATE SUFFICIENT HEAT TO FUSE PRODUCT AND CAUSE IGNITION OF OXIDIZABLE MATERIAL PRESENT.

6. Accidental Release Measures

Clean up spill immediately. Flush spill area with water in compliance with State and Federal Regulations.

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store material in a cool and dry place.

Handling Precautions

Avoid breathing dust or vapor. Avoid contact with skin and clothing. Avoid contact with eyes.

Storage Precautions

Keep product tightly sealed in original containers. Store in a cool dry place. Store in a dry, well ventilated place. Keep away from combustible or flammable products. Keep packaging clean and free from contamination including other pool treatment products , acids, organic materials, nitrogen containing compounds, dry powder fire extinguisher (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials

Do not store at temperatures above 52C (125F) Storage above this temperature may result in rapid decomposition, evolution or chlorine gas and heat sufficient to ignite combustible materials.

Work/Hygienic Practices

Use safe chemical handling procedures suitable for the hazards presented by this material.

MATERIAL SAFETY DATA SHEET

GLB Super Charge

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Wear NIOSH approved respirator if dusts are created.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Chemical-resistant gloves, impervious suit may be required.

Respiratory Protection

Use NIOSH/MSHA approved dust and mist respirator when applicable.

Ingredient(s) - Exposure Limits

CALCIUM CARBONATE

| | |
|---------------------------------------|-------------------|
| OSHA (PEL) | ACGIH(TLV) |
| TWA 15 mg/cubic-meter (total dust) | 10 mg/cubic-meter |
| 5 mg/cubic-meter(respirable fraction) | |

CALCIUM HYDROXIDE

ACGIH(TLV) 5 mg/cubic-meter

CALCIUM HYPOCHLORITE

3 mg/cubic meter(ceiling) as chlorine manufactures internal exposure limit

9. Physical And Chemical Properties

Appearance

White granules or powder

Odor

Chlorine

Chemical Type: Mixture

Physical State: Solid

Melting Point: DECOMPOSES °F

Boiling Point: DECOMPOSES °F

Specific Gravity: n/a

Molecular Weight: 143 (Active)

Percent Volitales: n/a

Packing Density: 0.8g/cc

Vapor Pressure: n/a

pH Factor: 10.4-10.8 At a Concentration Of 1% solution

Solubility: 18% @ 25C

Corrosive, Oxidizer

10. Stability And Reactivity

Stability: See comments

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

This product may be unstable at tempratures above 170C (338F)

MATERIAL SAFETY DATA SHEET

GLB Super Charge

10. Stability And Reactivity - Continued

Incompatible Materials

Keep packaging clean and free from contamination including other pool treatment products , acids, organic materials, nitrogen containing compounds, dry powder fire extinguisher (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials

Hazardous Decomposition Products

Chlorine Gas

Conditions To Avoid (Polymerization)

Avoid temperatures above 125 F (52C) Prevent ingress of humidity and moisture into container. Always close the lid.

11. Toxicological Information

Eye Effects

Severe irritation and/or burns can occur following eye exposure. Contact may cause impairment of vision and corneal damage.

Skin Effects

Acute dermal exposure can cause severe irritation and/or burns characterized by redness, swelling and scab formation. Prolonged skin exposure may cause permanent damage.

Chronic effect of skin exposure would be similar to those from single exposure for effects secondary to tissue destruction.

Acute Oral Effects

Irritation and/or burns to the entire gastrointestinal tract, including the stomach and intestines, characterized by nausea, vomiting, diarrhea, abdominal pain, bleeding and/or tissue ulceration. Due to the corrosive nature of this product ingestion may be fatal.

Acute Inhalation Effects

Inhalation of dust or vapor from this product can be irritating to the nose mouth , throat and lungs. In confined areas mechanical agitation can result in high levels of dust and reaction with incompatible materials can result in high concentrations of chlorine vapor, either of which may result in shortness of breath, wheezing, choking, chest pains, impairment of lung function and possible lung damage.

Conditions Aggravated By Exposure

Asthma, respiratory and cardiovascular disease.

12. Ecological Information

Toxicity - Aquatic And Terrestrial Plants

Bluegill, 96 hr. LC50 0.088 mg/l (nominal, static)

Rainbow trout, 96 hr. LC50: 0.16 mg/l (nominal, static)

Daphnia magna, 48hr. LC50: 0.11 mg/l (nominal, static)

Acute And Dietary Toxicity - Birds

Bobwhite quail, dietary LC50:>5,000 ppm

Mallard ducklings, dietary LC50:>5,000 ppm

Bobwhite quail oral LD50:3474 mg/kg

13. Disposal Considerations

This product meets the criteria of a hazardous waste as defined under 40 CFR 261. It is subject to Land Disposal restriction under 40 CFR 268 and must be managed accordingly. Dispose in accordance with applicable federal, state and local government regulations.

MATERIAL SAFETY DATA SHEET

GLB Super Charge

14. Transport Information

Proper Shipping Name

RQ CALCIUM HYPOCHLORITE, HYDRATED MIXTURES

Hazard Class

5.1,PGII (<1KG Consumer Commodity ORM-D)

DOT Identification Number

UN2880

15. Regulatory Information

U.S. Regulatory Information

This material is regulated as a DOT hazardous material. It is also regulated by FIFRA, USDA, and FDA.

This substance is listed on TSCA.


NSF Maximum Drinking Water Use Concentration 46mg/l as Calcium hypochlorite

SARA Hazard Classes

Acute Health Hazard

Fire Hazard

Reactivity Hazard



16. Other Information

Revision/Preparer Information

MSDS Preparer: JHW3

This MSDS Superceeds A Previous MSDS Dated: 09/18/2000

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

GLB

Printed Using MSDS Generator™ 2000