



# MSDS

## MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.

**ACOUSTIC TEXTURE II  
ITEM #4070**

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME) (J=SPLASHGOGGLES, GLOVES, SYNTHETIC APRON, AND VAPOR RESPIRATOR)

HAZARDOUS MATERIAL INFORMATION SYSTEM	
HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PROTECTIVE EQUIPMENT	J

### SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:  
HOMAX PRODUCTS, INC.  
840 WEST HORTON ROAD  
BELLINGHAM, WA 98226

24 HOUR EMERGENCY PHONE NUMBER:  
CHEMTREC 800-424-9300

INFORMATION PHONE NUMBER: 1-800-729-9029  
PREPARED BY: COMPLIANCE DEPARTMENT  
7/28/99

### SECTION IIA - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER	DESCRIPTION	PEL	TLV	%
1. 07727-37-9	NITROGEN			1
2. 14808-60-7	SILICA, CRYSTALLINE-QUARTZ	0.1 mg/m3	0.1 mg/m3	TRACE

-TRACE QUANTITIES LESS THAN 0.1% AND GREATER THAN 0.009%

-PEL'S REPRESENT LOWERED 1989 LIMITS AND MAY NOT BE ENFORCEABLE BY FEDERAL OSHA.

### SECTION IIB - OTHER REGULATORY INFORMATION

CAS NUMBER	DESCRIPTION	CARCINOGEN			SARA TITLE III		CALIFORNIA
		NTP	IARC	OSHA	302	313	P65 I II
1. 07727-37-9	NITROGEN						
2. 14808-60-7	SILICA, CRYSTALLINE-QUARTZ				X		X

---

---

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

---

APPEARANCE AND ODOR: VISCOUS LUMPY LIQUID  
BOILING POINT: 0 TO 0 DEG. F.  
WATER SOLUBILITY: APPRECIABLE  
VAPOR DENSITY : HEAVIER THAN AIR  
EVAPORATION RATE: SLOWER THAN (n-BUTYL ACETATE=MEDIAN)  
CALCULATED V.O.C.: .08 LB/GL(10GR/LT) WT/GAL: 9.83 (WITH PROP: .89)

---

---

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

---

FLASH POINT (METHOD USED): N/A  
UNIFORM FIRE CODE STANDARD 88-1 LEVEL ONE AEROSOL  
BULK PRODUCT FLASH POINT: N/A  
BULK PROPELLANT FLASH POINT: N/A  
PACKAGED PRODUCT FLAME EXTENSION: 00  
EXTINGUISHING MEDIA: USE FOAM, CO2, DRY CHEMICAL, WATER FOG

**SPECIAL FIREFIGHTING PROCEDURES:**

EVACUATE ALL UNNECESSARY PERSONNEL. USE FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS. USE WATER SPRAY, PREFERABLY FOG, TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE EXPLOSION. DO NOT ALLOW PRODUCT OR RUNOFF FROM FIRE CONTROL TO ENTER STORM OR SANITARY SEWERS, LAKES, RIVERS, STREAMS, OR WATERWAYS.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

CONTENTS UNDER PRESSURE. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

---

---

**SECTION V - REACTIVITY DATA**

---

**STABILITY:**

MATERIAL IS STABLE.

**INCOMPATIBILITY (MATERIALS TO AVOID):**

STRONG OXIDIZING AGENTS, ACIDS, AMMONIA.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES.

**CONDITIONS TO AVOID:**

HIGH TEMPERATURE AND HUMIDITY, IGNITION SOURCE, VAPOR BUILD-UP.

**HAZARDOUS POLYMERIZATION:**

WILL NOT OCCUR.

---

---

**SECTION VI - HEALTH HAZARD DATA**

---

ROUTES OF ENTRY: INHALATION: YES SKIN: YES

**ACUTE EFFECTS FROM SHORT TERM EXPOSURE:**

INHALATION: DUSTS AND PARTICLES CAUSE IRRITATION TO NOSE, THROAT AND LUNGS (POSSIBLE BURNING, STINGING, COUGHING).

EYES: NONE KNOWN.

SKIN: NONE KNOWN.

SKIN ABSORPTION: NONE KNOWN.

**CHRONIC EFFECTS FROM LONG TERM/REPEATED EXPOSURE:**

LONG-TERM OR REPEATED OVEREXPOSURE, WITHOUT PROPER VENTILATION OR PERSONAL PROTECTION, MAY CAUSE DAMAGE TO LIVER.

**OTHER:**

THIS PRODUCT CONTAINS A FORM OF CRYSTALLINE SILICA. LONG TERM EXPOSURE TO HIGH LEVELS OF CRYSTALLINE SILICA DUSTS MAY RESULT IN SILICOSIS, A DISABLING LUNG DISEASE. ALWAYS WEAR APPROPRIATE RESPIRATORY PROTECTION WHEN EXPOSED TO SANDING OR GRINDING DUSTS.

CARCINOGEN DATA:

CRYSTALLINE SILICAS ARE CLASSIFIED BY IARC AS POTENTIAL HUMAN CARCINOGENS. INHALATION OF CRYSTALLINE DUSTS MAY CAUSE LUNG TUMORS. RISK OF CANCER DEPENDS ON LEVEL AND DURATION OF EXPOSURE. THE FOLLOWING STATEMENT IS REQUIRED BY CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC REFORM ACT OF 1986).

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY TRACT IRRITATION; NAUSEA; SKIN AND EYE DISORDERS; SENSITIZATION TO CHEMICAL SUBSTANCES.

EMERGENCY AND FIRST AID PROCEDURES

SWALLOWING:

IN CASE OF ACCIDENTAL INGESTION, CALL POISON CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY.

INHALATION:

IF AFFECTED BY BREATHING ODORS OR VAPORS, REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.

EYE:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES, WHILE LIFTING UPPER AND LOWER EYELIDS. GET MEDICAL ATTENTION.

SKIN:

WASH WITH SOAP AND WATER. REMOVE AND CLEAN CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

---

---

**SECTION VII - EMERGENCY AND FIRST AID PROCEDURES**

---

---

SWALLOWING:

IN CASE OF ACCIDENTAL INGESTION, CALL POISON CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY.

INHALATION:

IF AFFECTED BY BREATHING ODORS OR VAPORS, REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.

EYE:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES, WHILE LIFTING UPPER AND LOWER EYELIDS. GET MEDICAL ATTENTION.

SKIN:

WASH WITH SOAP AND WATER. REMOVE AND CLEAN CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

OTHER: N/A

---

---

**SECTION VIII- PERSONAL PROTECTION**

---

---

RESPIRATORY PROTECTION: IF AFFECTED BY BREATHING VAPORS OR ODORS, WEAR A PROPERLY FITTED RESPIRATOR (NIOSH/MSHA TC23C OR EQUIVALENT) DURING USE. IF PRODUCT GIVES OFF SPRAY MIST, AVOID BREATHING BY EARING RESPIRATOR PREFILTER OR PARTICLE MASK.

VENTILATION: OPEN DOORS AND WINDOWS TO PROVIDE FRESH AIR VENTILATION. IN WORK AND SURROUNDING AREAS, DURING AND AFTER APPLICATION UNTIL ALL VAPOR (FUMES) ARE GONE.

HAND PROTECTION: WEAR GLOVES TO AVOID SKIN CONTACT.

EYE PROTECTION: EAR SAFETY GLASSES OR GOGGLES TO PORTECT EYES FROM SPLASH AND SPRAY MISTS. NOTE: CONTACT LENSES MAY CONTRIBUTE TO THE SEVERITY OF AN EYE INJURY AND SOULD NOT BE WORN WHEN WORKING WITH CHEMICALS.

WORK/HYGENIC PRACTICES: WASH HANDS AFTER USING AND BEFORE EATING, DRINKING OR USING TOBACCO

PRODUCTS. THOROUGHLY CLEAN CONTAMINATED CLOTHING AND SHOES BEFORE REUSE.

---

---

### **SECTION IX - SPILL OR LEAK PROCEDURES**

---

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

ELIMINATE IGNITION SOURCES AND VENTILATE AREA. EVACUATE UNNECESSARY PERSONNEL. WEAR PROTECTIVE EQUIPMENT. DIKE AND CONTAIN SPILL WITH INERT MATERIAL. TRANSFER LIQUID TO CONTAINERS FOR DISPOSAL OR RECOVERY. PREVENT MATERIAL FROM ENTERING STORM OR SANITARY SEWERS AND OPEN BODIES OF WATER.

WASTE DISPOSAL:

WASTE MATERIAL AND EMPTY CONTAINERS MUST BE DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL ENVIRONMENTAL CONTROL REGULATIONS. USE ONLY APPROVED WASTE MANAGEMENT FACILITIES.

---

---

### **SECTION X - SPECIAL PRECAUTIONS**

---

---

HANDLING PRECAUTIONS:

USE PROPER METHODS OF VENTILATION TO PREVENT VAPOR BUILD-UP. AVOID SPRAYING HOT SURFACES. DO NOT HEAT, PUNCTURE OR INCINERATE CONTAINERS. CONTENTS ARE UNDER PRESSURE AND MAY CONTAIN VAPORS, EVEN WHEN EMPTY. DO NOT REMOVE OR DEFACE LABEL.

SHIPPING AND STORAGE PRECAUTIONS:

CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEGREES F OR PERMIT PROLONGED EXPOSURE TO SUNLIGHT. PROTECT CONTAINERS FROM DAMAGE. STORE IN BUILDINGS OR AREAS DESIGNED AND PROTECTED FROM STORAGE OF AEROSOLS. KEEP OUT OF REACH OF CHILDREN.

---

---

### **SECTION XI - DISCLAIMER**

---

---

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX CORPORATION TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HERewith.