INSTALLATION INSTRUCTIONS 2 LIGHT FLUSH MOUNT

READ AND FOLLOW SAFETY INFORMATION

Turn off the main power at the circuit breaker before installing and servicing the fixture to prevent possible injury from electric shock.

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician.

INSTALLATION & ASSEMBLY

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

- 1. **Preparing the Crossbar Assembly:** Unscrew the mounting screws from the Crossbar Assembly, remove the Crossbar Assembly from the fixture body, and keep the mounting screws for later use.
- 2. Installing the Crossbar Assembly: Secure the crossbar to the outlet box (not included) with outlet box screws. Tighten until snug.
- 3: **Preparing the glass panels**: Place the glass panels into the frame of the fixture and secure them with the metal tabs.Repeat this step for the other glass panels.
- 4. **Making the electrical connections:** Ground Wire:1. Wrap supply ground wire around green ground screw on mounting bracket, no less than 2 in. from the end of the wire. Tighten ground screw.2. Connect fixture green ground wire to supply ground wire with wire connector.

Supply Wire:1. Connect the supply white wire to the white fixture supply wire with wire connector.2. Connect the supply black (or red) wire to the black fixture supply wire with wire connector.3. Wrap each connection with approved electrical tape and carefully stuff all of the connected wires into the outlet box.

5. Assembling the fixture body to the outlet box: Line up the holes on the canopy of the fixture body and the mounting holes on the crossbar. Secure with the mounting screws. Tighten until snug.

- 6. **Installing the light bulb:** Install correct bulb referring to fixture markings and/or labels for maximum wattage.
- 7. Installation complete, restore power at the circuit breaker and turn light switch on to activate this fixture.

Care and maintenance – Use damp and clean cloth to wipe the surface of the fixture.

