

# DEWALT®

20V<sup>MAX\*</sup>  
BRUSHLESS

XR<sup>®</sup>



## EXPERIENCE POWER™

### DCF900

## 20V MAX\* XR<sup>®</sup> 1/2 IN. HIGH TORQUE IMPACT WRENCH WITH HOG RING ANVIL

Complete the toughest jobs utilizing the power of the DEWALT 20V MAX\* XR<sup>®</sup> 1/2 in. High Torque Impact Wrench. Delivering 1030 ft-lb of max fastening torque and 1400 ft-lbs of max breakaway torque, the DCF900 is ideal for large sized pipe flanges, grooved couplings, wheel lugs, concrete anchor bolt setting and many other heavy-duty impact wrench applications. The PRECISION WRENCH™ control mode is included to help prevent over tightening in forward and run-off in reverse, for additional user control. Utilize the updated 4-mode push button switch to easily transition speeds and adjust LED brightness when needed.



SHOCK-ABSORBING  
BATTERY-TO-TOOL  
CONNECTION

## PRECISION WRENCH™

CONTROL

**GUARANTEED TOUGH.®**

**DCF900SS**



# 20V MAX\* XR® 1/2 IN. HIGH TORQUE IMPACT WRENCH WITH HOG RING ANVIL

**GLASS FILLED NYLON HOUSING**  
Resist effects of harsh automotive fluids and solvents.

**BRUSHLESS MOTOR**  
High-efficiency brushless motor of the battery-powered impact wrench maximizes runtime and motor life.

**1/2 IN. HOG RING ANVIL**

**VARIABLE SPEED TRIGGER WITH PUSH BUTTON MODE SELECT**  
Increase user control in a variety of applications with 4-mode speed settings and variable trigger. This includes PRECISION WRENCH™, designed to help prevent overtightening and fastener run-off.

**ILLUMINATE DARK WORKSPACES**  
Use on-tool LED work light button to easily adjust brightness when needed.

**REDUCE WEAR AND TEAR ON THE BATTERY WHILE YOU WORK WITH BATTERYGUARD™**

A shock-absorbing battery-to-tool connection system.



**47% MORE MAX FASTENING TORQUE**  
vs. DCF899 Impact Wrench with Rated Max Fastening torque of 700 ft-lb



**COMPLETE A WIDE VARIETY OF HEAVY DUTY FASTENING APPLICATIONS**  
With 1030 ft-lb of max fastening torque and 1400 ft-lbs of max breakaway torque

\*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

## SPECIFICATIONS

TOOL LENGTH	8.8 in.
ANVIL SIZE	1/2 in.
ANVIL STYLE	Hog Ring
RPM	0 – 2300
IPM	0 – 2200
MAX TIGHTENING TORQUE	1030 ft-lbs
MAX BREAKAWAY TORQUE	1400 ft-lbs
TOOL WEIGHT (TOOL ONLY)	6.4 lbs.

## TOOL WARRANTY

<b>3</b> YEAR LIMITED WARRANTY	<b>1</b> YEAR FREE SERVICE	<b>90</b> DAY MONEY BACK GUARANTEE
--------------------------------------	----------------------------------	--

## KIT OPTIONS

### DCF900P1

- (1) DCF900 Impact Wrench
- (1) 5.0 Ah Battery
- (1) Charger
- (1) Kit Bag



### DCF900P2

- (1) DCF900 Impact Wrench
- (2) 5.0 Ah Batteries
- (1) Charger
- (1) Kit Bag



### DCF900GP2

- (1) DCF900 Impact Wrench
- (2) 5.0 Ah Oil Resistant Batteries
- (1) Charger
- (1) Kit Bag



## RELATED ACCESSORIES

### PB900B

Protective Boot for DCF900  
(Sold Separately)



Copyright © 2022 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

DCF900SS

**GUARANTEED TOUGH.®**

**1-800-4-DEWALT**

**www.DEWALT.com**