

Everything you love about the DLR4 is now available with the aesthetics of a square trim. Designed to boost energy efficiency, the LED light engine draws only 11 watts while achieving a light output to over 600 lumens. The enriched 90+ CRI light output provides superior color quality. Not only is the light quality better, but this design improvement meets new industry standards like Title 24.

FEATURES

- Die cast aluminum trim routes heat away from electrical components
- · Low profile, high efficiency integrated driver
- Polystyrene diffuser and reflector cone create a uniform light distribution that reduces glare
- Greater than 90 CRI and an R9 greater than 50
- Dimmable to 10% with most standard dimmers
- Thermally protected, high efficiency driver standard
- Operating temperature rating of 0°F to 120°F (-18°C − 49°C)
- LM-79, LM-80 testing performed in accordance with IESNA standards
- Quick and easy installation with a screw-in Edison base (GU24 socket string available) and friction clip mounting system
- · Wet location rated











PRODUCT SPECIFICATIONS								
Series	Input Voltage (VAC)	Delivered Lumens (Lm)	System Level Power (W)	System Efficacy (Lm/W)	Color Rendering Index (CRI)			
DLQ4-10-120- 3K-WH	120	600	11	62	95			

ORDERING II	NFORMATION	Example: DLQ4-10-120-3K-WH		
Series	Version	Voltage	CCT's	Trim Color
DLQ4	10 (1.0)	120	2K (2700) 3K (3000) 4K (4000)	WH (white)