

Model 343 UL Listed Wire Combinations Strip Wires 7/16 in.

UL File Number E5238

Copper to Copper wire only (do not use on aluminum).

600 Volt Maximum. For use with solid or stranded combinations



2 to 6 #22	3 #18 with 1 or 2 #20 or #22	1 #14 with 1 to 4 #22	1 #12 with 1 to 3 #16
2 to 6 #20	4 #18 with 1 #20 AWG or #22	1 #14 with 1 to 3 #20	1 #12 with 1 or 2 #14
2 to 5 #18	1 #16 with 1 to 4 #20 or #22	1 #14 with 1 to 5 #18	2 #12 with 1 or 2 #18
2 to 4 #16	1 #16 with 1 to 5 #18	1 #14 with 1 to 4 #16	2 #12 with 1 #16
1 to 3 #14	2 #16 with 1 to 3 #22	2 #14 with 1 to 3 #20 or #22	2 #12 with 1 #14
1 to 3 #12	2 - #16 with 1 to 3 #20	2 #14 with 1 to 3 #18	1 #10 with 1 to 3 #18
4 #12 SOLID	2 #16 with 1 to 4 - # 18	2 #14 with 1 to 3 #16	1 #10 with 1 or 2 #16
1 #10	3 #16 with 1 to 3 #18 or #20 or #22	3 #14 with 1 or 2 #18	1 #10 with 1 or 2 #14
3 #20 with 1 or 2 #22	4 #16 with 1 #20 AWG or #22	3 #14 with 1 #16	1 #10 with 1 #12
4 #20 with 1 #22	4 #16 with 1 or 2 #18	1 #12 with 1 to 5 #18	
1 # 18 with 1 to 4 #20 or #22			
2 #18 with 1 to 3 #20 or #22			