ASSEMBLY AND INSTALLATION INSTRUCTIONS

W0172 / W0173 / W0191 / W0308

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements. 2. READ AND SAVE THESE INSTRUCTIONS.



- 1. Unscrew two ball nuts, and then remove the mounting plate from the back plate.
- 2. Attach the mounting plate to the outlet box by using two mounting screws.
- 3. Pull out the source wires from the outlet box. Make wire connections using wire connectors as follow:
 - ---Connect the hot wire (usually black insulation) from the fixture to the black wire from the power source. ---Connect the neutral wire (usually white insulation) from the fixture to the white wire from the power source.
 - ----Attach the fixture grounding wire (usually green insulation) norm the incure to the white when norm the power source.
 - grounding screw, and then connect it to the house grounding wire with the wire connector. Carefully put the wires back into the outlet box.



- 4. Attach the back plate to the mounting plate by inserting two fixture mounting screws, and then secure it with two ball nuts.
- 5. Install 4x60W Max. medium base bulbs (not included). Check relamping label at socket area or packaging for maximum allowed wattage.
- 6. Loose three set screws and then attach the glass shade to the glass holder, finally secure it with three set screws. Repeat for the other glass shades. (Don't over tighten.)
- 7. Screw two finials to two sides of tube tightly.

Turn on the power at fuse or circuit box.

The following parts are available for re-order if damaged or missing.





