

Bathroom Vanity Replacement Guide

Removal Process



Disconnect supply lines from valves and unscrew P-trap

Turn off water supply valves, and open faucet to relieve pressure



Slide Vanity from wall and repair or repaint any necessary areas

Remove fasteners attaching vanity to wall, and detach backsplash



Bathroom Vanity Replacement Guide

Installation Process



Select new faucet with drain and p-trap, ensuring compatibility



Slide new vanity into place, ensuring plumbing aligns and vanity is level



Wrap threads of supply valves with teflon tape, and attach supply lines



Turn on water supply and test faucet or drain functionality, and check connections for leaks



Select a new vanity - factor in plumbing cutouts, installation location (backsplash/side splash), and cabinet or furniture style



Install new faucet and drain according to manufacturer's guidelines and attach supply lines



Attach vanity to wall utilizing appropriate anchors



Connect P-trap assembly to drain spout and wall tube



Install backsplash or side splash if necessary, using construction adhesive, and seal with caulk

Required Tools and Materials

Power Drill/Driver | Adjustable Wrench | Bathroom Sink Faucet | Bathroom Vanity | Plumbers Tape
Cleaning Cloth | Plumbers Putty | Cleaning Gloves | Basin Wrench | Eye Protection | Tape Measures
Stud Finder | Caulk Gun | Hole Saw Kit | Utility Knife | Caulk | Bucket