

JOB NAME:

CONTRACTOR:

DATE:

WIRE COIL COLLATION FOR SIDING NAILS

TYPES


Smooth



Ring



PROFIT



FUNCTION

For general construction of cement board siding, fencing, and exterior trim
Fits most 15° wire coil siding nailers

FEATURES

Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)
Smooth Shanks provide lower withdrawal strength when compared to ring shanks
Ring Shanks are deformed to have repeated ridges to increase withdrawal strength

CORROSION

Electro Galvanized (EG) in accordance with ASTM A641 standards for low level corrosion resistance
Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards
300-series Stainless Steel is suitable for all marine applications

CAUTION



Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener
Electro Galvanized (EG) shall not be used within 3000 feet of saltwater
Only 300-series Stainless Steel will prevent tannin staining when used with cedar, cement board, or redwood
All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer

TECHNICAL	Length x Dia	Penny Length	Gauge (W&M)	Head Diameter	Ring Shank Length, MIN	Nails per Coil	ASTM F1667 Bend Yield*
	1-1/4 x .092	3d	13	Ø 0.219 in	1.00 in	300	100,000 psi
	1-1/2 x .080	4d	14	Ø 0.219 in	1.00 in	300	100,000 psi
	1-1/2 x .092	4d	13	Ø 0.219 in	1.00 in	300	100,000 psi
	1-3/4 x .080	5d	14	Ø 0.219 in	1.00 in	300	100,000 psi
	1-3/4 x .092	5d	13	Ø 0.219 in	1.00 in	300	100,000 psi
	2 x .092	6d	13	Ø 0.219 in	1.13 in	300	100,000 psi
	2 x .099	6d	12.5	Ø 0.219 in	1.13 in	300	100,000 psi
	2-1/4 x .092	7d	13	Ø 0.219 in	1.13 in	300	100,000 psi
	2-1/4 x .099	7d	12.5	Ø 0.219 in	1.13 in	300	100,000 psi
	2-1/2 x .092	8d	13	Ø 0.219 in	1.25 in	300	100,000 psi

* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

WIRE COIL COLLATION FOR SIDING NAILS

TYPES

Smooth



Ring



PROFIT



PRODUCT	Size	Box Count QTY	Brite sku	EG sku	HDG sku	305 SS sku	316 SS sku
Smooth	1-3/4 x .092	9000	-	616725	-	-	-
Smooth	2 x .099	3000	-	-	616830	-	-
Smooth	2-1/4 x .092	9000	-	616745	-	-	-
Ring	1-1/4 x .092	3600	-	-	-	640071	-
Ring	1-1/2 x .080	3000	-	-	616828	-	-
Ring	1-1/2 x .092	3600	-	-	-	640091	-
Ring	1-3/4 x .080	3000	-	-	616829	-	-
Ring	1-3/4 x .092	3600	-	-	616820	640111	-
Ring	2 x .092	3600	-	-	616823	640131	-
Ring	2 x .099	3000	-	-	616833	-	-
Ring	2-1/4 x .092	3600	-	616748	-	640141	-
Ring		4500	-	-	616845	-	-
Ring	2-1/4 x .099	3000	-	-	616846	-	-
Ring	2-1/2 x .092	3600	-	-	616856	640151	-