



Resi-
PROLINE T8
Residential Electronic Ballast

GE432-120RES-B
Instant Start, 120 Volts, 50/60 Hz




0 43168 60114 6

**WARNING**
AVERTISSEMENT!
RISK OF ELECTRIC SHOCK
RISQUE DE CHOC ÉLECTRIQUE

• Turn power off before servicing
• Éteindre avant de procéder à l'entretien
• Properly ground ballast and fixture
• Ballast et luminaire avec mise à la terre conforme

For 3 lamp operation, insulate one blue lead for 600Vrms
Install and ground per National Electrical Code



120V

120V Input Electronic Ballast
Open Circuit Voltage 600 Vrms
Min Start Temp 0°F (-18°C)
Inherent Thermal Protection
Protection thermique inhérente
Class P, Outdoor Type 1
Type HL
FCC Part 18, Consumer
Suitable for Residential Use
Sound Rated A
Product is compliant with material
restriction requirements of RoHS.

**LISTED**
FLUORESCENT
LAMP BALLAST
14VS

Assembled in China
Designed and Distributed by
General Electric Co.
Nela Park, Cleveland, OH. 44112
Transforming the Power of Light™

Use With
Lamp
Types

4 F32T8
4 F32T8/U
4 F32T8/WM
4 F32T8/25W
4 F28T8
4 F25T8
4 F17T8
3 F40T8

Line
Current
120 V

1.62
1.62
1.50
1.31
1.42
1.31
0.98
1.52

4 lamp
120 V
Normal
Light Output

For assistance call:
listed on App Spec **1-888-GEBALLast**

Product Code: 60114

REV 1 **SIZE: 1.5" x 8"**



Resi-
PROLINE T8
Residential Electronic Ballast

PC: 60114
GE432-120RES-B
Electronic Ballasts 120 Volt
Application: (4 or 3) F32T8, Normal Light
.87BF



1 0 0 4 3 1 6 8 6 0 1 1 4 3

**WARNING**
AVERTISSEMENT!
RISK OF ELECTRIC SHOCK
RISQUE DE CHOC ÉLECTRIQUE

• Turn power off before servicing
• Éteindre avant de procéder à l'entretien
• Properly ground ballast and fixture
• Ballast et luminaire avec mise à la terre conforme

For 3 lamp operation, insulate one blue lead for 600Vrms
Install and ground per National Electrical Code



120V

120V Input Electronic Ballast
Open Circuit Voltage 600 Vrms
Min Start Temp 0°F (-18°C)
Inherent Thermal Protection
Protection thermique inhérente
Class P, Outdoor Type 1
Type HL
FCC Part 18, Consumer
Suitable for Residential Use
Sound Rated A
Product is compliant with material
restriction requirements of RoHS.

**LISTED**
FLUORESCENT
LAMP BALLAST
14VS

Assembled in China
Designed and Distributed by
General Electric Co.
Nela Park, Cleveland, OH. 44112
Transforming the Power of Light™

Use With
Lamp
Types

4 F32T8
4 F32T8/U
4 F32T8/WM
4 F32T8/25W
4 F28T8
4 F25T8
4 F17T8
3 F40T8

Line
Current
120 V

1.62
1.62
1.50
1.31
1.42
1.31
0.98
1.52

4 lamp
120 V
Normal
Light Output

For assistance call:
listed on App Spec **1-888-GEBALLast**

Product Code: 60114

SIZE: 6" x 2.6"

REV 1