## DOLCECLIMA

## Air Pro Series

### Air Pro 14 AC

Model # 2148

Color: White UPC: 810016200284 3-Year Limited Warranty





Cooling Capacity: 14,000 (9,500DOE) btu/h Heating Capacity: 11,000 btu/h\* Refrigerant: R-32 Voltage: 115

#### FUNCTIONS

- Fan Mode: Adjustable 3 speed fan with fan only mode to optimize air circulation
- O<sup>o</sup>Dehumidification mode: Reduces airflow to increase the amount of moisture removed from the space.
- Auto Mode: Regulates cooling setpoint in relation to ambient temperature for increased comfort and efficency
- Turbo mode: Maximum fan speed with greater cooling capacity.
- Sleep mode: Gradually increases the temperature setpoint to reduce noise for greater comfort at night.







ADVANCED CONTROL TOUCH DISPLAY The most advanced technology insures optimized cooling performance.



"FOLLOW ME" Extend the unit's cooling range with our innovative feature using sensors in the remote to adjust the climate in the area where the remote is located.





MOTORIZED FLAP Enjoy a higher level of comfort with customized air flow management.





HEAT PUMP\* Reverse cycle heat pump offers both heating and cooling to provide yearround comfort.

### OLIMPIA SPLENDID

# D. LCECLIMA Air Pro 14 HP

### Model # 2148

Voltage (min 109, max 127)	Volts	115
Phase	Phase	1
Hertz	Hz	60
Maximum Cooling Capacity	BTU/h	14000
Rated Cooling Capacity	BTU/h	9500
Maximum Heating Capacity	BTU/h	N/A
Rated Power Consuption Cooling	Watts	N/A
Rated Power Consuption Heating	Watts	N/A
Energy Efficiency Ratio	EER	9.9
Coefficient of Performance	COP	N/A
Dehumidification Capacity	Pints/Hr	5.9
Compressor	Туре	Rotary
Rated Load Amps	R.L.A.	7.4
Locked Rotor Amps	L.R.A.	54
Indoor Fan	Туре	Centrifugal
Speeds	#	3
Rated Load Amps	R.L.A.	<1
Power cord size	AWG/# of wires	14/3
Power cord length	Feet	6.2
Indoor Air Volume Cooling	CFM (H,M,L)	306/283/261
Indoor Air Volume Heating	CFM (H,M,L)	N/A
Outdoor Fan speeds	# of speeds	2
Exhaust Hose diameter	Inches	6
Hose length	Feet	6
Maximum Remote-Control Range	Feet	26
Dimentions w/out packaging	W/H/D	19.3" x 30.1" x 16.7"
Dimentions with packaging	W/H/D	21.1" x 35" x 19.2"
Weight w/out packaging	lbs	77.2
Weight with packaging	lbs	88
Sound Level	dBa H/M/L	56/54/52
Refrigerant	ASHRAE #	R32
Factory Refrigerant Charge	oz	20





Minimum sound pressure values are rated in ventilation mode only.