


## WARNING! COMBUSTIBLE LIQUID AND VAPOR

For Emergency information call (614) 253-8511. For additional safety and chronic hazard information, refer to the Safety Data Sheet for this product. Contains: Petroleum Distillates. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. MAY BE HARMFUL IF SWALLOWED. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

KEEP OUT OF REACH OF CHILDREN

A-C

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### LIMITED WARRANTY

If this product, when applied according to directions, fails to perform as stated, return the unused portion for a full refund or product replacement. This warranty does not include labor costs, incidental expenses, or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so these limitations may not apply to you. This warranty gives you specific legal rights, that vary from state to state. Any question regarding this warranty should be directed to your local dealer, or write Yenkin-Majestic Paint Corp., 1920 Leonard Ave., Columbus, OH 43219

Less than 500 gms/ltr VOC

### DISPOSAL

Contains no chromium, lead or mercury. Place opened, empty containers in normal refuse for disposal. Contact your sanitation department or household waste coordinator for information concerning re-use, recycling or disposal of unused oil-base paint. EAD-C1



Five Gallons (18.972 Liters)

# Majic

# Town & Country



# Aluminum Paint

## Exterior Oil Base For Grain Bins, Tanks, Machinery, and Equipment

8-0020-5 Aluminum

**WARNING! COMBUSTIBLE LIQUID AND VAPOR**

See other cautions on back panel

## TOWN & COUNTRY ALUMINUM PAINT

A ready-mixed, ready-to-use aluminum paint formulated with the finest grade leafing aluminum pigments, long wearing oils, and synthetic resins.

**USE IT ON:** Interior or exterior metal, wood, or masonry surfaces. Recommended for radiators, boilers, smoke stacks, and other surfaces where a heat-resistant coating is necessary. This coating derives its brilliance from a surface leafing pigment. Therefore, it should not be used on any surface subject to abrasion or constant rubbing.

**SURFACE PREPARATION:** All surfaces, new or previously painted, must be clean, dry and free of oil, dirt, grease, mildew, and rust. Rusted metal should be cleaned with a wire brush or sandpaper. Remove loose, scaling paint by wire brushing, scraping, or sanding. Glossy surfaces, and all protected areas not exposed to normal weathering, should be dulled by sanding. Remove oily residues from new metal surfaces by cleaning with rags saturated in mineral spirits. Surfaces with extensive rust or heavy oxidation should be cleaned to remove loose scale, dust and, debris. New masonry surfaces should be allowed to age at least 90 days before painting.

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION:** Blend the paint by pouring off the top half to two-thirds of the paint into a separate container. Stir the remainder to a uniform consistency, making sure that all aluminum pigments are evenly dispersed. Add the removed portion back into the can while mixing thoroughly. Stir occasionally during application. Apply the paint with a good quality polyester brush, short nap roller, or spray equipment. The paint should be applied liberally, finishing off in one direction. Painting should not be done during the extreme heat of the day, when the temperature is likely to fall below 50°F, or when rain is expected within 24 hours. If painting a metal roof, avoid painting when the surface is hot or in direct sunlight. Do not apply to hot surfaces. DO NOT THIN.

**DRY TIME:** 4 to 6 hours to touch; 24 hours to recoat. Temperature and humidity may affect drying time.

**COVERAGE:** Up to 3,000 sq. ft. (278 sq. meters) per 5 gallon pail on smooth surfaces. Porous surfaces require more paint. Coverage figures do not include spray loss, loss due to surface irregularities and porosity, nor material loss when mixing.

**CLEAN-UP:** Paint thinner. Danger: Rags, steel wool, or waste soaked with Town & Country Aluminum Paint may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool, or waste in a sealed water-filled metal container.

For more information, visit  
[majicpaints.com](http://majicpaints.com) or call  
1-800-848-1898 ext. 356.

Manufactured by:  
**YENKIN MAJESTIC  
PAINT CORPORATION**  
COLUMBUS, OHIO 43219