Eastman™
An RWC Brand

RWC

How To Choose the Right Gas Connector?

¿Cómo elegir un conector de gas correcto?

1. Determine Appliance Category

Category 1		Category 2	
Appliance Type	Gas Logs, Space Heaters, and Low Usage Appliances	**Appliance Type**	Water Heaters, Dryers, and Moderate Usage Appliances
Gas Flow	Up to 48,000 BTU	**Gas Flow**	Up to 102,000 BTU
Gas Connector Outer Diameter (OD)	3/8-inch	**Gas Connector Outer Diameter (OD)**	1/2-inch
Category 3		**Category 4**	
Appliance Type	Ranges, Boilers, and High Usage Appliances	**Appliance Type**	Tankless Water Heaters and Very High Usage Appliances
Gas Flow	Up to 180,000 BTU	**Gas Flow**	Up to 290,900 BTU
Gas Connector Outer Diameter (OD)	5/8-inch	**Gas Connector Outer Diameter (OD)**	1-inch

2. Determine Connector Length

Measure the distance from gas supply to appliance.

Add additional length to allow access behind appliance.

3. Determine Connector Fitting

Match the inlet of your appliance & gas shut-off valve to the fittings on the gas connector.

1. Determine la categoría del electroméstico

Categoría 1

Tipo de electrodoméstico: estufa (calidad profesional) y calefacción
Flujo de gas – Hasta 48.000 BTU
Diámetro exterior del conector de gas (OD) – 3/8 pulgadas

Categoría 2

Tipo de electrodoméstico: calentador de agua, estufa y secadora
Flujo de gas – Hasta 102.000 BTU
Diámetro exterior del conector de gas (OD) – 1/2 pulgadas

Categoría 3

Tipo de electrodoméstico: leños simulados a gas, calentador de espacios y secadora
Flujo de gas – Hasta 180.000 BTU
Diámetro exterior del conector de gas (OD) – 3/8 pulgadas

Categoría 4

Tipo de electrodoméstico: calentadores de agua sin tanque y electrodomésticos de uso muy alto
Flujo de gas – Hasta 290.900 BTU
Diámetro exterior del conector de gas (OD) – 1 pulgada

2. Determine el largo del conector

Mida la distancia desde el suministro para servicio de gas hasta el electrodoméstico.

Agregue un largo adicional para permitir el acceso detrás del electrodoméstico.

3. Determine los tipos de conectores

Haga coincidir la entrada de su electrodoméstico y la válvula de cierre de gas con los conectores del conector de gas.

