

WHITE

WHITE

WHITE

WHITE

WHITE



WINDOWS

TRIM

DOORS

¡PRECAUCIÓN! Contiene: Destilados de petróleo. Utilice en un área bien ventilada. No permita el contacto con los ojos o la piel. Use guantes y gafas de seguridad. No lo ingiere. **En caso de emergencia**, llame a un centro de control de envenenamiento al 1-800-222-1222. Refiérase a la Hoja de datos de seguridad (SDS) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

GUARANTEE: If product fails to perform when used as directed, within one year of date of purchase, call **1-888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

QUESTIONS?/¿PREGUNTAS? Call/Llame al **1-888-DAP-TIPS** or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al **1-888-327-8477** o visite dap.com.

DAP Products Inc.,
Baltimore, MD 21224

Made in the USA with U.S.
and globally sourced materials.

dap.com

©
ALEX

**Painter's
Acrylic
Latex
Caulk**

25 YR.

- **PAINTABLE**
- **EASY WATER CLEAN-UP**
- **LOW ODOR**
- **INTERIOR/EXTERIOR**

DAP® ALEX® Painter's is an all purpose acrylic latex caulk that applies smoothly & easily to a wide variety of surfaces. Ideal for sealing around windows, doors, baseboards & trim prior to painting. Paintable, low odor & easy water clean-up.

FOR BEST RESULTS: Apply in temps. above 40°F. Do not apply when rain/freezing temps. are forecasted before full cure can occur. Do not use below waterline, for filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use foam backer rod. Store away from extreme heat/cold.

INSTRUCTIONS: **1.** Surface must be clean, dry & free of old caulk, dust, debris & grease. **2.** Cut nozzle at a 45° angle to desired bead size. **3.** Load into caulk gun. **4.** Fill gap with caulk. **5.** Smooth bead. **6.** Clean up excess uncured caulk with damp sponge before it skins over. Cured caulk must be cut or scraped away. **7.** Allow to dry 2 hours (longer in cool &/or humid conditions) before painting with latex or oil-based paints. **8.** Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead

CAUTION! Contains: Petroleum distillates. Use in well ventilated area. Do not get in eyes or on skin. Use gloves and safety glasses. Do not ingest. **For emergencies**, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

NCCS Calif. ARB VOC
<1.5 wt/wt% (VOC 58 g/L)



Paint Projects

Read back panel for cautions!
¡Lea las precauciones en el
panel posterior!

10.1 fl oz (300 mL)