

The power of true commercial

Built with professional-grade components to outlast the competition.

SMART DESIGN FOR A BETTER EXPERIENCE

- Extra Large Capacity for Families and Bulky Items
- Superior Cleaning Performance
- 4 Cycle Options: Cold, Warm, Hot, and Delicate
- Separate Controls for Heavy Soil and Extra Rinse
- Quicker Drying Time Due to a Fast 300G Spin

SIGNATURE FEATURES

- 3.5 cu. ft. Capacity
- 300 G-force Extraction resulting 4 Wash Cycles in 98% moisture extraction
- 15,000+ wash cycles
- AC Motor (brushless)
- Solid Steel Counterweights
- Easy Soft-Mount Installation
- Easy Access Repair Panel

- Quiet Operation
- Add Revenue with Heavy Soil and Extra Rinse Options
- Coin and Cashless System Compatible
- Limited Parts Warranty 3/5/10 year

RATING

- · ENERGY STAR® Certified
- ADA Compliant *
- CSA Certified
- Proposition 65 Compliant
- CEC Compliant
- · NRCAN Registered



8-POINT SUSPENSION

Robust suspension features advanced technology to keep loads in balance, eliminate oversuds, and finish the cycle.



HEAVY-DUTY SKF BEARINGS

Commercial-grade bearings with 3 seals and 5 lips to protect and provide a water-tight barrier around the driveshaft.



TIME-OF-DAY PROMO PRICING

Easily programmable for multiple promotional events or happy hour pricing using the built-in real-time clock.

CROSSOVER 2.0

22 LB. CAPACITY FRONT LOAD DRYER

MODELS	
Electric Washer	WASHERFRONTL

SPECIFICATIONS	
Capacity - Ib (kg)	22 lb (10 kg)
Cylinder Volume - cu. ft. (liters)	3.5 cu. ft. (98 l)
Wash Cycles & Options	Cold, Warm, Hot, Delicate, Heavy Soil, Extra Rinse
Motor	Variable-speed, reversible, thermoprotected, high-efficiency, controlled induction
Electrical Rating - v/Hz/Ph	120V/60 Hz/1-phase
Breaker Requirements - Amps	15 A
Wash Speed - RPM	45 RPM (1050 RPM max)
Maximum G-Force	300 G
Inlet Hose - in	2x ¾ in (hose included)
Water Pressure - Psi (kPa)	10-90 psi (70-600 kPa)
Drain Hose - in (mm)	1 in (25.4 mm)
Crated Weight - Ib (kg)	314 lb (142 kg)
Uncrated Weight - Ib (kg)	299 lb (136 kg)

EQUIPMENT DIMENSIONS A. Overall Height - in (mm) B. Height to Center of Door - in (mm) C. Height to Bottom of Door - in (mm) D. Overall Width - in (mm) E. Overall Depth - in (mm) 30 1/8 in (765 mm)

F. Depth w/ Door Open 90° - in (mm)

51 % in (1300 mm)

COMPLIMENTARY PRODUCTS

Coin Accessories for Top Control Dryer (floor/side by side model)	Only necessary for coin configuration (optional)
6"Washer Base (optional)	096792
10" Washer Base (optional	096794

Actual color may vary. Dimensions are for planning purposes only.

Refer installation and servicing to qualified, licensed personnel. Always read installation and Operating Manuals and consult local codes before installation. Protect machines with properly rated circuit breakers ONLY. Warranty void if not properly installed.

Because of continuous product improvement, specifications are subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

*ADA compliant when mounted on the floor or on a base up to 6 inches high.