



AFR SMT PRO-2.0 QuietCool Advanced Roof Mount Fan

AFR SMT PRO-2.0 Specifications

Airflow	Hi: 1,922 CFM / Low: 1,344 CFM
HVI-916 Airflow (for CA)*	Hi: 1,470 CFM / Low: 970 CFM
Attic SQFT Coverage @ .75 CFM per SQFT	Covers up to 2,500 SQFT
Energy Use	Hi: 266 Watts / Low: 209 Watts
Amps	Hi: 2.31 / Low: 1.90
Motor Voltage	120 VAC, 60 Hz
# of Fan Speeds	2
Housing Diameter	16 3/4"
Rough Cut-out Diameter	17 1/4"
Overall Height	10.25"
Roof Cap Dimension	28" x 28"
Flashing	26" x 26"
Cover to Flashing Clearance	4 1/2"
Primary Flashing (included)	For roofs 3:12 to 8:12 pitch
Curb Flashing - FLA-CRB-2222 (sold separately)	For flat roofs 3:12 pitch and below
Secondary Flashing - FLA-SEC-3743 (sold separately)	For tile/cement roofs 3:12 to 8:12 pitch
Wildlife Guard	0.25" diameter holes
Paint Coating	High-quality Hybrid Black Polyester Paint Premium film integrity and extreme UV protection from fade and chalk
Controls	QuietCool Smart Control Hub
Fire Safety Sense Shut-off	182 °F
Warranty	15 Years
Shipping Weight	36 lbs.
Box Dimensions	31" x 29" x 13"
In The Box	- AFR SMT PRO-2.0 - Accessory Bag - Smart Control Hub - Cut-out Template

Features & Benefits:

- 2-speed Energy Efficient PSC motor
- QuietCool Smart App Control
- 20 foot power cord attached
- Plug and play (no wiring required)



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM

Rev. 8/9/24

Testing conducted by QC Manufacturing, Inc.

*Per Test Report #279

