



Oaks Aura Modern Ceiling Fan

Installation & Troubleshooting Manual

CAUTION

READ INSTRUCTIONS CAREFULLY FOR SAFE INSTALLATION AND FAN OPERATION



Packge Contents



Unpack your fan and check the conterts. You should have the following items

- 1.) Mountaineering buckle x1
- 2.) Downrod x2
- 3.) Coupling Cover x1
- 4.) Fan x1
- 5.) Led x1
- 6.) Lampshade x1

Dimension Reference

A.600mm B.402mm

- 7.) Remote control x1
- 8.) Hook x1
- 9.) Power cord x1
- 10.) Installation instruction x1
- 11.) Assembly kit x1



Exploded View Detail



Safety Instructions

READALLSAFETYINFORMATIONANDINSTALLATION INSTRUCTIONS BEFORE YOU BEGIN TO INSTALL THE FAN AND SAVE INSTRUCTIONS.

- All set screws of the fan must be checked andretightened where necessary before installation.
- To reduce the risk of personal injury, do not bend the blade brackets when instal ling the brackets, balancing the blades or cleaning the fan. Do not insert foreign objects between rotating fan blades.
- Before changing the fan direction, turn off the fan and wait for the fan blades to stop completely.
- The safeguards provided by these safety instructions and by the separate installation instructions are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and careare factors which can not be built into this product. These factors must be supplied by the person(s) installing, caring for and operating the fan.

WARNNG

- To avoid risk of electric shock, besure to shut off power at the main fuse or circuit breaker box before installing or servicing this fixture. Turning off the electrical power by using the light switch is not sufficient to prevent electrical shock.
- To reduce the risk of injury, install the fan so that the blades are atleast7feet (2.3 meters)above the floor and at least 18 inches (0.5 meters)from the tip of the blades to the wall.
- To reduce the risk of fire, electric shock, or personal injury, mount to outlet box marked "acceptable for fan support" and use mounting screws provided with the outlet box.
- The installation has to be in accordance with the national electrical code, ansinfpa 70-1999 and local codes. If you are unfamilar with the methods of installing electrical wiring, seek the services of a qualified licensed electrician.

INSTALLATIONINSTRUCTIONS IMPORTANT:

- before you begin installation, carefully fread all information provided in the safety instructions and installation instructions.if in doubt, consult a qualified electrician.
- save al linstructions.

NOTE: The fan weight is 17.64 lbs(8 kgs). Be sure the ouutlet box you are using is securely attached to the building structure and can support the full weight of thefan. Failure to do so can result in serious injury.

Installation Steps



Turn OFF the electric circuit at the main fuse or circuit breaker box.



Fan blades to the ground shall not less than 2.3 meters.



The hook must be securely fastened to a structural ceiling member.



Loosen parts at the yoke of the downrod assembly.



Wood Screws

To use wood screws to fix hook for wooden or false ceiling.



Assemble the coupling cover onto the downrod.



Insert the downrod to the yoke, then fix with the bolt and screws.



Remove the screws.



Connect the power cord and fan power cord according to the diagram.



Install the coupling cover.



Attach the mountaineering buckle to the hook.



Install the LED and lampshade on the ceiling fan according to the diagram.



Installation is completed.



Turm on the electric power at the main fuse or circuit breaker box.

Remote control and Wiring instructions

WIRING INSTRUCTIONS : Before doing wiring, ensure that you have shut down the power supply!

Your fan is supplied with a radio frequency remote control unit, and the fan does not have a pull switch for speed control, the fan can only be controlled by remote control You can find the unit in the box. Before connecting the wiring.

CODING RESET

If you have multiple devices or controller matching issues, please follow the steps below to rest the codes:

1. Press an hold on the serve key more than 3s to code the receiver powered in 10s. 2. If the controller and receiver code successfully, the buzzer will ring twice. NOTE

An existing wall dimmer switch must be replaced with a single ON/OFF wall switch before installing a Fan to ensure consistent power flow from the switch to the fan. You cannot operate our ceiling fan with a wall dimmer switch

Power Specifications

Voltage	Fan	Led	Transmitter batteries
120V 60Hz	26W	3000K/4000K/6000K 9W / 18W / 9W	AAA 1.5V x2 (included)

Transmitter function keys

ALL OFF	Light&Fan all OFF	
1-6	Fan Speed	
\\$	Swing	
F/R	Forward/Reverse Switch	
FAN/OFF	Fan Off	
SETUP	Code Key	
් ON රූ OFF	Light On/Off	
(K	Color temperature switching	
Ś	Night light	
°Ç°-	Brightness -	
\$. +	Brightness +	
K -	Color temperature-	
®+	Color Temperature+	
2H	Fan Stop After 2 Hour	



Controller

PROBLEM

SUGGESTED REMEDY

1. If fan does not start:	 Check main and branch circuit fuses or circuit breakers. Make sure that the wall control is turned "ON". CAUTION: Make sure main power is turned off. 	
2. If fan sounds noisy:	 Make sure all screws in motor housing are snug. (not over tightened) Make sure the screws which attach thefan blade bracket to the motor are tight. Make sure wire connectors in switcl housing are not rattling against each other or against the interior wall of the switch housing. CAUTION: Make sure main power is turned off before entering switch housing. Some fan motors are sensitive to siignals from Solid State variable speed controls. DO NOT USE a Solid State variable speed control. Allow "break-in" period of 24 hours.Most noises associated with a new fan will disappear after this period. 	
3.If fan wobbles:	 All blades are weighed and grouped byweight. Natural woods vary in density which could cause the fan to wobble even though all blades are weight-matched. The following procedures should eliminate most of the wobble. Check for wobble after each step. 1. Check that all blades are screwed firmly into blade holders. 2.Check that all blade holders are tightened securely to motor. 3. Make sure that canopy and mounting plate are tightened securely to ceiling junction box and junction box is mounted firmly to ceiling joist. 4. Most wobble problems of fan are caused when blades are not in equal level. To check the blade levels, select a point on the ceiling above the tip of any blade. Measure the distance from the ceilingto the blade tip, to an accuracy of 1/8 inch. Rotate the blades until the next bleade is in the measuring position. Repeat measurement for each blade. To adjust a blade bracket at the screw closest to the motor. To adjust a blade tip up, insert washer (not supplied) between the blade and blade bracket at the screw closest to the motor. To adjust a bladle tip up, insert washer (not supplied) between the blades coulc redistribute the weight and possibly result in smoother operation. 	
4. If light does not work:	 Check blue wire from fan to make sure iit is connected to hot wire from supply wire coming out of the ceiling. Check for loose or disconnected wires in fan switch housing. Check for loose or disconnected wires in light kit. Check for faulty light bulbs. CAUTION: Make sure main circuit is turned off before entering switch housing. 	

APP OPERATING INSTRUCTIONS

- 1.Scan the QR code to download the app.
- 2.Download the corresponding OS app from your phone and install it, then add devices in order.









SETP 4 Set the name of the device.



SETP 2 Download the app.



SETP 5 After setting the name, open the Bluetooth on your phone and click on the device to enter the operation interface.



SETP 3 Add equipment according to the position of the ceiling fan.



Within 5 seconds of turning on the main power of the ceiling fan, press the button to complete the connection between the phone and the ceiling fan. After successful connection, the LED will flash once.

PAGE:10/10