AM CONSERVATION GROUP//COMMERCIAL LIGHTING

LED T8 UL TYPE B DOUBLE-END BYPASS L17T8G35BDE - L17T8G50BDE SERIES

INSTRUCTIONS

1. PRODUCT FEATURES:

- UL certified
- Full glass housing: No Aging, Yellowing, Bending.



2. PRODUCT APPLICATIONS:

Widely used in residential buildings, offices, shopping malls, supermarkets, hospitals, assembly lines, warehouses, etc. for energy saving illumination.

3. INSTALLATION INSTRUCTIONS:

Please comply with all instructions to ensure that the product is installed in safe conditions.

A SAFETY PRECAUTIONS:

For yours and others' safety, please read the precaution's carefully before installation:

- (1). Product should be installed by qualified electrician.
- (2). Switch off the power supply before beginning work and make sure the connection is correct before powering on.
- (3). NOT FOR EMERGENCY LIGHTING.
- (4). Direct replacement for 32/30/28/25W 48T8 lamps only.

(5). CAUTION: RISK OF FIRE. USE ONLY IN PLACE OF FLUORESCENT LAMPS SPECIFIED ON LABEL.

The units covered by this report were intended to retrofit surface mount, Type IC or non-IC recessed mount Listed fluorescent luminaires that use maximum 4 tubular lamps. The minimum lamp compartment dimensions are tabulated below:

MODEL NUMBER	MINIMUM COMPARTMENT DIMENSIONS (LENGTH X WIDTH X HEIGHT) (MM)	LAMP QUANTITY
LYYT8GXXBDE	1230 x 340 x 45	4
conditions: (1) th	plies with Part 15 of the FCC Rules. Operation is subject to the is device may not cause harmful interference, and (2) this devic ived, including interference that may cause undesired operation	ce must accept any



AM CONSERVATION GROUP//COMMERCIAL LIGHTING

LED T8 UL TYPE B DOUBLE-END BYPASS L17T8G35BDE - L17T8G50BDE SERIES

WIRING DIAGRAMS

THE BELOW BALLAST WIRING REPRESENTS TYPICAL CONFIGURATION.

The actual ballast wiring varies according to ballast model. It is not necessary to change the socket (if it is in good condition) to operate double ended lamps, regardless the type of sockets. Please make sure one side of fixture is connected to Live (L) and the other side to Neutral (N).





AM CONSERVATION GROUP//COMMERCIAL LIGHTING

LED T8 UL TYPE B DOUBLE-END BYPASS L17T8G35BDE - L17T8G50BDE SERIES





0-