

72" x 36" freestanding bath with straight shroud **K-6366**

Features

- Freestanding design creates a striking focal point in your bathing area
- Integral lumbar support on both ends
- 16" (406 mm) depth offers a deep soaking experience
- Wide deck along one side simplifies installation and provides support for getting in and out of bath
- Straight shroud
- Textured bottom surface

Material

Acrylic

Installation

- Center drain
- Freestanding

Required Products/Accessories

For freestanding installation K-7265 Brass toe tap bath drain

Recommended Products/Accessories

K-23726 Drain treatment



Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662

KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0 White









72" x 36" freestanding bath with straight shroud **K-6366**


No change in measurements if connected with drain illustrated. (K-7265)


Recommended Faucet Location





Recommended Faucet Hole Location





Technical Information

All product dimensions are nominal.

Drain location: Center

Basin area, bottom: 50" x 25-1/2" (1270 mm x 648 mm) Basin area, top: 61" x 27-1/2" (1549 mm x 699 mm)

Weight: 152 lbs (68.9 kg)

Minimum floor load: 48.8 lbs/ft² (238.3 kg/m²)

Water depth: 15-11/16" (399 mm)

Water capacity: 90 gal (340.7 L)

Template: Footprint, 1245664, not required, not

included

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

This bath is designed for freestanding installation only.

Do not support the load weight of the bath by the rim.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.

