

16587-A



Call Us First!
DO NOT RETURN TO STORE.

For questions on assembly or for general inquiries, you may contact us in the following ways:

Call customer service: **1-877-743-3400**

AVOID THE WAIT!

visit us online at
help.backyardproducts.com

- Submit a help request
- Answers to frequently asked questions
- Live chat with an agent



Did you enjoy building your shed?

JOIN OUR TEAM
AND MAKE UP TO \$1,500/WEEK*

Call a Recruiter Today! 734-365-7000




Flexible schedule



No selling,
just building



Bonus incentives
available



*based on number of completed installations




Win \$500

A new winner is selected every 2 months.

Review your product for the chance to win a **\$500 Visa Gift Card**.



How to Enter:



Open camera.
Aim. Tap.



1

Scan
QR code above.

2

Click
'write a review'

3

Find your product.
Tell us what you think.

4


Submit your review.
You'll be notified by e-mail if
you've won the \$500 gift card.

Write a Backyard Products, LLC. product review at backyardreviews.net for a chance to win a \$500 Visa gift card. No purchase necessary to enter. Must be legal U.S. resident (including DC & Puerto Rico), 18 or older to participate. Taxes on prize are responsibility of winner. Odds of winning depend on the number of eligible reviews received. Void where prohibited. For complete details and official rules, visit <https://backyardreviews.net/sweepstakes-rules>.

GABLE 10' x 8' (305 x 244 cm)

ACTUAL FLOOR SIZE IS 116-1/2 x 96" (295,9 x 243,8 cm)

KEEP THIS MANUAL FOR FUTURE REFERENCE



IMPORTANT!



READ INSTRUCTIONS THOROUGHLY PRIOR TO BEGINNING ASSEMBLY.

BEFORE YOU BEGIN

- **BUILDING RESTRICTIONS AND APPROVALS**

Be sure to check local building department and homeowners association for specific restrictions and/ or requirements before building.

- **ENGINEERED DRAWINGS**

Contact our Customer Service Team if engineered drawings are needed to pull local permits.

- **SURFACE PREPARATION**

To ensure proper assembly you must build your shed on a level surface.

Recommended methods and materials to level your shed are listed on page 9.

- **CHECK ALL PARTS**

Inventory all parts listed on pages 4-7.

- **ADDITIONAL MATERIALS**

You will need additional materials to complete your shed. See page 3 for required and optional materials and quantities.



*****CONTACT OUR CUSTOMER SERVICE TEAM
IF ANY PARTS ARE MISSING OR DAMAGED*****

















- Order form and warranty at back of manual -

Call: 1-877-743-3400 email: customerservice@backyardproductsllc.com

TOOLS

Required

- ☐ Phillips Screwdriver 
- ☐ Drill / Driver 
 - ☐ 3/8" Drill Bit
 - ☐ #2 Philips Drive Bit
- ☐ Hammer 
- ☐ Pencil 
- ☐ Tape Measure 
- ☐ Square  or 
- ☐ Level 

- ☐ Chalk Line 
- ☐ Utility Knife 
 - ☐ Shingle Blades
- ☐ Caulk Gun 
- ☐ Exterior rated Wood Glue 
- ☐ Ladder 
- ☐ Paint Tools 

Optional

- ☐ Tool Belt/ Nail Pouch 
- ☐ Safety Glasses 
- ☐ Nail Gun 
 - Gun Nails
- ☐ Gloves 
- ☐ Clamps 

Safety! Always use approved safety glasses during assembly.

HELPFUL REMINDER SYMBOLS

Look for these symbols for helpful reminders throughout this manual.



= Assistance Required; two or more people.



= Ensure squareness.



= Important required step or operation.



= Helpful assembly hint.



= Mark part with pencil.



= Beginning of steps for assembly or installation.



= You have finished the assembly or installation.






= Level

ORIENT LUMBER AND TRIM FOR BEST APPEARANCE

Framing lumber is graded for structural strength and not appearance. Exterior trim is graded for one good side.

Always install the material leaving the best edge and best surface visible. Please remember that these blemishes in no way negatively affect the strength or integrity of our product. (See Fig. A, B, C.)



ADDITIONAL MATERIALS


FOUNDATION OR FLOOR MATERIALS

- This shed kit includes a wood floor frame, it does not include floor panels.
- This shed does not include any leveling materials.
- See the **FLOOR LEVELING** section on page 9 for recommended methods and suggested materials to properly level your floor, as this will vary depending on your specific site.

REINFORCED WOOD FLOOR FRAME (OPTIONAL)


IMPORTANT! The included floor has been designed for general use. Depending on your specific use you may want to construct a heavy duty floor frame by adding additional floor joists (shown below as shaded). Below is a list of additional materials (not included).

- ☐ **x5** 2 x 4 x 8' (5,1 x 10,2 x 243,8 cm) Treated Lumber
- Cut lumber to 2 x 4 x 93" (5,1 x 10,2 x 236,2 cm) Treated Lumber
- ☐ **x20** ea. 3" (7,6 cm) hot-dipped galvanized nails



COMPLETING YOUR SHED

You will need these additional materials:

- | | |
|---|---|
| <input type="checkbox"/> 3-TAB SHINGLES5 Bundles | <input type="checkbox"/> 1" GALVANIZED ROOFING NAILS 2 Lbs
For shingles. |
| <input type="checkbox"/> PAINT FOR SIDING2 Gallons
Use 100% acrylic latex exterior paint. (2) coat recommended. | <input type="checkbox"/> PAINT FOR TRIM1 Quart
Use 100% acrylic latex exterior paint. |
| <input type="checkbox"/> CAULK2 Tubes
Use acrylic latex exterior caulk that is paintable.  | |


OPTIONAL MATERIALS

- | | |
|---|--|
| <input type="checkbox"/> DRIP EDGE 40 Feet | <input type="checkbox"/> #15 ROOFING FELT
To cover 100 Sq. Ft. of roof area. |
| | <input type="checkbox"/> 1" GALVANIZED ROOFING NAILS1/4 Lb
For roofing felt. |

REFER TO THE BACK OF THIS MANUAL AND THE MANUFACTURER'S INSTRUCTIONS FOR INSTALLATION OF SHINGLES, DRIP EDGE AND FELT.

PARTS IDENTIFICATION AND SIZES

Part identification is stamped on some parts.



• Check these locations for Part stamps

Nominal Board Size	Actual Size
2" x 4".....	1-1/2" x 3-1/2" (3,8 x 8,9 cm)
1" x 4".....	3/4" x 3-1/2" (1,9 x 8,9 cm)
2" x 3".....	1-1/2" x 2-1/2" (3,8 x 6,3 cm)
1" x 3".....	3/4" x 2-1/2" (1,9 x 6,3 cm)




PARTS LIST



INVENTORY YOUR PARTS before you begin.

We suggest sorting parts by the category they are listed in.













FLOOR


- ☐ x2  2 x 4 x 24" (5,1 x 10,2 x 61 cm)
- ☐ x2  2 x 4 x 92-1/2" (5,1 x 10,2 x 235 cm)
- ☐ x6  2 x 4 x 93" (5,1 x 10,2 x 236,2 cm)

Treated lumber is stamped:


TREATED

WALLS



- ☐ x1  2 x 4 x 9" (5,1 x 10,2 x 22,9 cm)
- ☐ x4  2 x 4 x 14-13/16" (5,1 x 10,2 x 37,6 cm)
- ☐ x2  2 x 4 x 17" (5,1 x 10,2 x 43,2 cm)
- ☐ x1  2 x 4 x 29" (5,1 x 10,2 x 73,6 cm)
- ☐ x2  2 x 4 x 42-3/4" (5,1 x 10,2 x 108,6 cm)
- ☐ x1  2 x 4 x 44-1/2" (5,1 x 10,2 x 113 cm)
- ☐ x2  2 x 4 x 66-3/4" (5,1 x 10,2 x 169,6 cm)
- ☐ x18  2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)
- ☐ x1  2 x 4 x 80-1/2" (5,1 x 10,2 x 204,5 cm)
- ☐ x4  2 x 4 x 96" (5,1 x 10,2 x 243,8 cm)
- ☐ x2  2 x 6 x 21-1/4" (5,1 x 15,2 x 54 cm)
- ☐ x2  2 x 6 x 96" (5,1 x 15,2 x 243,8 cm)

- ☐ x1  1 x 3 x 5" (2,5 x 7,6 x 12,7 cm)









Gauge Block for 3/4" (1,9 cm) measurement



ROOF

- ☐ x8  GUSSET
- ☐ x8  2 x 4 x 54-1/8" (5,1 x 10,2 x 137,5 cm)
- ☐ x2  1 x 4 x 60" (2,5 x 10,2 x 152,4 cm)

TRIM


- ☐ x4  19/32" x 2-1/2" x 8" (1,5 x 6,4 x 20,3 cm)
- ☐ x2  2 x 3 x 22" (5,1 x 7,6 x 55,9 cm)
- ☐ x6  19/32" x 2-1/2" x 22-1/4" (1,5 x 6,4 x 56,5 cm)
- ☐ x2  19/32" x 2-1/2" x 22-5/8" (1,5 x 6,4 x 57,5 cm)
- ☐ x4  2 x 4 x 56" (5,1 x 10,2 x 142,2 cm)
- ☐ x8  3/8" x 1-3/4" x 72" (1 x 4,4 x 182,9 cm) CORNER TRIM
- ☐ x1  5/8" x 3" x 96" (1,6 x 7,6 x 243,8 cm) OSB
- ☐ x2  2 x 3 x 96" (5,1 x 7,6 x 243,8 cm)

DOOR

- ☐ x2  69" (175,3) Door Stiffener


WALL PANEL & DOOR PARTS LIST

NOTE: Panel parts are not stamped with part identification.



ROOF PANELS

Roof panels are 7/16" (1,1 cm) thick.



NOTES

FLOOR PANELS (Not Included)

You will need floor panels to complete your floor. • Floor panel sizes and quantities shown below.

NOTE: Use a minimum of 5/8" (1,6 cm) oriented strand board (OSB).



x1



20-1/2 x 96"
(60,6 x 243,8 cm)



x2



48 x 96"
(121,9 x 243,8 cm)

NAIL BOXES




x2 BOXES



3" (7,6 cm)







x4 BOXES



2" (5,1 cm)

NOTES

WINDOW & DOOR HARDWARE (Not actual size)




56" (142,2 cm) METAL THRESHOLD



3/4" (1,9 cm)

Bagged separately - special coating



1-1/2" (3,8 cm)

FASTENER/HARDWARE BAG



1-1/2" (3,8 cm)



2" (5,1 cm)



3" (7,6 cm)



2" (5,1 cm)



1-1/4" (3,2 cm)



1" (2,5 cm)



3/4" (1,9 cm)




1/2" (1,3 cm)



1/2" (1,3 cm)

NOTES

BUILDING ANATOMY



All of our buildings have been engineered to withstand demanding wind and snow loads. If you live in an area with extreme wind/snow load requirement, contact us and we can assist with engineering to meet your local codes.


- ❖ 1 Sub-assembled doors with attached hinges.
- ❖ 2 2x3 wall studs have been engineered to support roof load and to meet demanding wind loads.
- ❖ 3 Sidewall top and bottom plates tie wall studs together and provide nailing support for top and bottom edge of siding.
- ❖ 4 Siding overhangs the wall framing and floor to keep the elements out.
- ❖ 5 Collar tie maintains door frame integrity.
- ❖ 6 Includes treated floor frame and sturdy Oriented Strand Board (OSB) floor deck.

FLOOR LEVELING OPTIONS

There are multiple ways to level your floor frame. Our recommended leveling method is shown below.
Leveling materials are not included in this kit.

PREFERRED METHOD - 4x4 TREATED RUNNERS

- 3" (7,6 cm) Screws angled into 4x4.
- (2) at each point frame and 4x4 touch.




MATERIAL REQUIRED

- ☐ x2 4" x 4" x 10' (8,9 x 8,9 x 304,8 cm) Treated Lumber
- ☐ Fasteners for Frame to 4" x 4". (3" (7,6 cm) Screws shown as one option.) Minimum (24) 3" (7,6 cm) screws / exterior grade.

⚠ Use only wood treated for ground contact and fasteners approved for use with treated wood.

⚠ Always support frame seams.



LEVELING METHODS

- Level under 4x4 runners only.
- Locate leveling material 12" (30,5 cm) from ends of runners and no more than 48" (121,9 cm) apart.
- Asphalt shingles should be used between 4x4 runners and blocks or treated lumber.
Never use shingles in direct contact with ground.
- For best results and aiding in water drainage use gravel under each concrete block.

LEVELING MATERIALS

- ☐ Gravel
- ☐ Solid Masonry Blocks in 1", 2", 4" or 8" thickness
- ☐ 2x4 Treated Lumber
- ☐ Asphalt Shingles


⚠ Leveling higher than 16" (40,3 cm) not recommended.

CONCRETE

- If you are building your shed on a concrete foundation see the following page.




CONCRETE FOUNDATION

Your kit contains all materials to construct a wooden floor.
If you choose to install your kit on a concrete slab refer to the diagram below.



Building Size	Actual Size	A	B	C
10'x 8' (304,8 x 243,8 cm)	116-1/2" x 96" (295,9 x 243,8 cm)	116-1/2" (295,9 cm)	89" (226,1 cm)	96" (243,8 cm)

Requires:

- ☐ x2 2 x 4 x 10' (5,1 x 10,2 x 304,8 cm)  MUST be treated lumber.
- ☐ x2 2 x 4 x 8' (5,1 x 10,2 x 243,8 cm)  MUST be treated lumber.
- ☐ x1 Caulk 

 Allow new concrete slabs to cure for at least seven (7) days.

- A treated 2 x 4 sill plate is required when installing your shed on concrete. Hint: Use treated lumber in your kit or purchase full length treated lumber.
- Use a high quality exterior grade caulk beneath all sill plates.
- Fasten 2 x 4 sill plates to slab with approved concrete anchors (fasteners not included).
- Check local code for concrete foundation requirements.

NOTES

FLOOR FRAME

STOP!



LEVEL AND SQUARE FLOOR FRAME



Before attaching floor decking, it is important to level and square the floor frame. A level and square floor frame is required to correctly construct your shed.

STOP!



✓ BEGIN

- 1 See page 9 for the preferred floor leveling method.
- 2 Use level and check the frame is level before applying floor panels.
- 3 Check for frame squareness by measuring diagonally across corners. If the measurements are the same, the frame is square. The diagonal measurement will be approximately 151" (383,5 cm).
- 4 When the frame is level and square secure one side of frame to the 4x4 runners with one fastener at ends of each runner. Move to the opposite end of the frame. Secure the frame to 4x4 runners with one fastener at ends of each runner making sure the frame remains square (Fig A).




Fig. A





FINISH


After leveling and squaring your floor floor, fasten the frame to 4x4s at each connection where the frame contacts the 4x4 runners .


FLOOR FRAME

PARTS REQUIRED:


x 28  3" (7,6 cm)

x2  **TREATED**
2 x 4 x 24" (5,1 x 10,2 x 61 cm)

x6  **TREATED**
2 x 4 x 93" (5,1 x 10,2 x 236,2 cm)

x2  **TREATED**
2 x 4 x 92-1/2" (5,1 x 10,2 x 235 cm)

NOTE: Look for
TREATED
Stamp



✓ BEGIN



1 Arrange parts as shown on flat surface. Measure and mark each dimension from end of boards.

2 Use (2) 3" (7,6 cm) nails at each mark, and (4) 3" (7,6 cm) nails at seams as shown.




FINISH

3 You have finished your floor frame. Proceed to level and square frame.



HINT:
For easier nailing
stand on frame.



FLOOR


PARTS REQUIRED:

x1



5/8 x 48 x 96"
(1,6 x 121,9 x 243,8 cm)



x55



Ensure your floor frame is square by installing one panel and squaring frame.




BEGIN


- 1 Attach the 48 x 96" (121,9 x 243,8 cm) panel with the rough side up (painted-grid lines side) with the 48" (121,9 cm) edge and corner flush to the floor frame (**Fig A**). Secure panel with (2) 2" (5,1 cm) nails in the corners.
- 2 Move to the opposite side. Using the long edge of the panel as a lever, move the panel side-to-side until corner is flush to the floor frame (**Fig. B**). Secure panel with (2) 2" (5,1 cm) nails in the corners.
- 3 Check the floor frame is square by measuring diagonally across the frame corners. If the measurements are the same your floor frame is square. The measurement will be approximately 151" (383,5 cm) (**Fig. C**).
- 4 Continue attaching the panel with 2" (5,1 cm) nails 6" (15,2 cm) apart on edges, and 12" (30,5 cm) apart inside panel.





FLOOR PANELS

PARTS REQUIRED:




- 5 Continue installing panels with rough side up (painted grid lines).
- 6 Use a chalk line or grid lines on panel for 2" (5,1 cm) nails 6" (15,2 cm) apart on edges, and 12" (30,5 cm) apart inside panels.
-  **FINISH**
- 7 You have finished attaching your floor panels.



IMPORTANT!


STOP!

Check the floor frame is level after installing floor panels. Re-level if needed.



HINT:

- The floor should be used as a level work surface for wall construction.
- Organize your wall sections during sub-assembly to avoid over-handling of the walls.





SIDE WALL FRAMES

PARTS REQUIRED:

x10 **UM**
2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)

x4 **TP**
2 x 4 x 96" (5,1 x 10,2 x 243,8 cm)

x40  3" (7,6 cm)



Build (2) identical side walls.



✓ **BEGIN**

1 Arrange parts on floor as shown.

Secure with (2) 3" nails at connection.



Repeat steps to build the second side wall frame.

HINT:
For easier nailing
stand on frame.



SIDE WALL PANELS





PARTS REQUIRED:



Install all panels with the primed side facing up.




! Ensure your wall frame is square by installing one panel and squaring the frame.

- 2** Place (1) 46-1/8" x 72" panel onto wall frame, as shown. Use the gauge block to mark the 3/4" measurement on the wall stud. Secure panel with (2) 2" nails in the corners (**Fig. A**).
- 3** Move to the opposite end. Using the long edge of the panel as a lever move the panel side-to-side until you have a 3/4" measurement on the wall stud. Secure corner with (2) 2" nails (**Fig. B**).
- 4** Complete securing the panel with 2" nails spaced 6" apart on edges and 12" apart inside panel.




SIDE WALL PANELS



PARTS REQUIRED:



- 5** Install 2nd 48" x 72" panel flush to installed panel.
Secure panels 2" nails spaced 6" apart on edges and 12" apart inside.



Repeat steps 2 - 5 to install panels on your 2nd side wall frame.



Your (2) side walls are now assembled.


BACK WALL FRAME


PARTS REQUIRED:

x2 **CFA**
2 x 4 x 42-3/4" (5,1 x 10,2 x 108,6 cm)

x2 **CDA**
2 x 4 x 66-3/4" (5,1 x 10,2 x 169,6 cm)

x4 **UM**
2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)


x20  3" (7,6 cm)





✓ BEGIN

1 Arrange parts on edge on floor. Measure and mark.

Secure parts with (2) 3" nails at each mark and (4) 3" nails at seams.





HINT:
For easier nailing
stand on frame.



BACK WALL

PARTS REQUIRED:




Install all panels with the primed side facing up.



Ensure your wall frame is square by installing one panel and squaring the frame.




- 3 Place (1) 46-1/8" x 72" panel onto wall frame, as shown.
Use the gauge block to mark the 3/4" measurement on the wall stud.

Secure panel with (2) 2" nails in the corners (**Fig. A**).






- 4 Move to the opposite end. Using the long edge of the panel as a lever move the panel side-to-side until you have a 3/4" measurement on the wall stud. Secure corner with (2) 2" nails (**Fig. B**).

- 5 Complete securing the panel with 2" nails spaced 6" apart on edges and 12" apart inside panel.



BACK WALL

PARTS REQUIRED:





- 6** Install **23-7/8" x 72"** panel flush to installed panel.

Secure with 2" nails spaced 6" apart.



For squareness maintain flush along panel edges.




- 7** Install 2nd **46-1/8" x 72"** panel flush to installed panel.

Secure with 2" nails spaced 6" apart on edges and 12" apart inside panel.




For squareness maintain flush along panel edges.



FINISH

Your back wall is now assembled.

Carefully flip your back wall over.



FRONT WALL FRAME

PARTS REQUIRED:

x1 **UU**

2 x 4 x 9" (5,1 x 10,2 x 22,9 cm)

x1 **CHA**

2 x 4 x 29" (5,1 x 10,2 x 73,6 cm)

x1 **STL**

2 x 4 x 44-1/2" (5,1 x 10,2 x 113 cm)

x4

UM



2 x 4 x 68" (5,1 x 10,2 x 172,7 cm)

x1

CGA

2 x 4 x 80-1/2" (5,1 x 10,2 x 204,5 cm)

x18






✓ BEGIN

1 Arrange parts on edge on floor as shown. Measure and mark.


Secure parts with (2) 3" nails at each mark and (4) 3" nails at seams.

HINT:
For easier nailing
stand on frame.






FRONT WALL PANELS

PARTS REQUIRED:




x1 Temporary Brace
69" (175,3) Door Stiffener




Install all panels with the primed side facing up.

- 2** Install (1) 48" x 72" panel (with window cutout) and (1) 2-1/2" x 72" panel on wall frame, as shown. Ensure panels are flush to the top plate and studs. Secure panels with 2" nails spaced 6" apart on edges and 12" apart inside panel.



- 3** Install as temporary brace to maintain 56" (142,2 cm) dimension. Secure with (2) 3" screws.



Flip front wall over to install window framing.


FRONT WALL

PARTS REQUIRED:


x2 **CCA**
2 x 4 x 17" (5,1 x 10,2 x 43,2 cm)


x8 3" (7,6 cm)

x6 2" (5,1 cm)



- 4** Place (2) **CCA** on edge flush to window opening.
Secure to frame with (8) 3" nails (**Fig A**).



- 5** *Flip front wall over again, with panels facing up.* 
Secure panel to window framing with 2" nails spaced 6" apart.





FINISH

Your front wall is now assembled
Proceed to standing your walls.

BACK / FRONT WALL INSTALLATION

PARTS REQUIRED:


x2 **NPE** 
2 x 4 x 54-1/8" (5,1 x 10,2 x 137,5 cm)



✓ BEGIN

1 Center back wall assembly on the 116-1/2" (295,9 cm) floor dimension.

2 Install rafter **NPE** as a temporary brace.
Secure with (2) 3" screws.




3 Secure lower edge of panel to floor frame with 2" nails spaced 6" apart.
Angle nails into floor frame (**Fig. A**).

4 Secure frame to floor with (2) 3" nails between studs (**Fig. B**).



Repeat steps to install your front wall.




FINISH
Your back and front walls are now standing.

SIDE WALLS INSTALLATION


PARTS REQUIRED:

x32




2" (5,1 cm)

x16




3" (7,6 cm)

x4




3" (7,6 cm)


x56



1-1/2" (3,8 cm)




✓ BEGIN




Right Wall

- 1 Center right side wall on floor.
Secure the lower side wall corner to the back wall stud with (1) 1-1/2" nail (**Fig A**).
- 2 Ensure the measurement between the panel edges are the same along the corner.
Secure with (1) 1-1/2" nail in the upper corner (**Fig B**).
- 3 Secure front and back panels to side wall studs with 2" nails spaced 6" apart.
Secure bottom of panel to floor frame with 2" nails spaced 6" apart. Angle nails into floor frame (**Fig A**).
- 4 Secure the side wall top plate to the back and front wall top plates with (2) 3" screws at an angle (**Fig C**).
Secure bottom plate to floor with (2) 3" nails between wall studs.



Repeat steps to install your left side wall.

Left Wall



FINISH

You have finished standing your (2) side walls
Remove temporary parts.

WALL DOUBLERS

PARTS REQUIRED:

x2 **CR**
2 x 6 x 21-1/4" (5,1 x 15,2 x 54 cm)

x2 **VX**
2 x 6 x 96" (5,1 x 15,2 x 243,8 cm)



x28 3" (7,6 cm)



✓ **BEGIN**

- 1 Install parts flush to inside of front and back top plates (**Fig. A**) and flush to wall panels (**Fig. B**).


Secure with (2) 3" nails spaced 24" apart and with (4) nails at seams, as shown.





Your wall doublers are now installed.


RAFTERS

PARTS REQUIRED:

x8  6 x 24" (15,2 x 61 cm)

x2  3" (7,6 cm) x96 

2" (5,1 cm)



x8  **NPE**
2 x 4 x 54-1/8" (5,1 x 10,2 x 137,5 cm)

x1  **CBA** Temporary Part
2 x 4 x 14-13/16" (5,1 x 10,2 x 37,6 cm)




✓ BEGIN

- 1 Position and square **CBA** as a temporary jig at measurement shown. Secure with (2) 3" screws.
- 2 Place (2) rafter halves **NPE** in the corner of back and side wall and **CBA**. Ensure rafters are flush at peak.




- 3 Secure gusset to rafters with (12) 2" nails in pattern shown.
- 4 Flip over rafter assembly and repeat STEPS 2-4 to attach second gusset to other side.
- 5 Repeat STEPS 2 - 5 to build (3) additional rafter assemblies. Remove **CBA**.



Your rafters are now assembled.

RAFTER INSTALLATION

PARTS REQUIRED:

x16  3" (7,6 cm)





✓ BEGIN

1 Mark doubler to measurements shown.

Locate rafters centered on marks.

2 Secure rafters in position with (2) 3" screws at each connection (**Fig. A**).


Drive screw through top plate into doubler (**Fig. B**).



FINISH Your rafters are now installed.

GABLE UNITS


PARTS REQUIRED:



x4 **CBA**

2 x 4 x 14-13/16" (5,1 x 10,2 x 37,6 cm)



x28 1-1/2" (3,8 cm)




Assemble (2) gable units. Install gable panels with primed side up.

✓ BEGIN

- 1 Arrange parts flat on floor to measurements shown. Measure and mark center of gable panel. Secure center gable panel to (2) **CBA** with 1-1/2" nails.
- 2 Install left and right gable panels flush to center gable panel. Secure with 1-1/2" nails spaced evenly.



Repeat steps to build 2nd gable.




Your gable units are now assembled.


GABLE UNIT INSTALLATION

PARTS REQUIRED:


x42



x8




✓ BEGIN



- 1 Center gable assembly on side wall with mark.
Ensure gable connectors **CBA** are sitting flush on top of frame.
 Panels should be flush to doublers, as shown (Fig. A, B).

Secure panel to top plate with 2" nails spaced 6" apart.

- 2 Working inside, secure gable connectors to top plate with (2) 3" screws at an angle.



Repeat steps to install opposite side gable unit




FINISH

Your gable units are now installed.

GABLE TRIM INSTALLATION

PARTS REQUIRED:


x4 **MCB**
2 x 4 x 56" (5,1 x 10,2 x 142,2 cm)

x40 
1-1/4" (3,2 cm)




✓ BEGIN


1 Install (1) gable trim **MCB** flush along top of panel and with end flush to center mark (**Fig. A**). Secure trim to gable unit panels with 1-1/4" screws spaced 6" apart. Screw through panels into gable trim.



2 Repeat step 1 to install 2nd gable trim flush to installed trim (**Fig. B**).



Repeat steps to install gable trim on opposite side.




Your gable trim is now installed.

FASCIA TRIM

PARTS REQUIRED:

x2 **PRD**
2 x 3 x 22" (5,1 x 7,6 x 55,9 cm)

x2 **PT**
2 x 3 x 96" (5,1 x 7,6 x 243,8 cm)

x28 


2" (5,1 cm)




 **BEGIN**

1 Place parts flush to bottom of doubler, as shown (**Fig. A**).

Secure with 2" finish nails spaced 24" apart.



Repeat process on opposite side.








 **FINISH**

Your fascia trim is now installed.

ROOF PANELS


PARTS REQUIRED:

x2		7/16 x 8-1/2 x 96" (1,1 x 21,6 x 243,8 cm)	x 2		7/16 x 8-1/2 x 23-7/8" (1,1 x 21,6 x 60,6 cm)
x1		7/16 x 48 x 96" (1,1 x 121,9 x 243,8 cm)	x 2		7/16 x 23-7/8 x 48" (1,1 x 60,6 x 121,9 cm)



Roof panels may cause serious injury until securely fastened.

Install all roof panels with the rough side facing up (painted grid lines side).



✓BEGIN

1

Install (1) 48" x 96" panel.

Use the gauge block to ensure the 3/4" measurement on the rafter (Fig. A), and that the panel is flush at the peak (Fig. B).

Secure the panel with (2) 2" nails in the corners.



Flush at peak

Fig. B

Two Nails

Gauge Block

Fig. A

3/4"
(19 mm)

Flush at peak

Fig. C

Two Nails

Move Gable

9/16"
(1,4 cm)


Gable Trim

Fig. D

1-1/2"
(3,8 cm)


ROOF PANELS

PARTS REQUIRED:

x130  2" (5,1 cm)



3/4" GAUGE
BLOCK



3

Maintain spacing between the center of the rafters (**Fig. E**).

Secure top of panels with (1) 2" nail into each rafter.

Move to the bottom and secure panels with (1) 2" nail into each rafter (**Fig. E**).

4

Secure panel with 2" nails spaced 6" apart on edges and 12" apart inside panel.

5

Install the 8-1/2" x 23-7/8" roof panel flush to installed panel, flush at peak and with the 9/16" measurement at the gable (**Fig. F, Fig. G**).

Move the gable if necessary.

6

Install (2) lower roof panels flush to the upper panels.

Ensure the 23-7/8" x 48" panel is at the 9/16" measurement along the gable trim (**Fig. G**).

Secure the 23-7/8" x 48" panel with 2" nails spaced 6" apart on edges and 12" apart inside panel.


Secure the 8-1/2" x 96" panel to rafters with 2" nails, as shown.

Repeat steps to install roof panels on the opposite side.



Your roof panels are now installed.

Fig. E



Flush
at peak.

Fig. F







Fig. G



DOOR SUPPORT



PARTS REQUIRED:

x1 
5/8 x 3 x 96" (1,6 x 7,6 x 244 cm)

x15  2" (5,1 cm)




1 Install 3" x 96" support flush with bottom edge of top plate and side wall frame.
Secure with 2" nails, as shown.



Your door frame support is now installed.

DOORS

PARTS REQUIRED:




x1 **GAA**
1 x 3 x 5" (2,5 x 7,6 x 12,7 cm)

x1 **OO**
69" (175,3 cm) Door Stiffener

x4 3" (7,6 cm)



x2 1-1/4" (3,2 cm)



✓ BEGIN

- 1 Place doors on flat surface. **3/8" offset is to top.**
Look for red (right) and green (left) on hinge board.

Attach temporary supports **OO** and **GAA** as shown.



DOORS



PARTS REQUIRED:

x1 **OO** Temporary Support
69" (175,3) Door Stiffener

x6 3" (7,6 cm)
x6 2" (5,1 cm)



- 2 Attach temporary support **OO** as a ledger board flush under wall panels for doors to rest on, with (2) 3" screws (**Fig. A**).



- 3 Measure and mark center of door opening. Center doors on mark as shown (**Fig B**).

⚠ Check hinge boards are flush under overhang (**Fig C**).




- 4 Screw hinge boards into top plate and floor with 3" screws.

⚠ Make sure screws go into framing and floor (**Fig. D, Fig. E**).

- 5 Screw hinge boards into studs with 2" screws, as shown.

Remove temporary supports and ledger board. Ensure the doors open properly.




Your doors are now installed.

DOOR TRIM & THRESHOLD

PARTS REQUIRED:





- x1  56" (142,2 cm) **METAL THRESHOLD**
- x10  3/4" (1,9 cm) Bagged separately/ special coating

x38  3/4" (1,9 cm)



✓ BEGIN

- 1 Reinforce the door trim with 3/4" screws through door panel into trim (**Fig. A**).
- 2 Locate screws as shown in **Fig. B**. Use (2) screws at seams.
- 3 Center metal threshold between doors and secure with (10) 3/4" special coating screws into floor as shown (**Fig. C**).




You have installed your door trim and threshold.

DOOR WEATHERSTRIPS

PARTS REQUIRED:



x1 **OO**

69" (175,3) Door Stiffener



✓ BEGIN


- 1 With left door closed, center a weatherstrip **OO** vertically on the left door in the door opening (**Fig A**).
OO will offset the left door 1" (2,5 cm) OUT past the door trim (**Fig B**).
- 2 Secure **OO** with (7) 2" screws through outside trim into **OO** (**Fig B**)
- 3 On right door center **OO** vertically in door opening (**Fig A**). **OO** will offset the right door 1" (2,5 cm) IN from the door trim (**Fig C**).
- 4 Secure **OO** with (7) 2" screws through outside trim into **OO** (**Fig C**).




Your (2) door weatherstrips are now installed.

DOOR HARDWARE

PARTS REQUIRED:



5/16" (0,8 cm) Drill Bit



✓ BEGIN

- 1 Place bolts onto **OO** in open position with bolt ends 3/8" (1 cm) down from frame. Bolt is open when loop is contacting base (**Fig A**).


Mark and pre-drill holes for screws.

- 2 Install bolt with screws supplied and drill 5/16" (0,8 cm) hole deep enough for bolt to slide into.

- 3 Place bolts onto **OO** in open position with bolt ends 1/2" (1,3 cm) up from floor. Bolt is open when loop is contacting base (**Fig B**).

Mark and pre-drill holes for screws.

- 4 Install bolt with screws supplied and drill 5/16" (0,8 cm) hole deep enough for bolt to slide into.



HINT: With door closed extend bolt and tap with hammer to leave a mark in wood for drilling.

Fig. A





Fig. B




Your (2) spring bolts are now installed.


DOOR HARDWARE

PARTS REQUIRED:

x1



x2





✓ BEGIN

- 1 Measure and mark location of hole on outside of right door, as shown.
Pre-drill pilot hole with 1/4" drill.

Pre-drill through hole with 1/2" drill.




Drill hole square to trim to avoid breaking edge of door stiffener.



- 2 Insert handle in hole and secure with 1-1/2" screws.

- 3 Secure inside handle and secure with set screw.




Your T-handle is now installed.

COLLAR TIES

PARTS REQUIRED:

x2 **JF**
1 x 4 x 60" (2,5 x 10,2 x 152,4 cm)





✓ BEGIN

1 Install (2) collar ties **JF** on the two center rafters above the door.

Ensure collar ties are level and flush to roof panels.

Secure collar ties to rafter with three 2" nails at each end.


For best appearance, install collar ties away from view from door (back side of rafters).





FINISH
Your collar ties are now installed.

CORNER TRIM

PARTS REQUIRED:

x8 
3/8 x 1-3/4 x 72" (1 x 4,4 x 182,9 cm)

x56 
2" (5,1 cm)



✓ **BEGIN**

1 Place parts under fascia trim and flush to gable panel cutouts (**Fig.A**).

Secure with 2" finish nails 10" (25,4 cm) apart.

Repeat on each corner of shed.






Fig. A


Flush under
panel cutout.



Flush under
eave fascia trim.



2" (5,1 cm)
Finish nails



Seam is flush. Caulk seam before painting trim.

✓ **FINISH**


Your corner trim is now installed.

WINDOW SHUTTERS

PARTS REQUIRED:

x6 **FF** 19/32 x 2-1/2 x 22-1/2" (1,5 x 6,4 x 63,5 cm)

x4 **KV** 19/32 x 2-1/2 x 8" (1,5 x 6,4 x 20 cm)

x12  1" (2,5 cm)






Build (2) identical shutters.

BEGIN

- 1 Arrange parts primed side-down on floor, as shown.
Flush ends of **FF**.

Secure parts with 1" screws.

Repeat to build your second shutter.




FINISH


Your (2) window shutters are now assembled. Proceed to install your window.

WINDOW & SHUTTER INSTALLATION

PARTS REQUIRED:





x4
1-1/4" (3,2 cm)



✓ **BEGIN**

- 1** Seal window with high-quality exterior-grade caulk.
- 2** Install and secure window with (4) 1-1/4" screws, as shown.
- 3** Mark center of window frame.



WINDOW SHUTTERS


PARTS REQUIRED:

x2 **FA**
19/32 x 2-1/2 x 22-5/8" (1,5 x 6,4 x 57,5 cm)



x12 2" (5,1 cm)


x6 3/4" (1,9 cm)




4 Locate one shutter centered on marks as shown.
Fasten shutter with (1) 2" finish nail at "dot".
(Nail into wall frame inside.)

5 Working from INSIDE of the shed, secure the shutter to wall panel with (3) 3" screws, indicated at "X".


Repeat steps 4 - 5 to install shutter on opposite side.



3/4" Screws
from inside.



6 Install (2) **FA** centered on mark and flush to shutters.
Secure with 2" finish nails.
(Nail into window frame inside.)




Your window and shutters are now installed.

PAINT & CAULK

- NOT INCLUDED -

PARTS REQUIRED:



- Use acrylic latex caulk that is paintable. Caulk at all horizontal and vertical seams, between the trim and walls, and all around the door trim.
- Use a high quality exterior acrylic latex paint. When painting your building, there are a few key areas that can be easily overlooked that must be painted:
 - Bottom edge of all siding and trim
 - Inside of doors and all 4 edges
 - Paint under door trim to match shed color.

Note:


Prime all un-primed exterior wood before painting.
(Follow directions provided by manufacturer.)

ROOF FELT

- NOT INCLUDED -

- Install felt flush to all roof edges overlapping 3". Use minimal amount of roofing nails to hold in place.



OK to overlap at ridge.



DRIP EDGE

- NOT INCLUDED -

- Install drip edge over roof felt on gable side and under roof felt on eave side (**Fig. A**).
- Do not use nails on side of drip edge that hangs over side of building.
- Only nail top of drip edge as shown.



Edge flush
to trim.

Snip bottom side of drip edge and
bend over to other side of roof.


(Follow directions provided by
manufacturer.)

SHINGLES - NOT INCLUDED -

- Follow directions provided by manufacturer and these instructions.



⚠ Familiarize yourself with a 3-Tab Shingle.




⚠ NEVER DRIVE FASTENERS INTO OR ABOVE SEALING STRIPS.

✓ BEGIN

- 1** Install first starter row upside down and color up with a 1" overhang at back and bottom of roof panel. Use (4) nails per shingle.


Starter row must be straight and level all the way across with lower edge of roof deck.

NOTE: If you have installed drip edge install shingles flush to drip edge.




SHINGLES continued...


- 2** Beginning at front of shed, install first row of shingles with notch at 1" past roof edge or flush with drip edge.



- 3** Install second row of shingles flush at top of first row's rain slots. Ensure 1" overhang or flush to drip edge at front, stagger each row.





- 4** Continue installing rows of shingles by staggering at front.




SHINGLES continued...

- 5** Continue installing rows of shingles to the peak. At the peak make sure there is a maximum of 5" or less to the rain slot, as shown below. If shingles overlap at ridge cut to peak with a utility knife.



! • If more than 5" (12,7 cm) to rain slot you must install another row of shingles.

- 6** Repeat steps 1 - 6 to shingle the opposite side of your roof. Trim shingles at ridge.
- 7** Once both sides are shingled you need to trim ends. Strike a chalk line 1" from edge.
- 8** Using your shingle hooked blade carefully cut shingles along chalk line.



You have finished shingling your roof. Proceed to capping the ridge.


SHINGLES - RIDGE CAP



- You will finish off the top of the roof with a ridge cap made from shingles.

✓ **BEGIN**


1 Cut shingles into **THREE** pieces. Hint: Use cut-off pieces first.




Note: • You will need about 24-26 cut pieces.



2 Install first ridge cap flush to shingles at front, as shown.




3 Install second ridge cap 5" back, as shown.




SHINGLES - RIDGE CAP

continued...


- 4 Continue installing ridge cap to back of roof.




- 5 Make sure there is 4" (10,2 cm) between the shingle-color and edge of shingles.



- 6 When you have 4" minimum of shingle color cut one piece to cap your roof.



- 7 Install flush to shingles.



FINISH

You have finished your ridge cap.

16587-A 10' x 8' Order Form

CATEGORY	PART DESCRIPTION	PART SIZE	PART ITEM #	BUILDING QTY.	PART ID
2 X 3	Fascia "A"	LUM SPF 2X3X96 #2&BTR	12115	2	PT
	Fascia "B"	2 X 3 X 22" TOP PLATE	Q 22000000000	2	PRD
2 X 4	Gable Trim	2 X 4 X 56" 22.5"L/S TRIM	O 56002222000	4	MCB
	Rafters	2 X 4 X 54 1/8" 22.5" RAFTER	O 5402222200A	8	NPE
	Gable Connectors	2 X 4 X 14 13/16" 22.5" O/E	O 14132200000	4	CBA
	Studs	2 X 4 X 68" STUD	O 68000000000	18	UM
	Window Framing	2 X 4 X 17"	O 17000000000	2	CCA
	Eave Back Side Top Plate "A"	2 X 4 X 66 3/4"	O 66120000000	2	CDA
	Eave Back Side Top Plate "B"	2 X 4 X 42 3/4" PLATE	O 42120000000	2	CFA
	Eave Door Side Bottom Plate "A"	2 X 4 X 9"	O 09000000000	1	UU
	Eave Door Side Bottom Plate "B"	2 X 4 X 44 1/2" PLATE	O 44080000000	1	STL
	Eave Front Top Plate "A"	2 X 4 X 80-1/2" STUD	O 80080000000	1	CGA
2 X 6	Double Top Plate "A"	LUM WSPF 2X6X96 #1 PREMIUM PET	12416	2	VX
	Double Top Plate "B"	2 X 6 X 21 1/4" DOUBLER	N 21040000000	2	CR
2 X 4 TREATED FLOOR FRAME	Floor Bond "A"	2 X 4 X 92-1/2 #2&BTR	P 92080000000	2	---
	Floor Bond "B"	2 X 4 X 24 #2&BTR	P 24000000000	2	---
	Floor Joist	LUM TRTD 2 X 4 X 93 #2&BTR	P 93000000000	6	---
1 X 3 PINE	Gauge Block	1 X 3 X 5" PINE FILLER	U 05000000000	1	GAA
1 X 4 PINE	Collar Tie	1 X 4 X 60" PINE COLLAR TIE	T 60000000000	2	JF
7/16 OSB	Large Upper Roof Panel	OSB 7/16" x 4' x 8'	11110	2	---
	Large Lower Roof Panel	7/16" OSB 23 7/8" X 48" ROOF &	C 48002314000	2	---
	Small Lower Roof Panel	7/16" OSB 8-1/2" X 96" PANEL	C 96000808000	2	---
	Small Upper Roof Panel	7/16" OSB 8-1/2" X 23 7/8"	C 23140808000	2	---
5/8 OSB	Over Door Stiffener	*5/8" OSB 3" X 96" DOOR	E 96000300000	1	---
GUSSETS	Gusset	EZ8"/OSB 6" X 24" GUSSET 22.5"	J 24000600225	8	---
NO GROOVE SIDING	Front Wall Panel "A"	3/8" NG 12 1/2" X 72"	K 72001208000	1	---
	Front Wall Panel "B" Window opening	3/8" NG 48" X 72" FRONTWALL W	K 72004800310	1	---
	Back Wall Panel "A"	3/8" NG 46 1/8" X 72" PANEL	K 72004602000	2	---
	Back Wall Panel "B"	3/8"NG 23 7/8" X72" PANEL OR	K 72002314000	1	---
	Side Wall Panel	SIDING NGSE 3/8X4'X6'	11509	4	---
	Corner Trim	3/8" NG 1 3/4" X 72"	K 72000112000	8	---
	Gable Panel Center	3/8" NG 23-5/8" X 47-5/8"	K 4710231000A	2	---
	Gable Panel wing RIGHT	3/8" NG 15 7/16" X 26 1/8" RGT	K 26021507100	2	---
	Gable Panel wing LEFT	3/8" NG 15 7/16" X 26 1/8" LFT	K 26021507200	2	---
19/32 X 3 SMART TRIM	Horizontal Door Rails	19/32 TST 2 1/2" X 22 5/8"	UT22100208000	2	FA
	Shutter horizontal brace	19/32 TST 2 1/2" X 8"	UT08000208000	4	KV
	Vertical Window Trim	19/32 TST 2 1/2" X 22 1/4"	UT22040208000	6	FF
PURCHASED COMPONENTS	Door Stiffener	LSL 1-1/4 X 2-1/4 X 69 PET	12715	2	OO
	Fixed Window	WINDOW 16-3/4X21-3/4 TRANSOM	15284	1	---
	Threshold	THRESHOLD 7/8" X 1-1/2" X 55-7/8	15419	1	---
	Hardware Kit	H/K 8 X 8 W/ 12 SQ WINDOW	15770	1	---
	Black T-Handle	HANDLE - T 5-1/2" SHAFT & "D"	15375	1	---
	2" 6d Nails	NAIL 6D 2" BOX HDG BOX	15105	4	---
	3" 10d Nails	NAIL 10D 3" BOX HDG BOX	15109	2	---
PACKAGING	Instructions		16587-A	1	---
Right Door Assembly	30189-RA				
	Door Panel	3/8" NG 27-3/8" X 71-1/2" DOOR	K 7108270600A	1	---
	Right Hinge Assembly	HINGE RIGHT (RED) 19/32x3 THIN TRIM	30121-TT	1	---
	Vertical Door Stiles	19/32 TST 2 1/2" X 71 5/8"	UT71100208000	1	GY
	Horizontal Door Rails	19/32 TST 2 1/2" X 22 5/8"	UT22100208000	3	FA
Left Door Assembly	30189-L				
	Door Panel	3/8" NG 27-3/8" X 71-1/2" DOOR	K 71082706000	1	---
	Left Hinge Assembly	HINGE LEFT (GREEN) 19/32x3 THIN TRIM	30131-TT	1	---
	Vertical Door Stiles	19/32 TST 2 1/2" X 71 5/8"	UT71100208000	1	GY
	Horizontal Door Rails	19/32 TST 2 1/2" X 22 5/8"	UT22100208000	3	FA

WARRANTY REGISTRATION

Please complete your warranty registration to properly validate your warranty.

Register your product online at: www.OnlineWarranty.net.

LIMITED CONDITIONAL WARRANTY*

Backyard Storage Solutions, LLC warrants the following:

1. Every product is warranted from defects in workmanship and manufacturing for 1 year.
2. All accessories, hardware and metal components are warranted for 2 years.
3. All Oriented Strand Board (OSB) is warranted for 2 years
4. Siding and Trim is warranted for 10 years.
5. Solar Shed windows are warranted for 1 year.
6. Cedar lumber is warranted for 15 years.
7. Preserved Pine is warranted for 10 years.

Backyard Storage Solutions, LLC will repair, replace or pay for the affected part. In no event shall Backyard Storage Solutions, LLC pay the cost of labor or installation or any other costs related thereto. All warranties are from date of purchase. If a cash refund is paid on an affected part, it will be prorated from the date of purchase.

CONDITIONS

The warranty is effective only when:

1. The unit has been erected in accordance with the assembly instructions.
2. The unit has been properly shingled and painted or stained and reasonably and regularly maintained thereafter.
3. The failure occurs when the unit is owned by the original purchaser.
4. Backyard Storage Solutions, LLC has received the warranty registration card within thirty (30) days of purchase and notification of the failure in writing within the warranty period specified above.
5. Backyard Storage Solutions, LLC has had reasonable opportunity during the sixty (60) days following receipt of notification to inspect and verify the failure prior to commencement of any repair work.

REQUIREMENTS

Storage Buildings

To validate your warranty, it is necessary to properly maintain your Backyard Storage Solutions, LLC unit; shingle the roof and paint or solid-colored stain the siding using quality, 100% acrylic latex exterior product with a minimum of two (2) coats within thirty (30) days of assembly; caulk above all doors and all horizontal and vertical trim boards; paint and seal all exposed edges, sides and faces of siding/trim and OSB siding to include all exterior walls and all sides and all edges of doors.

Gazebos & Pergolas

To validate your warranty, it is necessary to properly maintain your Backyard Storage Solutions, LLC unit. This includes treating all of the exposed cedar and pine surfaces on your gazebo or pergola structure with an exterior grade wood preservative, an exterior oil-based semi-transparent stain, an acrylic latex exterior paint or an acrylic latex solid color exterior stain within 30 days of assembly and as needed thereafter to maintain your warranty.

Keep vegetation trimmed away from building and make sure siding panels and trim do not come in contact with masonry or cement. The minimum ground clearance for siding must be one half inch ($\frac{1}{2}$ inch) from concrete slab or two and one half inches ($2\frac{1}{2}$ ") from the ground when building is erected or constructed on a treated wood floor kit. Water from sprinklers must be kept off unit. In no event will Backyard Storage Solutions, LLC be responsible for any indirect, incidental, consequential or special damages nor for failure(s) that are caused by events, acts or omissions beyond our control including, but not limited to, misuse or improper assembly, improper maintenance (which eventually leads to rot or decay) and acts of God. Backyard Storage Solutions, LLC will not be held responsible for any labor costs incurred to construct your unit.

This warranty gives you certain specific rights that vary from state to state.

CLAIM PROCEDURE

To make a claim under this warranty, you can either call 1-888-827-9056 or email: customerservice@backyardproducts.com. Please have ready the information below when you call or include the information in your email:

1. The model and size of the product.
2. A list of the part(s) for which the claim is made.
3. Proof of purchase of the Backyard Storage Solutions, LLC item, as shown on the original invoice.
4. Run code: found on exterior product label or assembly instructions enclosed in the product package.

All other inquiries can be mailed to:

Backyard Storage Solutions, LLC
Attn: Customer Service
1000 Ternes
Monroe, MI 48162

***WARRANTY TERMS MAY VARY OUTSIDE THE U.S.A.**

IMPORTANT: This is your warranty certificate.