Compact Vacuum Laser Level, Red



The Red Compact Vacuum Laser Level utilizes vacuum suction technology and an EPDM foam seal for secure, damage-free mounting on different surfaces, including rough walls. High-visibility red lasers project precise lines up to 40 feet, even in low-light conditions. A central viewing window and LED bubble vials improve visibility and accuracy. Features a class 3R laser (IEC 60825-1 Ed. 3.) with an output power of less than or equal to 5 mW at 635+/- 10nm for reliable, professional-quality results.

Specifications

Type:	Line Generator Laser Level	**Application:**	Laser Alignment
Special Features:	Damage-Free Vacuum Suction Mount for Secure Hold on Any Surface	**Material:**	PC+ABS+TPE
Batteries:	2 x AA	**Laser Wavelength:**	635+/- 10nm
Laser Safety:	21 CFR 1040.10 and 1040.11 Except for Conformance with IEC 60825-1 Ed. 3., as Described in Laser Notice No. 56, Dated May 8, 2019	**Number of Beams:**	2
Laser Color:	Red	**Laser mW:**	?5mW
Laser Class:	Class 3R	**Plumb Laser:**	No
Indoor Range:	40' (12.19 m)	**Maximum Distance (Feet):**	40
Maximum Distance (m):	12.2	**Number of Vials:**	2
Type of Vials:	Bubble	**Accuracy:**	Single Beams: ± 0.31'' at 20' (±8mm at 6m); Both Beams: ± 0.47'' at 20' (±12mm at 6m)
Pulse Mode:	No	**Receiver:**	No
Drop Protection:	6.5' (2 m)	**Transit Locking Mechanism:**	No
Low Battery Alarm:	No	**Low Battery Indicator:**	Yes
Out-of-Level Indicator:	No	**Standard:**	Complies with 21 CFR 1040.10 and 1040.11 Except for Conformance with IEC 60825-1 Ed. 3, as Described in Laser Notice No. 56, Dated May 8, 2019
Mounting Type:	Vacuum Suction	**Included:**	Laser Level, Batteries
Overall Length (Inch):	4.22	**Overall Length (cm):**	10.7
Overall Height (Inch):	1.91	**Overall Height (cm):**	4.9
Overall Width (Inch):	1.47	**Overall Width (cm):**	3.7
Weight (lb):	0.525	**Weight (kg):**	0.2
Battery Life:	6 hr		