KOHLER_®

Prosa[™] The Complete Solution[®] one-piece elongated toilet, 1.28 gpf **K-46126**

Features

- One-piece toilets integrate the tank and bowl into a seamless, easy-to-clean design
- Elongated bowl offers added room and comfort
- Comfort Height[®] feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 1.28 gpf (4.8 lpf)
- The Complete Solution toilets provide everything you need, including bowl, tank, seat, wax ring, and hardware
- Quiet-Close™ lid and seat prevents slamming
- Left-hand Polished Chrome trip lever
- 2-1/8" (54 mm) fully glazed trapway
- Precision-engineered patented tank, bowl, and trapway create strong siphon during flushing
- AquaPiston[®] canister optimizes the flow out of the tank, harnessing gravity and the natural powerful reducing cascade of water to increase the power and effectiveness of the flush
- Easy-to-flush canister design requires less force to actuate than a 3" (76 mm) flapper, and has 90% less exposed seal material which resists conditions that cause wear, tear, shrinkage and swelling

Installation

- Standard 12" (305 mm) rough-in
- Supply line sold separately





ADA CSA B651 OBC

Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER[®] Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color Code Description

0 White





The Complete Solution® one-piece elongated toilet, 1.28 gpf K-46126



Technical Information

Rim to water surface:

Seat-mounting holes:

Rough-in:

All product dimensions are nominal.	
Toilet type:	Floor-mount
Waste Outlet:	Floor
Flush type:	AquaPiston
Trap passageway:	2-1/8" (54 mm)
Water surface size:	11" x 7-3/4" (279 mm x 197 mm)

6-1/16" (154 mm)

12" (305 mm)

5-1/2" (140 mm)

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.



Prosa™