Recreate the elegant look of marble and stone and add a touch of elegance and natural beauty to any space.

SWEDENTM Glazed Porcelain



FLOOR / WALL

RESIDENTIAL

COMMERCIAL







Vadret

Sizes	24"x24" 23,62"x23,62"	12"x24"	3"x12" Floor SBN				
Thickness	8.2mm	8.2mm	9mm				
Faces	6	20	N/A				
Finish	Polished	Polished	Polished				
Edge	Rectified	Rectified C	Cut/Rounded				
Grout Joint ecommendation	3/16"	3/16"	3/16"				
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A137.1	Scratch Hardness MOHS	Shade Variation Rating
Results*	III	>350 lbf	Resistant	<0.50%	<0.42	3	V ₂

Product and Installation Details | ANSI A108.02 Section 4.3.8.2 - For running bond/brick joing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



Ded List Free

- .
- Product Packaging is 100% recyclable