ELECTRIC WALL OVEN INSTALLATION INSTRUCTIONS

(and Optional Electric or Gas Cooktop Combination)

INSTALLATION AND SERVICE MUST BE PERFORMED BY A QUALIFIED INSTALLER.
IMPORTANT: SAVE FOR LOCAL ELECTRICAL INSPECTOR'S USE.
READ AND SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE.

լ (Սլ՝

United States

and Canada

WARNING FOR YOUR SAFETY: Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.

Your new wall oven has been designed to fit a limited variety of cutout sizes to make the job of installing easier. The first step of your installation should be to measure your current cutout dimensions and compare them to the cutout dimensions chart below for your model. You may find little or no cabinet work being necessary.

! WARNING Do not remove spacers (if equipped) on the side walls of the built-in oven. These spacers center the oven in the space provided. The oven must be centered to prevent excess heat buildup that may result in heat damage or fire.

NOTES:

- 1. Base must be capable of supporting 150 pounds (68 kg) for 27" models and 200 pounds (90 kg) for 30" models.
- 2. Allow at least 21" (53.3 cm) clearance in front of oven for door depth when it is open.
- Dimension G (cutout depth) is critical to the proper installation of the built-in oven. If the oven decorative trim does not butt against the cabinet, or if noise is heard on convection models, verify dimension G to assure it is the required depth.
- 4. For a cutout height greater than 28¹/8" (71.4 cm) add one 2"(5 cm) wide wood shim of appropriate height to each side of the opening under the appliance side rails.
- 5. 30" MODELS ONLY: For a cutout height (H) greater than 28⁵/s" (72.7 cm) you can order a larger bottom trim through a Service Center.

Min. Hole for Cord H B 27 1/4" (69.2 cm) 3" (7.6 cm) 31"* (78.7 cm) Door Open Spacer (see note 2) (5.1 cm) Min. Electrical Junction Box 2" (5 cm) Wide Wood Spacer if Needed

1½" (3.8 cm)

* Suggested distance from floor is 31" (78.7cm). Minimum required distance is 4 ½" (11.4cm).

Figure 1
27" and 30" Single Wall Ovens (Double ovens see Figure 2)

					• ,	
PRODUCT DIMENSIONS						
MODEL	А		В	С		D
27" (68.6 cm) Wall Oven	27 (68.6)		29 (73.7)	24 ⁵ / ₈ (62.5)		24¾ (62.9)
30" (76.2 cm) Wall Oven	30 (76.2)		29 (73.7)	28¼ (71.8)		24¾ (62.9)
CUTOUT DIMENSIONS AND CABINET WIDTH						
	F		G (Min.)	H. Standard Height (**Others, see notes 4 & 5)		I
MODEL	Min.	Max.		Min.	Max.	
27" (68.6 cm) Wall Oven	24 ⁷ / ₈ (63.2)	25¼ (64.1)	23½ (59.7)	27¼ (69.2)	285/8 (72.7)	27 ¹ / ₈ (68.9) Min
30" (76.2 cm) Wall Oven	28½ (72.4)	29 (73.7)	23½ (59.7)	27¼ (69.2)	285/8 (72.7)	30 ¹ / ₈ (76.5) Min