

# Hisense

**34 PINTS**  
DOE Test Procedure,  
10 CFR part 430, subpart B,  
appendix X

**50 PINTS**  
DOE Test Procedure,  
10 CFR part 430, subpart B,  
appendix X

DEHUMIDIFIER AUTO DRY  
up to 1000 sq.ft. coverage

**DH5019K1G**



- Bucket full indicator avoids overflows
- 3 Modes - Auto, Continuous, Manual
- 2 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38°F)



#### Low Noise Airflow System

High-performance centrifugal fan ensures quiet operation, achieving just 46 dB(A) with the fan set on "Low".



#### Energy Efficient

Energy efficient and helps reduce your utility bill.



#### Filter Indicator

Washable filter helps to reduce bacteria, odors and particles.



#### Warranty

2 Years Parts & Labor.

## Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH5019K1G 50\* Pint 2-Speed Dehumidifier quietly collects water into the slide-out internal bucket, or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Three operating modes (manual set, continuous and auto dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

# Hisense



DEHUMIDIFIER AUTO DRY  
up to 1000 sq.ft. coverage

**DH5019K1G**

## TECHNICAL SPECIFICATIONS

Performance	
Hisense-Model	DH5019K1G
Dehumidification (Pints / 24 hours)	50*
Dehumidification (Pints / 24 hours)	34**
Heating Capacity	N/A
Coverage	Up to 1000 sq. ft.
Refrigerant	R-410A
Noise Level in dB(A)	46-48 dB(A)
Electrical	
Voltage / Freq / Amps	115V / 60Hz. 4.5A* / 3.6A**
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% ~ 80%
Timer-Clock	Yes
Fan Speeds	2 Speeds (Lo. Hi. Auto)
Pump Mode	No
General Features	
Auto Bucket Shutoff	Yes
Bucket Capacity	11.4 pints
Bucket Shutoff Capacity	9.1 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	N/A
Accessories	
Quick Connect Hose	No
Approvals	
Safety	UL
Energy Star	No
Shipping	
Unit Dimension WxDxH (mm)	356 x 273 x 507
Carton Dimension WxDxH (mm)	405 x 335 x 535

Net Weight / Gross Weight (Kg)	15.5 / 17.4
Unit Dimension WxDxH (inch)	14 x 10.7 x 20.0
Carton Dimension WxDxH (inch)	15.9 x 13.2 x 21.1
Net Weight / Gross Weight (lbs)	34.1 / 38.3
Loading (40HQ)	1020
Loading (53')	1008 (floor loaded)
Product	
Parts & Labor	2 years
UPC	00819130023663

Note:

\* : DOE Test Procedure 10 CFR part 430, subpart B, appendix X;

\*\* : DOE Test Procedure 10 CFR part 430, subpart B, appendix X1;



Control Panel



Gravity Draining with Garden Hose (not included)

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2019 Hisense USA. All rights reserved

Hisense USA Corporation  
7310 McCinnis Ferry Road, Suwanee, GA, 30024  
1-877-465-3566  
www.hisense-usa.com

