
Specifications and Warranties

General:

Description:	Textured loop pile carpet tile
Dye Method:	Injection dyed
Dye Resolution:	400 dpi
Fiber:	BCF Type 6,6 2-Ply Premium Nylon
Total Weight:	89 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/10 th
Pile Height:	.27 in.
Backing:	StayTac® cushion - PVC free. No adhesives required
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion® soil and stain treatment
Antimicrobial Treatment:	Impervion® mold, mildew, and odor protection
Tile Size:	1m x 1m (39.4" x 39.4")
Origin:	U.S.A.

Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified



Flammability:

Radiant Panel:	> 0.45 watts/cm ² (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (CPSC FF-1-70)

Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction.

Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Antimicrobial Protection	Lifetime Color Pattern Permanency
Lifetime Soil and Stain Protection	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	Lifetime Edge Ravel
Lifetime Moisture Resistance	

Specifications are subject to normal manufacturing tolerance.
Sizes are approximate and actual carpet color may vary.

Main Street

Fiber: 100% Premium Nylon

Gauge: 1/10th

Total Weight: 89 oz. sq/yd

Tile Size: 1m x 1m