

**Model 73B UL Listed Wire Combinations Strip Solid Wire #16 and smaller 3/8 in., all others 5/16 in.
UL File Number E5238**

Copper to Copper wire only (do not use on aluminum).



For use with solid or stranded combinations

300 Volt Maximum		600 Volt Maximum	
3 or 4 #16	3 #16 w/1 #18	1 or 2 #14	2 #16 w/1 to 3 #22
5 #18	3 #16 w/1 or 2 #20 or #22	1 #16 str.	2 #16 w/1 #18
3 to 5 #20	4 #16 w/1 #20 or #22	2 #16	1 or 2 #16 w/1 #20 w/1 #22
5 #22	1 #18 w/1 #20	1 #18 str.	1 #16 w/1 #18 w/1 #22
1 #14 w/2 #16	1 #18 str. w/5 #22 str.	2 or 4 #18	1 #18 w/2 to 4 #20
1 #14 w/1 #16 w/1 #18	2 #18 w/3 #22	1 #14 w/1 or 2 #18	1 #18 w/ 3 or 4 #22
1 #14 w/3 #18	3 #18 w/2 #20 or #22	1 #14 w/1 to 3 #20	1 or 2 #18 w/1 #20 w/1 #22
1 #14 w/4 #20	4 #18 w/1 #20 or #22	1 #14 w/1 to 3 #22	2 #18 w/1 or 2 #20
2 #14 w/1 #18	1 #20 w/4 #22	1 #14 w/1 #16 w/1 #18	2 #18 w/1 to 3 #22
2 #14 w/1 to 3 #20 or #22	2 #20 w/2 or 3 #22	1 #14 w/1 #16	3 #18 w/1 #20 or #22
1 #16 w/4 #18	3 #20 w/1 or 2 #22	1 #16 w/1 or 2 #18	
2 #16 w/2 or 3 #18	4 #20 w/1 #22	1 #16 w/1 to 3 #20 or #22	
2 #16 w/3 #20		2 #16 w/1 or 2 #20	