



2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 1/29/16

DAP[®] ALEX PLUS[®] All Purpose Acrylic Latex Adhesive Caulk Plus Silicone

- All purpose
- Paint in 30 minutes
- Excellent flexibility
- Adheres to a wide variety of surfaces
- Shrinks less for a durable seal*
- 100% waterproof seal
- Easy water clean-up & low odor
- Interior/Exterior
- 40 year
- Exceeds ASTM C834

Packaging: 10.1 fl. oz. (300 mL) cartridge, 5.5 fl. oz. (162 mL) squeeze tube
Colors: White, Antique White, Almond, Slate Gray, Brown, Cedar Tan, Dark Bronze, Black
UPC Numbers: 70798 18128, 70798 18101, 70798 18135, 70798 18110, 70798 18112, 70798 18111, 70798 18109, 70798 18107

Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on “Ask the Expert”
Order Information: 800-327-3339
Fax Number: 410-534-1068
Also, visit the DAP website at www.dap.com

Product Description:

DAP[®] ALEX PLUS[®] ALL PURPOSE ACRYLIC LATEX CAULK PLUS SILICONE is an excellent quality, all purpose caulk for sealing a wide variety of interior and exterior surfaces. It contains silicone additives for greater flexibility and adhesion and shrinks less for a durable, waterproof seal.* **ALEX PLUS[®]** is paintable in just 30 minutes with latex or oil-based paints, saving time. It won't shine through or discolor paint finish for superior paint results. It is easy to apply and tool, low in odor and cleans up easily with water. Cured caulk is mold and mildew resistant. 40 Year Durability. Exceeds ASTM C834. Interior/exterior use.

**When compared to DAP[®]ALEX[®] Painter's Caulk*

Suggested Uses:

Ideal for caulking and sealing:

- Window & door frames
- Baseboards
- Pipes & vents

- Other gaps & cracks

- Molding & trim
- Siding and trim
- Corner Joints

Adheres to:

- *Wood – painted & unpainted*
- *Aluminum & vinyl*
- *Brick & stone*
- *Glass*
- *Drywall*
- *Drywall & plaster*
- *Metal*
- *Concrete & masonry*
- *Most plastics*

- *Stucco*

Performance Characteristics:

- Exceeds ASTM C834
- Contains silicone additives for improved adhesion and flexibility
- Paintable in 30 minutes
- Shrinks less for a durable seal
- Low odor and easy water clean up
- Won't shine through paint
- Resists cracking and chalking
- Tack free in 30 minutes.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old caulk, dirt, dust, grease and debris.
2. Remove cap (from tube).
3. Cut nozzle at 45° angle to desired bead size.
4. If using the cartridge, load into caulk gun.
5. Fill gap or joint with caulk, pushing caulk ahead of nozzle.
6. If necessary, tool or smooth the bead of caulk with a finishing tool for a neat finish.
7. Clean up excess uncured caulk with a damp sponge before it skins over. Cured caulk must be cut or scraped away.
8. Allow caulk to dry at least 30 minutes (longer in cool or humid conditions) before painting with latex or oil-based paints.
9. Reseal cartridge for storage and reuse.

For Best Results:

- Apply in temperatures above 40°F.
- Do not apply when rain or freezing temperatures are forecasted before full cure can occur. Cold weather and high humidity will slow down cure time.
- Do not use below waterline, for filling butt joints, surface defects or tuck-pointing.
- Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material.
- Store caulk away from extreme heat or cold.

Typical Physical & Chemical Characteristics:

Vehicle:	Siliconized Acrylic Polymer
Solids:	83% by weight
Filler:	Calcium Carbonate
Specific Gravity:	1.67
Density:	14.0 lbs./gal.
Volatile:	Water
Flash Point:	None
Service Temperature Range:	-20°F to 180°F
Application Temperature Range:	40°F to 100°F
Tooling Time:	10 minutes
Tack Free Time:	30 minutes
Full Cure Time:	24 hours (@3/16" bead)
Consistency:	Smooth and creamy
Odor:	Very mild
Paintable:	Yes
Freeze Thaw Stability:	Passes 5 Cycles @ 0°C (1 cycle = 16 hrs. @ 0°C, 8 hrs. @ 25° C)
Dynamic Joint Movement:	± 12%
Shelf Life:	12 months

Coverage: 10.1 fl. oz.: 55 linear feet at a 3/16" diameter bead
5.5 fl. oz.: 30 linear feet at 3/16" diameter bead
SDS No: 00010002001

Clean Up & Storage:

Clean up excess uncured caulk with a damp sponge before it skins over. Cured caulk must be cut or scraped away. Clean hands and tools with warm water and soap.

Safety:

Caution! Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Use gloves and safety glasses. **Keep out of reach of children. Do not take internally. Warning:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. In an **emergency**, call your poison control center at 1(800) 222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit **dap.com**. See product label or Safety Data Sheet for additional safety information. You can request an SDS sheet by visiting dap.com or calling 888-DAP-TIPS.

Guarantee:

If product fails to perform when used as directed, within one year of date of purchase, return used container and sales receipt to DAP Products Inc., TCS, 2400 Boston St., Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.