















specifications:

- 1. Visible surface must be smooth and smooth, natural transition.
- 2. Against the wall must be vertical, the other several faces also try to vertical.
- 3. Make sure there is no water in the basin.
- 4. Can Not have acute angle, visible surface of the corner is R=2.
- 5. Positive and negative tolerance: 2mm

						Resine Basine			Taizhou Elsa Sanitary Ware Co. , Ltd.
		Intial relea			Size:750*500*50mm				
Mark		Change co	Change content			Qty	Unit	Proportion	
Design	+		standardization			1	PCS	1	
Revise	9		Check			'	100	_ '	
Technolog	Approve Approve				Total 1 PCS No. 1 PCS				





72"D SINK

84"D SINK

20

20

12

12

Sink Size	Length (from left to right)	Width (from front to back)	Depth (from top to bottom)			center of the drain hole and the back edge of the top	center of the faucet/drain hole and closer side edge of the top	faucet/drain holes (center to center)	Distance between the two basins
			-I	<u> </u>					
24" SINK	18	12	4	1.75	2.35	10.5	12	/	J
30" SINK	18	12	4	1.75	2.35	10.5	15	/	1
36" SINK	18	12	4	1.75	2.35	10.5	17.75	/	/
42" SINK	20	12	4	1.75	2.35	10.5	21	/	1
48" SINK	20	12	4	1.75	2.35	10.5	23.5	/	/
60"S SINK	24	13	5	1.75	2.5	9.25	29.5	/	1
60"SL SINK	20	12	4	1.75	2.35	10.5	14.75	1	1
60"SR SINK	20	12	4	1.75	2.35	10.5	14.75	/	/
60"D SINK	18	12	4	1.75	2.35	10.5	14.75	29.5	11.5

2.35

2.35

Drain Hole: φ 1.75

Distance between the

Distance between the

10.5

10.5

Distance between the

center of the

17.75

21

Distance between two

35.5

41.75

15.75

22

BASIN DIMENSIONS (inch)

Distance between the

1.75

1.75

Faucet Hole: φ 1.2