KOHLER_®

Wellworth® Two-piece round-front toilet, 1.28 gpf K-3997-U

Features

- Two-piece design
- Round-front bowl offers an ideal solution for smaller bathrooms and powder rooms
- Left-hand Polished Chrome trip lever
- Insuliner® tank liner minimizes condensation on the tank
- Combination consists of the K-4467-U tank and the K-4197 bowl
- Coordinates with other products in the Wellworth collection
- KOHLERs canister flush valve harnesses the natural force of gravity and optimizes flushing performance
- Eligible for consumer rebates in some municipalities
- 1.28 gpf (4.8 lpf)
- 2-1/8" (54 mm) fully glazed trapway
- Class Five® canister optimizes the flow out of the tank, harnessing gravity and the natural powerful reducing cascade of water to increase the power and effectiveness of the flush

Installation

- Standard 12" (305 mm) rough-in
- Three-bolt quick-connect installation
- Seat and supply line sold separately

Recommended Products/Accessories

K-5589 Purefresh® Deodorizing round-front toilet seat K-76923 PureWash® M250 Quiet-Close[™] round-front toilet seat with antimicrobial agent K-5420 Low-Profile Bolt Caps K-9379 Trip Lever 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose K-23726 Drain treatment K-4636-RL Cachet® ReadyLatch® Quiet-Close[™] elongated toilet seat

Included Components

K-4197 Round-front toilet bowl K-4467-U Toilet tank, 1.28 gpf





Codes/Standards ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® IAPMO Certification


KOHLER[®] Toilets and Seats Limited Warranty

See website for detailed warranty information.





Wellworth® Two-piece round-front toilet, 1.28 gpf K-3997-U



Technical Information

All product dimensions are nominal.	
Toilet type:	Floor-mount
Waste Outlet:	Floor
Bowl shape:	Round-front
Flush type:	Class Five
Trap passageway:	2-1/8" (54 mm)
Water surface size:	10-1/2" x 7-3/4" (267 mm x 197 mm)
Rim to water	5-1/4" (133 mm)
surface:	
Rough-in:	12" (305 mm)
Seat-mounting	5-1/2" (140 mm)
holes:	

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

