

NEW SPLIT JAW FORK METER

PATENTED TIGHTSIGHT® BOTTOM DISPLAY

MAGNETIC
HANGING STRAP

FREE UP A HAND



SPLIT-JAW DESIGN

19MM JAW OPENING
FITS AROUND 4/O
CONDUCTORS



18MM JAW TINES SLIP
BETWEEN ADJACENT
CONDUCTORS



PROBE HOLDERS

FOR EASE OF
TESTING



FOR LEAD
STORAGE



THE ELECTRICIAN'S
CHAMPION



idealind.com

FORK METER FEATURES AND SPECIFICATIONS



Non-Contact Voltage Indication
Built in Clamp Tip



0.75 in. (19mm) Jaw Opening



Flashlight/Backlight



Probe Storage & Lead Holders
(on back)



Delta Δ
(difference from reference)



Max./Min.



Patented TightSight® Backlit Display eliminates need to bend or twist conductors or place your head near or in the panel and allows you to easily read the bottom display when taking measurements

CLAMP METER SELECTION GUIDE



	61-415
FEATURES	
CAT Rating (Safety)	CAT IV 600V CAT III 1000V
Listing	cULus, CE, RCM
Drop Protection	6.6 ft. (2m)
Clamp/Jaw Opening	0.75 in. (19mm)
AC Voltage (Volts)	1000V
DC Voltage (Volts)	1000V
AC Current (Amps)	200A
DC Current (Amps)	200A
Ohms (Resistance)	60MΩ
AC Millivolts	✓
DC Millivolts	✓
True RMS	✓
High Voltage Alarm	ACV/DCV >30V
Audible Continuity	✓
Visual Continuity	✓
Backlight	✓
NCV	40-600V
Auto Ranging	✓
Range Hold	✓
Data Hold	✓
Relative	✓
Diode Test	✓
Capacitance Test	6.000mF
Max / Min	✓
Magnetic Strap Mount	✓
Test Probe Holder	✓
Flashlight	✓
Auto-Power Off (APO)	✓
APO Disable	✓
Low Battery Indication	✓
Battery Type (Included)	2 x 1.5V AAA
Bottom LCD Display	✓
LCD Display Count	6000
Warranty	2-Year*
ACCESSORIES	
Leads, Case & Batteries	Included

Specifications are subject to change without notice.



IDEAL INDUSTRIES, INC.

IDEAL INDUSTRIES, INC.
1800 S. Prairie Drive, Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA

International offices:
Australia • Canada • China • France • India • Germany • Mexico • UK

For complete sales office contact information, visit us at:
www.idealind.com