- FOR SAFE INSTALLATION AND OPERATION Follow the instructions in the Use and Care Manual provided. A replacement copy may be obtained by writing the manufacturer.
- This appliance must be installed in accordance with the manufacturer's instructions, local codes, utility company requirements, and/or in the absence of local codes, the latest edition of the National Electrical Code.
- FOR YOUR SAFETY DO NOT store or use gasoline or other flammable vapors or liquids in the vicinity of this or any other appliance. Keep rags and other combustibles away.
- CAUTION Hotter water increases the risk of scald injury. See Use and Care Manual for instructions before changing the temperature settings.
- WARNING Any thermostat setting above I25°F may cause severe burns and consume energy unnecessarily.
- Power supply must be shut off before removing access panels prior to adjusting thermostat(s) or resetting temperature limiting control.
- CAUTION Risk of electric shock. Connect branch circuit equipment grounding means to water heater. For detailed information refer to Use and Care Manual. USE COPPER CONDUCTORS ONLY.
- · Tank must be full of water before being energized to avoid damaging the heating element.
- WATER LEAKAGE Regardless of the material from which water heater is constructed, it will at some time leak, due to the corrosive action of water. This water heater must not be located in an area where leakage will result in damage to adjacent area or lower floors. When such area cannot be avoided, it is recommended that a suitable catch pan, adequately drained, be installed under the water heater. See Use and Care Manual.
- WARNING: California law requires that this water heater must be braced, anchored, or strapped to avoid
 falling or moving during an earthquake. See Use and Care Manual for information regarding correct installation
 procedures.
- CALIFORNIA PROPOSITION 65 WARNING: This product contains chemicals known to the state
 of California to cause cancer, birth defects, or other reproductive harm.
- When using this water heater or any electrical appliance use basic safety precautions to reduce risk or fire, electric shock or injury.
- SERVICE Service should be performed by qualified service personnel only. Contact the nearest service facility
 if you are not qualified to service this water heater.
- SUPPLEMENTAL PREHEATED WATER If this water heater receives water from a preheated source such as a solar water heating system then a tempering valve must be installed on the hot water outlet to ensure safe hot water outlet temperatures.

MAX, WORKING PRESSURE 150 PSI