

QUICKLY & EASILY CLEAN MARBLE SURFACES, STONE WALLS, GRANITE COUNTERTOPS & MORE

GT-5 is a pH neutral combination of special chemicals that quickly and easily cleans marble surfaces, stone walls, granite countertops, ceramic, porcelain, Corian, glass and most other hard surfaces. It works great on mirrors and bath and kitchen fixtures. It is not designed to clean heavily soiled areas or remove soap buildup.

DIRECTIONS:

1. Hold sprayer about 6 to 8 inches from the surface.
2. Spray a light mist over the area to be cleaned.
3. Let the product set for approximately 30 seconds.
4. Scrub with a sponge or a light duty pad.
5. Allow to dry. (For best results, buff the surface dry with a clean microfiber towel.)

GREENTOUCH and logo are trademarks of Greentouch USA Inc. in the United States of America and elsewhere.

Distributed by: **Greentouch USA Inc.,**
207-D Byers Creek Rd, Mooresville, NC 28117

www.greentouchhome.com

GT-5

ALL STONE **CLEANER** PLUS

Greentouch[®] Home

MULTI SURFACE CLEANER

STONE, GLASS & MORE

.....

pH
neutral

SAFE FOR
DAILY CLEANING

Step 1

EASY STAIN REMOVAL REMOVES STUBBORN STAINS FROM MOST STONE SURFACES SAFE ON MARBLE, GRANITE & MORE

GT-40 is easy, ready-to-use, and releases no VOCs. It pulls deep-seated oil, dirt, harmful salts, and other embedded stains out of interior sensitive masonry, including limestone, travertine, granite and marble. It is safe to use on most polished stone finishes.

DIRECTIONS:

1. Wet area that you are treating with water.
2. Apply paste to the wet surface 1/8 to 1/4 inches thick using a suitable applicator, like a putty knife.
3. Cover the poultice with plastic wrap and let stay for 12 hours. It will cling to the surface. Press down around the edges.
4. Remove the plastic and allow poultice to dry completely. This is the most important part. As it dries, it will draw the stain from the surface.
5. Remove the poultice and captured contaminants by scraping off the surface. Insert a corrosion-resistant spatula or towel under the paste and carefully lift from the surface. Non-metal tools are preferred to avoid scratching the surface. Remove as much residue as possible.
6. Rinse the surface thoroughly with fresh water, using a sponge or soft cloth.
7. Repeat application if needed.

GREENTOUCH and logo are trademarks of Greentouch USA Inc. in the United States of America and elsewhere.

Distributed by: **Greentouch USA Inc.,**
207-D Byers Creek Rd, Mooresville, NC 28117

www.greentouchhome.com

GT-40

STONE STAIN REMOVER

poultice paste

Greentouch^{Home}

READY TO USE

REMOVES
STUBBORN
STAINS FROM
MOST STONE
SURFACES

Step 2

(If necessary for staining.)

EASY ETCH REMOVAL WITHOUT THE NEED OF POWER TOOLS

GT-11 is designed to restore the finish on polished stone surfaces damaged by chemical etching (commonly called water marks). To remove colored stains use GT-40 poultice paste. Be certain to test product first on a spare tile or inconspicuous area for extra cautions before use.

DIRECTIONS:

1. Apply approximately $\frac{1}{8}$ teaspoon of powder to the dull spot to be restored. Using a spray bottle, gently spray (prevent splattering) a mist of water over the powder making sure all the powder is moistened. If you do not have a spray bottle, you can pour a few drops of water onto the powder from a cup. The mixture should be a wet paste consistency similar to hand lotion.
2. Using a clean, slightly moistened white piece of cotton cloth (a washcloth will do fine), rub until the area treated is dry. This will require some pressure while rubbing to ensure the etch is being removed.
3. To finish with a "professional touch", spray a bit more water to the area being treated, then using the same part of the cloth with product residue, rub in circles (with a little pressure). Then use a fast back and forth motion (with more pressure) until the stone surface is dry and shiny. This will make a perfect blend.
4. Repeated applications may be needed to completely remove the etch & blend with surrounding areas.
5. To eliminate any residue, spray a little GT-5 spray cleaner, then rub it dry.

GREENTOUCH and logo are trademarks of Greentouch USA Inc. in the United States of America and elsewhere.

Distributed by: **Greentouch USA Inc.,**
207-D Byers Creek Rd, Mooresville, NC 28117

www.greentouchhome.com

GT-11

MARBLE ETCH REPAIR POWDER

for easy touch up

Greentouch[®] Home

FORMULATED
FOR:
POLISHED MARBLE,
TRAVERTINE & OTHER
CALCITE BASED
STONES

- Easy to apply
- Works best on lighter stones

Step 3

(If necessary for *etching*.)

Greentouch All Natural Stone Sealer is a formidable water-based penetrating sealer for all porous natural stone, slate and grout.

DIRECTIONS:

1. Read the safety data sheet completely before use.
2. Make sure surface is dry and free from soils, waxes, sealers, and/or coatings.
3. Generously apply an even coat of the stone sealer on the surface being treated using a lambswool applicator, paint brush, low pressure sprayer, or spray bottle.
4. Allow sealer to soak into the stone's surface for up to 30 minutes. Stone surfaces will have different rates of porosity. If the sealer absorbs into the surface in under 10 minutes, multiple applications will be needed. Repeat the process until the sealer stays on the surface for more than 15 minutes.
5. **DO NOT ALLOW EXCESS SEALER TO DRY ON THE SURFACE.** After the stone sealer has remained wet on the stone surface for approximately 20 minutes, you must remove all sealer and residue from the surface with a dry cloth or towel.
6. Should any residue be left or dried on the surface, you may be able to remove it by applying a light coat of sealer to the affected area and buff it off using a clean cloth.
7. We recommend that you complete the first application of the entire surface in manageable sections, so the sealer does not dry on the surface. For countertops, we recommend working 7-8 linear foot sections. For floors, 50-100 square foot sections. Complete one section and then overlap the following section using step 3-5 until the entire surface has been sealed. At this point all excess sealer and residue should have been removed from the first application. Perform a second application, if needed.
8. All stone surfaces are different, maximum stain protection is after sealer has fully cured. This takes 24 to 36 hours. When properly applied and cared for, GT-24 all natural stone sealer will protect for 3 to 5 years.

GREENTOUCH and logo are trademarks of Greentouch USA Inc. in the United States of America and elsewhere.

Distributed by: **Greentouch USA Inc.,**
207-D Byers Creek Rd, Mooresville, NC 28117

www.greentouchhome.com

GT-24

ALL NATURAL **STONE SEALER**

seals & protects

Greentouch[®] Home

**FORMULATED
FOR:**

ALL NATURAL STONE,
UNGLAZED TILE
& CONCRETE

• • • • •

EASY TO APPLY

**ON FLOORS
& COUNTERTOPS**

STEP 4

(If necessary *after water test*)

PENETRATES, ENHANCES, PROTECTS, SMOOTHS AND BEAUTIFIES ALL POLISHED STONE SURFACES.

Creates a protective shield that repels water, reduces finger print marks, and makes routine cleaning easier! Visually restore shine to slightly worn-down surfaces to like-new condition! Terrific for polished stone countertops and shower enclosures. DO NOT USE ON FLOORS. SHAKE WELL BEFORE USE.

DIRECTIONS:

1. Clean the stone surface thoroughly using our ALL STONE CLEANER.
2. Once the stone surface is clean and dry spray the ALL STONE POLISH sparingly across the entire surface.
3. Buff surface to a dry streak free uniform finish using a clean non-colored piece of terrycloth or microfiber towel. If you notice some smearing occurring stop buffing, wait for another minute or so then buff again with a clean terrycloth or microfiber towel. If streaking persists, spray a little more product on and buff immediately to blend.
4. When first used, a repeat application may be called for.
5. ALL STONE POLISH may need to be reapplied in a few days or a few weeks according to the intensity of use of the surface on which the product is applied. CONTAINS FOOD GRADE EMULSIFIERS.

GREENTOUCH and logo are trademarks of Greentouch USA Inc. in the United States of America and elsewhere.

Distributed by: **Greentouch USA Inc.,**
207-D Byers Creek Rd, Mooresville, NC 28117

www.greentouchhome.com

GT-13

ALL STONE POLISHING SPRAY

Greentouch[®] Home

WORKS GREAT ON

POLISHED STONE
& STAINLESS STEEL



REDUCES FINGER
MARKS

SHINES & PROTECTS



STEP 5